than those prescribed in paragraph 2.1 above.
RESOLUTION MSC.570(109) (adopted on 6 December 2024)
PERFORMANCE STANDARDS FOR A UNIVERSAL
SHIPBORNE AUTOMATIC IDENTIFICATION SYSTEM (AIS)

SOURCE: MSC.570(109).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.570(109).pdf
RESOLUTION MSC.570(109) (adopted on 6 December 2024)
PERFORMANCE STANDARDS FOR A UNIVERSAL
SHIPBORNE AUTOMATIC IDENTIFICATION SYSTEM (AIS)

ANNEX

PERFORMANCE STANDARDS FOR
A UNIVERSAL SHIPBORNE AUTOMATIC IDENTIFICATION SYSTEM (AIS)

1 Scope

1.1 These performance standards specify the requirements for the universal AIS.

1.2 The AIS should improve the safety of navigation by assisting in the efficient navigation of ships, protection of the environment, and operation of vessel traffic services (VTS), by satisfying the following functional requirements:

.1 in a ship-to-ship mode for collision avoidance;

.2 as a means for littoral States to obtain information about a ship and its cargo; and

.3 as a VTS tool, i.e. ship-to-shore (traffic management).

1.3 The AIS should be capable of providing to ships and to competent authorities
---
SOURCE: MSC.570(109).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.570(109).pdf
.3 as a VTS tool, i.e. ship-to-shore (traffic management).

1.3 The AIS should be capable of providing to ships and to competent authorities information from the ship, automatically and with the required accuracy and frequency, to facilitate accurate tracking. Transmission of the data should be with the minimum involvement of a ship's personnel and with a high level of availability.

1.4 The installation, in addition to meeting the requirements of the Radio Regulations, applicable ITU -R Recommendations and the general requirements as set out in resolution A.694(17), should comply with the following performance standards.

2 Functionality

The system should be capable of operating in a number of modes:

.1 an "autonomous and continuous" mode for operation in all areas. This mode should be capable of being switched to/from one of the following alternate modes by a competent authority;

.2 an "assigned" mode for operation in an area subject to a competent authority

---

SOURCE: MSC.570(109).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.570(109).pdf

modes by a competent authority;

.2 an "assigned" mode for operation in an area subject to a competent authority responsible for traffic monitoring such that the data transmission interval and/or time slots may be set remotely by that authority; and

.3 a "polling" or controlled mode where the data transfer occurs in response to interrogation from a ship or competent authority.

3 Capability

3.1 The AIS should comprise:

.1 a communication processor, capable of operating over a range of maritime frequencies, with an appropriate channel selecting and switching method, in support of both short- and long-range applications;

.2 a means of processing data from an electronic position -fixing system which

---

SOURCE: MSC.570(109).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.570(109).pdf
Annex 23, page 3
I:\MSC\109\22\MSC 109-22-Add.1.docx

.2 a means of processing data from an electronic position -fixing system which provides a resolution of one ten-thousandth of a minute of arc and uses the WGS-84 datum;

.3 a means to automatically input data from other sensors meeting the provisions as specified in paragraph 6.2;

.4 a means to input and retrieve data manually;

.5 a means of error checking the transmitted and received data; and

.6 built-in test equipment (BITE).

3.2 The AIS should be capable of:

.1 providing information automatically and continuously to a competent

authority and other ships, without involvement of ship's personnel;
.2 receiving and processing information from other sources, including that from a competent authority and from other ships;
.3 responding to high -priority and safety -related calls with a minimum delay; and
.4 providing positional and manoeuvring information at a data rate adequate to
---
SOURCE: MSC.570(109).pdf
URL: https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.570(109).pdf
and
.4 providing positional and manoeuvring information at a data rate adequate to facilitate accurate tracking by a competent authority and other ships.
4 User interface
To enable a user to access, select and display the information on a separate system, the AIS should be provided with an interface conforming to an appropriate international marine interface standard.
5 Identification
For the purpose of ship and message identification, the ship's Maritime Mobile Service Identity (MMSI) should be used.
6 Information
6.1 The information provided by the AIS should include:
.1 Static:
- IMO number1
- Call sign and name
- Length and beam
- Type of ship
- Location of position -fixing antenna on the ship (aft of bow and port or starboard of centreline)
1 In accordance with IMO ship identification number scheme adopted by the Organization (resolution A.1117(30)). If not required to have an IMO number, an official flag State number may be used
---
SOURCE: MSC.570(109).pdf
URL: https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.570(109).pdf
(resolution A.1117(30)). If not required to have an IMO number, an official flag State number may be used
(refer to Recommendation ITU-R M.1371 for the entry of an official flag State number).

.2 Dynamic:
- Ship's position with accuracy indication and integrity status
- Time in UTC 2
- Course over ground
- Speed over ground
- Heading
- Navigational status (e.g. NUC, at anchor, etc. - manual input)
- Rate of turn (where available)
- Optional - Angle of heel (where available)3

- Optional - Pitch and roll (where available)3
.3 Voyage-related:
- Ship's draught
- Hazardous cargo (type)4
- Destination and ETA (at master's discretion)
- Optional - Route plan (waypoints)3
.4 Short safety-related messages
.5 Equipment Identification message5

SOURCE: MSC.570(109).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.570(109).pdf
- Optional - Route plan (waypoints)3
.4 Short safety-related messages
.5 Equipment Identification message5
6.2 Information update rates for autonomous mode
The different information types are valid for a different time period and thus need a different update rate:
- Static information: Every 6 minutes and on request
- Dynamic information: Dependant on speed and course alteration according to table 1
- Voyage-related information: Every 6 minutes, when data has been amended and on request
- Safety-related message: As required
2 Date to be established by receiving equipment.
3 Field not provided in basic message.
4 As required by a competent authority.
5 The AIS equipment should broadcast a unique manufacturer equipment identification number, which should also be physically marked on the equipment.

SOURCE: MSC.570(109).pdf