Precautions
Appropriate precautions shall be taken to protect machinery and accommodation spaces from the dust of the cargo. Bilge wells of the cargo spaces shall be protected from ingress of the cargo. Due consideration shall be given to protect equipment from the du st of the cargo.

SOURCE: MSC.575(110).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.575(110).pdf
cargo. Due consideration shall be given to protect equipment from the du st of the cargo.
Persons who may be exposed to the dust of the cargo shall wear protective clothing, goggles or other equivalent dust eye -protection and dust filter masks, as necessary. Bilge wells shall be clean, dry and covered, as appropriate, to prevent ingress of the cargo.
Ventilation
The cargo spaces carrying this cargo shall not be ventilated during the voyage
Carriage
The appearance of the surface of this cargo shall be checked regularly during the voyage. If free water above the cargo or fluid state of the cargo is observed during the voyage, the master shall take appropriate action to prevent cargo shifting and potential capsize of the ship and give consideration to seeking emergency entry into a place of refuge.
Discharge
No special requirements.
Clean-up
After discharge of this cargo, the bilge wells and the scuppers of the cargo spaces shall be
---
SOURCE: MSC.575(110).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.575(110).pdf
Discharge
No special requirements.
Clean-up
After discharge of this cargo, the bilge wells and the scuppers of the cargo spaces shall be checked and any blockage in the bilge wells and the scuppers shall be removed."
RESOLUTION MSC.575(110) (adopted on 26 June 2025)
AMENDMENTS TO THE INTERNATIONAL MARITIME SOLID
BULK CARGOES CODE (IMSBC CODE)

"ASPHALT GRANULATES
Description
Granulates from the demolition of asphalt roads. The granulates are re -used for the foundation/sub-base for new roads. The cargo has a dark grey/black colour and contains no more than 10% asphalt. The material has, in principle, no odour, but a light bitumen odour may be possible. The cargo is stored outside (open air).
Characteristics
Physical properties
Size Angle of repose Bulk density (kg/m3) Stowage factor (m3/t)
Up to 60 mm 30° to 45° 1,700 to 1,800 0.55 to 0.59
Hazard classification
Class Subsidiary hazard(s) MHB Group
Not applicable Not applicable Not applicable C
Hazard

SOURCE: MSC.575(110).pdf

URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.575(110).pdf
Hazard classification
Class Subsidiary hazard(s) MHB Group
Not applicable Not applicable Not applicable C
Hazard
No special hazards.
This cargo is non-combustible or has a low fire risk.
Stowage and segregation
"Away from" alkalis, oxidizing substances, acids, food, drink and animal feeding stuffs.
Hold cleanliness
No special requirements.
Weather precautions
No special requirements.
Loading
Trim in accordance with the relevant provisions required under sections 4 and 5 of this Code.
When the stowage factor of this cargo is equal to or less than 0.56 m 3/t, the tank top may be overstressed unless the cargo is evenly spread across the tank top to equalize the weight distribution. Due consideration shall be given to ensure that the tank top is not overstressed during the voyage and during loading by a pile of the cargo.
Precautions
Bilge wells shall be clean, dry and covered as appropriate, to prevent ingress of the cargo.

SOURCE: MSC.575(110).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.575(110).pdf
Precautions
Bilge wells shall be clean, dry and covered as appropriate, to prevent ingress of the cargo.
Bilge wells of the cargo spaces shall be protected from ingress of the cargo. Persons who may be exposed to cargo shall wear eye/face protection and applicable filter masks (in case of inadequate ventilation).
Ventilation
No special requirements.
Carriage
No special requirements.
Discharge
No special requirements.
Clean-up
Contaminated washing water shall be retained and disposed of in an appropriate manner/facility."
RESOLUTION MSC.575(110) (adopted on 26 June 2025)
AMENDMENTS TO THE INTERNATIONAL MARITIME SOLID BULK CARGOES CODE (IMSBC CODE)
- 10 -
"CRUSHED GRANODIORITE, COARSE
The provisions of this schedule shall apply only to cargoes containing less than 0.1% respirable quartz and less than 7% of particles under 2 mm.
Description
Crushed granodiorite is made by blasting, crushing and sieving the common rock species
---
SOURCE: MSC.575(110).pdf
URL:

https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.575(110).pdf
Description
Crushed granodiorite is made by blasting, crushing and sieving the common rock species granodiorite, a grey, very hard and compact mineral stone. The aggregate is used as a component in asphalt, concrete and hydraulically unbound materials.
Characteristics
Physical properties
Size Angle of repose Bulk density (kg/m3) Stowage factor (m3/t)
Up to 200 mm and less than 7% of particles less than 2 mm
34° to 40° 1,340 to 1,900 0.53 to 0.75
Hazard classification
Class Subsidiary hazard(s) MHB Group
Not applicable Not applicable Not applicable C
Hazard
No special hazards.
This cargo is non-combustible or has a low fire risk.
Stowage and segregation
No special requirements.
Hold cleanliness
No special requirements.
Weather precautions
No special requirements.
Loading
During loading, due consideration shall be given to minimize dust generation. Trim in accordance with the relevant provisions required under sections 4 and 5 of this Code.

SOURCE: MSC.575(110).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.575(110).pdf
accordance with the relevant provisions required under sections 4 and 5 of this Code.
When the stowage factor of this cargo is equal to or less than 0.56 m 3/t, the tank top may be overstressed unless the cargo is evenly spread across the tank top to equalize the weight distribution. Due consideration shall be given to ensure that the tank top is not overstressed during the voyage and during loading by a pile of the cargo.
Precautions
Appropriate precautions shall be taken to protect machinery and accommodation spaces from the dust of the cargo. Bilge wells of the cargo spaces shall be protected from ingress of the cargo. Due consideration shall be given to protect equipment from the du st of the cargo.
Persons who may be exposed to the dust of the cargo shall wear goggles or other equivalent dust eye -protection and dust filter masks. Those persons shall wear protective clothing, as necessary.
Ventilation
No special requirements.
Carriage
No special requirements.

SOURCE: MSC.575(110).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.575(110).p

df
as necessary.
Ventilation
No special requirements.
Carriage
No special requirements.
RESOLUTION MSC.575(110) (adopted on 26 June 2025)
AMENDMENTS TO THE INTERNATIONAL MARITIME SOLID
BULK CARGOES CODE (IMSBC CODE)
- 11 -
Discharge
No special requirements.
Clean-up
No special requirements."
"FERRIC SULPHATE GRANULAR
Description
Ferric sulphate consists of inorganic granules, usually yellow, brown or grey in colour.
Hygroscopic in nature. Soluble in water. Used as a coagulant for water treatment. No special
odour. Moisture normally around 10% (measured at 105°C); no oil in the car go. Stored
under cover.
Characteristics
Physical properties
Size Angle of repose Bulk density (kg/m3) Stowage factor (m3/t)
less than 5 mm 38° to 42° 1,000 to 1,300 0.77 to 1.00
Hazard classification
Class Subsidiary hazard(s) MHB Group
Not applicable Not applicable CR B
Hazard
Harmful if swallowed.
Causes skin irritation.
May cause an allergic skin reaction due to sensitization.

SOURCE: MSC.575(110).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.575(110).pdf
Hazard
Harmful if swallowed.
Causes skin irritation.