URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.576(110).pdf
attached to the bulwark ladder to prevent the bulwark ladder from overturning and shall be positioned no greater than 0.12 m inboard of the edge of the deck. A ring or eye with an inner diameter not less than 60 mm at a height of the stanchion above the deck shall be provided to accommodate manropes;

.2 a bulwark ladder, it shall be securely attached to the ship to prevent overturning. Two separate handhold stanchions with a diameter of not less than 32 mm and not more than 36 mm shall be fitted at the point of embarking on or disembarking from the ship on each side which shall be not less than 0.7 m and not more than 0.8 m apart in clear width. Each stanchion shall be rigidly secured and locked to the ship at or near its base and also at a higher point and shall extend not less than 1.2 m above the top of the bulwarks. Stanchions or handrails of the gateway shall not be attached to the bulwark ladder to prevent the bulwark from overturning and shall be
---
SOURCE: MSC.576(110).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.576(110).pdf
bulwarks. Stanchions or handrails of the gateway shall not be attached to the bulwark ladder to prevent the bulwark from overturning and shall be positioned no greater than 0.12 m inboard of the edge of the deck. A ring or eye with an inner diameter not less than 60 mm at a height of the stanchion above the deck shall be provided to accommodate manropes; or

.3 a shipside opening or door, adequate handholds with a diameter of not less than 32 mm and not more than 36 mm shall be provided at the point of embarking on or disembarking from the ship on each side which shall be not less than 0.7 m and not more than 0.8 m apart in clear width. Each handhold shall be rigidly secured and locked to the ships structure at or near its base and also to the ship at a higher point to prevent dislodgement and shall extend not less than 1.2 m above the entry threshold. Stanchions or handrails shall be positioned no greater than 0.12 m inboard of the edge of the deck.

SOURCE: MSC.576(110).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.576(110).pdf
shall be positioned no greater than 0.12 m inboard of the edge of the deck. A ring or eye with an inner diameter not less than 60 mm at a height of the stanchion above the deck shall be provided to accommodate manropes.

9 Protection from chafing

Equipment and arrangements shall be designed and installed so that it is not possible for a pilot ladder side rope or manrope to make contact with any part of the ship's hull or associated

fixtures and fittings which could have the potential to cause sharp bends, chafing, abrasion,

pinching or otherwise degrade their performance. Where contact is unavoidable, contact points shall be rounded to minimize chafing. The means of rounding could be a permanent fixture, such as a rounded pipe. Where it is not possible to round contact points owing to ship design,
---
SOURCE: MSC.576(110).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.576(110).pdf
such as a rounded pipe. Where it is not possible to round contact points owing to ship design,
removable chafing pads or other temporary arrangements may be used. They shall be considered acceptable to the Administration, provided the se arrangements do not prevent pre-use inspections, are removed after use and stowed in accordance with section 23.

10 Safe approach of the pilot boat

Where rubbing bands or other constructional features prevent the safe approach of a pilot boat, these shall be cut back to provide at least 6 m of unobstructed ship's side. Specialized offshore ships less than 90 m or other similar ships less than 90 m for which a 6 m gap in the rubbing bands would not be practicable, as determined by the Administration, may be exempted. In this case, other appropriate measures shall be taken to ensure that pilots and other personnel are able to embark and disembark safely.

11 Associated equipment

Manropes shall be:

SOURCE: MSC.576(110).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.576(110).pdf
able to embark and disembark safely.

11 Associated equipment

Manropes shall be:

.1 not less than 28 mm and not more than 32 mm in diameter and shall be mildew-resistant manila rope, 7F or other material of equivalent strength, durability, elongation characteristics and grip;

.2 of a single length free from splices and knots; and

.3 tagged or otherwise permanently marked by the manufacturer with at least the following information:

.1 the name of the manufacturer;

.2 an equipment serial number or other means of unique identification which the manufacturer shall be able to validate;

.3 date of manufacture; and

.4 name and details of the approving authority.

PART B RIGGING

12 Pilot ladder

In all ships, when it is intended to embark and disembark pilots or other personnel by means of the pilot ladder, the pilot ladder shall be secured to the dedicated strong points meeting the requirements of paragraph 6.1 and positioned so that:

SOURCE: MSC.576(110).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.576(110).pdf

requirements of paragraph 6.1 and positioned so that:

.1 it is clear of any possible discharge from the ships and at all times hangs vertically, free and without obstruction;

.2 it is within the parallel body length of the ship and within the midship half-length of the ship;

.3 each step rests firmly against the ship's side and is horizontal in all planes throughout the entire vertical length of the ladder;

.4 when used in conjunction with ships' side openings, the ladder is secured in accordance with section 14;

.5 when a retrieval line is considered necessary to ensure the safe rigging of a pilot ladder, the line is secured to the forward end, at or above the lowest spreader step and leads forward. The retrieval line shall not hinder the pilot or other personnel nor obstruct the safe approach of the pilot boat; and

---

SOURCE: MSC.576(110).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.576(110).pdf

or other personnel nor obstruct the safe approach of the pilot boat; and

.6 the lowest step of the pilot ladder, by using the means specified in paragraph 6.3, is at the height above the surface of the water requested by the pilot or other personnel being transferred.

13 Combination arrangements

13.1 The combination arrangement shall be so positioned and secured that:

.1 the pilot ladder complies with the requirements in section 12;

.2 the accommodation ladder leads aft and is clear of any discharges;

.3 the lower platform of the accommodation ladder is secured to the ship's side

by means of permanent fixtures or removable fixtures within the parallel body length of the ship and within the midship half-length;

.4 the lower platform is in a horizontal position when in use and is a minimum of 5 m above the surface of the water in all seagoing conditions of draught and trim;

.5 the pilot ladder and manropes are secured to the ship's side at a point of

---

SOURCE: MSC.576(110).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.576(110).pdf

and trim;

.5 the pilot ladder and manropes are secured to the ship's side at a point of nominally 1.5 m above the lower platform of the accommodation ladder except as outlined in paragraph 5.5.7;

.6 the pilot ladder and manropes are not secured to the lower platform of the accommodation ladder at any time; and

.7 the pilot ladder is rigged immediately adjacent to the lower platform of the accommodation ladder and the highest step of the pilot ladder is at least 2 m above the lower platform. The horizontal distance between the pilot ladder and the lower platform shall be between 0.1 and 0.2 m.

13.2 In the case of a combination arrangement using an accommodation ladder with a trapdoor in the lower platform, the lower platform shall be positioned and rigged in accordance with the requirements of paragraphs 5.5 and 13.1.

14 Ships' side openings

14.1 Pilot ladders rigged from ships' side openings without a boarding platform shall not

---

SOURCE: MSC.576(110).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.576(110).pdf

14 Ships' side openings