21.6 A mechanical device or locking pin shall also be utilized to lock powered winch reels.

PART D OPERATIONAL READINESS, ONBOARD INSPECTION AND MAINTENANCE

22 Periodic maintenance and inspections shall be carried out to ensure the pilot transfer arrangements are in good condition, free from contamination and ready for use. Regardless of the date of installation, maintenance and inspection of accommodation ladders used in the combination arrangement shall be carried out in accordance with SOLAS regulation II-1/3-9.3.

23 Pilot ladders, manropes and all associated equipment, when not in use, shall be stowed to prevent degradation caused by moisture, icing and sunlight, chemicals and greases
---
SOURCE: MSC.576(110).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.576(110).pdf
stowed to prevent degradation caused by moisture, icing and sunlight, chemicals and greases and similar contaminants, and in accordance with the manufacturer's instructions.

24 Instructions for care, maintenance, inspection and stowage shall be supplied with each pilot ladder, manropes and all associated equipment. These instructions shall include:

.1 pre- and post-use inspection instructions;

.2 detailed periodic inspection procedures, including those for side ropes;

.3 instructions for inspecting and repairing rope seizings or securing devices, along with a list of permitted onboard repairs;

.4 care and stowage instructions, including warnings about chemical exposure, sunlight impact and other potential causes of ladder degradation;

.5 factors affecting pilot ladder life, including stowage arrangements;

.6 acceptable method(s) of securing ladder to strong points;

.7 pictorial examples and detailed written description of damage or conditions
---
SOURCE: MSC.576(110).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.576(110).pdf
.6 acceptable method(s) of securing ladder to strong points;

.7 pictorial examples and detailed written description of damage or conditions warranting withdrawing the ladder from service; and

.8 care and maintenance specifics for natural fibre rope ladders.

25 Pilot transfer arrangements shall be subject to:

.1 inspection before and after each use by a responsible officer on board; and

.2 a detailed inspection every three months by a responsible officer on board.

26 In order to determine the suitability for ongoing use of the pilot transfer arrangements, inspections shall include the following:

.1 the pilot ladder including spares;

.2 the accommodation ladder used in a combination arrangement;

.3 winch reels;

.4 securing arrangements;

.5 conditions of point of access;

SOURCE: MSC.576(110).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.576(110).pdf

.3 winch reels;

.4 securing arrangements;

.5 conditions of point of access;

.6 relevant equipment, in particular stanchions and stanchion sockets welded onto the deck; and

.7 stowage arrangements.

27 A maintenance plan shall be developed and shall be available for inspection. The maintenance plan shall be easily understood, illustrated as appropriate wherever possible, and shall include the following:

.1 a checklist for use when carrying out the inspections required by section 25;

.2 maintenance, repair and stowage instructions, in accordance with manufacturer's instructions;

.3 schedule of periodic inspection and maintenance;

.4 list of sources of spare parts or replacements;

.5 log for records of inspections and maintenance; and

.6 record of when the pilot ladder or manropes were brought into service and their anticipated date of withdrawal from service in accordance with section 30 of these performance standards.

SOURCE: MSC.576(110).pdf
URL:

https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.576(110).pdf
their anticipated date of withdrawal from service in accordance with
section 30 of these performance standards.

28 Repair or replacement of pilot ladder steps or spreader steps shall be prohibited.

29 At least one spare compliant pilot ladder and one spare set of compliant manropes
shall be carried on board the ship.

30 Pilot ladders and manropes, including their spares, shall be removed from service,
either at any time not complying with these performance standards, or within 36 months after
the date of manufacture or within 30 months after the date of being placed into service,
whichever comes first, and shall not be used for the embarkation and disembarkation of pilots
or other personnel.

RESOLUTION MSC.576(110) (adopted on 26 June 2025)
PERFORMANCE STANDARDS FOR PILOT TRANSFER ARRANGEMENTS
- 14 -
PART E FAMILIARIZATION
31 Onboard personnel involved in the inspection, maintenance, rigging or operation of
---
SOURCE: MSC.576(110).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.576(110).pdf
- 14 -
PART E FAMILIARIZATION
31 Onboard personnel involved in the inspection, maintenance, rigging or operation of
any equipment for pilot transfer arrangements shall receive familiarization to perform their
assigned duties. This shall form part of the onboard familiarization of the crew.
32 On ships to which SOLAS chapter IX applies, the company, as defined in SOLAS
regulation IX/1.2, ensures that onboard personnel involved in the operation of inspection,
maintenance, rigging or operation of any equipment for pilot transfer arrangements are
familiarized with the onboard pilot transfer arrangements for safe operation in accordance with
STCW regulation I/14.
33 On ships to which SOLAS chapter IX does not apply, familiarization on board shall
include, but not be limited to:
.1 operation and use of the equipment and arrangements for the transfer of
pilots and other personnel provided on board the ship;

SOURCE: MSC.576(110).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.576(110).pdf
.1 operation and use of the equipment and arrangements for the transfer of
pilots and other personnel provided on board the ship;
.2 the characteristics of pilot transfer arrangements which shall not be used for
the transfer of pilots or other personnel;
.3 carrying out inspections and maintenance of the pilot transfer arrangements,
including spare ladders on board;
.4 replacement procedures of pilot ladders and manropes; and
.5 when applicable, measures and additional equipment or operational
considerations to be made to ensure the integrity of the pilot ladder in special

conditions, i.e. freezing or windy condition or rough weather especially when there is moderate swell.

PART F APPROVAL

34 Pilot transfer arrangements installed in accordance with SOLAS regulation V/23.3 shall be approved by the Administration in accordance with these performance standards before being put into service for the first time and after repair, alteration or modification to the

---

SOURCE: MSC.576(110).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.576(110).pdf

before being put into service for the first time and after repair, alteration or modification to the arrangements provided for in sections 5 to 8 and section 10 of part A, or part C, of these performance standards.

35 Pilot transfer arrangements installed in accordance with SOLAS regulations V/23.4 and 23.5 shall be approved by the Administration in accordance with these performance standards after alteration or modification, if any, or repair, to the arrangements provided for in sections 5 to 8 and section 10 of part A, or part C, of these performance standards.

36 A pilot ladder, including the means of securing the pilot ladder at intermediate lengths, and manropes shall be type -approved by the Administration in accordance with these performance standards.

37 A manufacturer quality control system shall be required and shall be audited by a competent authority to ensure continuous compliance with the type approval conditions.

SOURCE: MSC.576(110).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.576(110).pdf

competent authority to ensure continuous compliance with the type approval conditions. Alternatively, the Administration may use final product verification procedures where compliance with the type approval certificate is verified by a competent authority before the product is installed on board ships.

RESOLUTION MSC.576(110) (adopted on 26 June 2025)
PERFORMANCE STANDARDS FOR PILOT TRANSFER ARRANGEMENTS

SOURCE: MSC.580(110).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.580(110).pdf

RESOLUTION MSC.580(110) (adopted on 27 June 2025)