as forecastle head spaces, pump-rooms, compressor rooms, inert gas rooms and other spaces that are adjacent to, or connected to, spaces containing a hazardous atmosphere.
These spaces include cargo holds containing cargo that depletes oxygen and /or emits toxic, flammable or explosive gases, or is under fumigation.
RESOLUTION MSC.581(110) (adopted on 27 June 2025)
REVISED RECOMMENDATIONS FOR ENTERING

SOURCE: MSC.581(110).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.581(110).pdf
flammable or explosive gases, or is under fumigation.
RESOLUTION MSC.581(110) (adopted on 27 June 2025)
REVISED RECOMMENDATIONS FOR ENTERING
ENCLOSED SPACES ABOARD SHIPS

1.2 An unsafe atmosphere can also occur in void spaces, cofferdams, pipe tunnels and also in accommodation areas and engine -rooms adjacent to or connected to cargo holds containing hazardous cargo or under fumigation due to a failure in the means of sealing the connection between the cargo space and the adjacent spaces.
1.3 The emission of toxic, flammable or explosive gases from cargo tanks, fuel tanks, slop tanks and sewage tanks can also give rise to a potentially dangerous situation around open access hatches, manholes and ventilators on deck.
2 DEFINITIONS
2.1 Enclosed space means a space which may contain a hazardous atmosphere or lack of oxygen and has any of the following characteristics:

SOURCE: MSC.581(110).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.581(110).pdf
2.1 Enclosed space means a space which may contain a hazardous atmosphere or lack of oxygen and has any of the following characteristics:
.1 limited openings for entry and exit;
.2 inadequate ventilation; or
.3 not designed for continuous human occupancy.
This includes but is not limited to spaces that are diverse in their characteristics such as cargo holds, bilge spaces, ballast and other tanks, pump -rooms, chain lockers and engine crankcases.
2.2 Connected space means a space that is connected, by either permanent or temporary means (such as a door), to a source space that may contain a hazardous atmosphere.
For clarity, a space separated by a manual door, even if watertight, should be considered as "connected" as it is impossible to tell from outside the space whether it is open or closed or indeed properly sealed. A connected space should be treated as containing a hazardous atmosphere until testing proves otherwise. The nature of the connection may lead to a
---
SOURCE: MSC.581(110).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.581(110).pdf
atmosphere until testing proves otherwise. The nature of the connection may lead to a
trapped hazardous atmosphere.

2.3 Adjacent space means a space that shares a common boundary with a compartment that may contain a hazardous atmosphere. Such a space has no openings, temporary or permanent, into the hazardous compartment whatsoever and is designed to be a contiguous barrier. Such a space may only contain a hazardous atmosphere in the event of failure of that barrier. Precautions should relate to the possibility of such a failure.
2.4 Trapped Hazardous Atmosphere means a hazardous atmosphere that may be trapped in a connected space in a manner that causes that spaces atmosphere to fill and/or to empty at a different rate to the source space. Such a space, while recognized as containing the same atmosphere, should be treated independently to the source space, and should be assumed to contain a hazardous atmosphere until proved otherwise by testing. For example,
---
SOURCE: MSC.581(110).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.581(110).pdf
assumed to contain a hazardous atmosphere until proved otherwise by testing. For example, a trapped atmosphere may remain even after the cargo in the source space is discharged.
2.5 Competent person means a person with an operational level of competency to make an informed assessment of the likelihood of a dangerous atmosphere being present or subsequently arising in the space.
2.6 Responsible person means a person in a management level on board a ship (i.e. master, chief mate, chief engineer officer or second engineer officer) of competency and authorized by the shipping company to permit entry into an enclosed space.
RESOLUTION MSC.581(110) (adopted on 27 June 2025)
REVISED RECOMMENDATIONS FOR ENTERING
ENCLOSED SPACES ABOARD SHIPS
MSC 110/21/Add.3
Annex 28, page 4
I:\MSC\110\MSC 110-21-Add.3.docx
2.7 Attendant means a person maintains a watch over those entering the enclosed space, to maintain communications with those inside the space and to initiate the emergency
---
SOURCE: MSC.581(110).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.581(110).pdf
to maintain communications with those inside the space and to initiate the emergency procedures in the event of an incident occurring.
2.8 Enclosed Space Register means a ship -specific register which lists all enclosed spaces on board the ship, along with their connected spaces and adjacent spaces, their hazards, associated risk mitigations if applicable, and how the atmosphere in these spaces may change depending upon the nature of cargo carried or the content of the space, and which forms a part of the safety management for enclosed spaces.
3 SAFETY MANAGEMENT FOR ENTRY INTO ENCLOSED SPACES
3.1 A safety strategy should be adopted in order to prevent accidents on entry into enclosed spaces in a comprehensive manner by the company, in consultation with the ship. This should include an Enclosed Space Register, which should be produced on a ship-by-ship basis to identify enclosed spaces, the hazards of those spaces, assessment of risks under the
---
SOURCE: MSC.581(110).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.581(110).pdf
basis to identify enclosed spaces, the hazards of those spaces, assessment of risks under the

differing conditions likely to arise in the space and the risk mitigation measures required to be put into place prior to entry. This should also include an assessment of how the atmosphere in these enclosed spaces may be impacted by the contents of the spaces themselves, such as in case a ship stores treated sewage or grey water temporarily in its ballast water tanks, or the contents of connected spaces or adjacent spaces, including cargo, fumigants, fuel oils, slops, oxygen-depleting conditions and the physical or structural arrangement of the space.
3.2 The company should ensure that all relevant information relating to the hazards of the cargo, as submitted by the shipper in accordance with the applicable requirements of SOLAS regulation VI/2, the International Maritime Solid Bulk Cargoes Code (IMSBC Code), the
---
SOURCE: MSC.581(110).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.581(110).pdf
regulation VI/2, the International Maritime Solid Bulk Cargoes Code (IMSBC Code), the International Maritime Dangerous Goods Code (IMDG Code), the IBC Code and the International Gas Carrier Code (IGC Code), is provided in a format that is understandable to the ships crew and distributed to those on board who may be exposed to these hazards.
3.3 The company should ensure that the procedures for entering enclosed spaces are included and implemented among the key shipboard operations concerning the safety of the personnel and the ship, in accordance with paragraphs 6.4, 7 and 12.3 of the International Safety Management (ISM) Code.
3.4 The company should ensure that all relevant crew members are given adequate training in the safety management of enclosed spaces as per paragraphs 6.3 and 6.5 of the ISM Code.
3.5 The company should ensure that adequate time has been allowed for any planned
---
SOURCE: MSC.581(110).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.581(110).pdf
ISM Code.
3.5 The company should ensure that adequate time has been allowed for any planned enclosed space activity, and that undue time pressure, either explicit or implied, is avoided as this has been found to be a causal factor of many enclosed space accidents.
3.6 The company should elaborate a procedural implementation scheme which provides for comprehensive training in the maintenance, calibration and use of atmospheric testing equipment in such spaces. This training should be recorded, and individual crew member s who have been deemed competent in the maintenance, calibration and use of atmospheric testing equipment should be listed.
RESOLUTION MSC.581(110) (adopted on 27 June 2025)
REVISED RECOMMENDATIONS FOR ENTERING
ENCLOSED SPACES ABOARD SHIPS
MSC 110/21/Add.3
Annex 28, page 5
I:\MSC\110\MSC 110-21-Add.3.docx
3.6.1 The competent and the responsible persons should be trained in enclosed space
---
SOURCE: MSC.581(110).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.581(110).pdf
Annex 28, page 5
I:\MSC\110\MSC 110-21-Add.3.docx

3.6.1 The competent and the responsible persons should be trained in enclosed space hazard recognition, evaluation, measurement, control and elimination, using standards acceptable to the Administration. The competent person should have received adequate training along with sufficient theoretical knowledge and practical experience to make an informed assessment of the likelihood of a dangerous atmosphere being present or subsequently arising in the space. The responsible person should have sufficient knowle dge of the procedures to be established and complied with on board and received adequate training, in order to ensure that an enclosed space is safe for entry and occupancy. The attendant should be adequately trained within the safety management system.
3.6.2 All crew members should be trained, as appropriate, in enclosed space safety,
---
SOURCE: MSC.581(110).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.581(110).pdf
3.6.2 All crew members should be trained, as appropriate, in enclosed space safety,
including familiarization with onboard procedures for recognizing, evaluating and controlling hazards associated with entry into enclosed spaces.
3.7 The company should identify and provide the necessary equipment such as ventilation devices, atmosphere testing equipment, breathing apparatus and personnel recovery apparatus to facilitate safe entry and rescue from an enclosed space. The equipment provided should be suitable for the intended use. A careful study of the operational profile should be carried out and all necessary equipment should always be on board in operational condition. Consideration should be given to the appropriate use of technol ogy to assist in the hazard identification and mitigation of enclosed space entry. Crew members should be trained in the use of equipment necessary to facilitate rescue from an enclosed space and a record of this training should be maintained.

SOURCE: MSC.581(110).pdf
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.581(110).pdf
in the use of equipment necessary to facilitate rescue from an enclosed space and a record of this training should be maintained.
3.8 The company should ensure that rescue drills from enclosed space identified in their Enclosed Space Register are undertaken regularly as required by SOLAS regulation III/19.3.6 using the equipment provided to facilitate a rescue from an enclosed space. Such drills should focus on different aspects of operations involving enclosed spaces . SOLAS regulation III/19.3.6 requires:
.1 checking and use of personal protective equipment required for entry;
.2 checking and use of communication equipment and procedures;
.3 checking and use of instruments for measuring the atmosphere in enclosed spaces;
.4 checking and use of rescue equipment and procedures; and
.5 instructions in first aid and resuscitation techniques.