---CHUNK---

SOURCE: MSC.216%2882%29.pdf
m represents each horizontal boundary counted upwards from the waterline under consideration;
RESOLUTION MSC.216(82)
(adopted on 8 December 2006)
AMENDMENTS TO THE INTERNATIONAL CONVENTION FOR THE SAFETY OF LIFE AT SEA, 1974, AS AMENDED-30 -

d is the draught in question as defined in regulation 2; and

x1 and x 2 represent the terminals of the co mpartment or group of compartments considered in regulation 7-1.

6.1.1 The factors v(Hj, n, m, d) and v(Hj, n, m-1, d) shall be obtained from the formulae:

, if (Hm-d) is less than, or equal to, 7.8 m;

in all other cases,

where:

v(Hj, n, m, d) is to be taken as 1, if Hm coincides with the uppermost watertight boundary of the ship within the range (x1(j)...x2(j+n-1)), and

v(Hj, n, 0, d) is to be taken as 0.

In no case is vm to be taken as less than zero or more than 1.

6.2 In general, each contribution dA to the index A in the case of horizontal

---CHUNK---

SOURCE: MSC.216%2882%29.pdf
v(Hj, n, 0, d) is to be taken as 0.

In no case is vm to be taken as less than zero or more than 1.

6.2 In general, each contribution dA to the index A in the case of horizontal
subdivisions is obtained from the formula:

() ( )[] mmi s vs v v s v p dA min 12 min 1 2 1 min 11 +++ =

where:

vm = the v-value calculated in accordance with paragraph 6.1;
smin = the least s-factor for all combinations of damages obtained when the assumed damage extends from the assumed damage height Hm

downwards.

Regulation 7-3
Permeability

1 For the purpose of the subdivision and damage stability calculations of the regulations, the permeability of each general compartment or part of a compartment shall be as follows:

Spaces Permeability
Appropriated to stores 0.60
Occupied by accommodation 0.95
Occupied by machinery 0.85
Void spaces 0.95
Intended for liquids 0 or 0.951
1 Whichever results in the more severe requirement.

()

---CHUNK---

SOURCE: MSC.216%2882%29.pdf
Appropriated to stores 0.60
Occupied by accommodation 0.95
Occupied by machinery 0.85
Void spaces 0.95
Intended for liquids 0 or 0.951
1 Whichever results in the more severe requirement.

()
8 . 78 . 0) , (d Hd H v =
()

+ = 7 . 4 8 . 72 . 0 8 . 0) , (d Hd H v
RESOLUTION MSC.216(82)
(adopted on 8 December 2006)
AMENDMENTS TO THE INTERNATIONAL CONVENTION FOR THE SAFETY OF LIFE AT SEA, 1974, AS AMENDED-
31 -

2 For the purpose of the subdivision and damage stability calculations of the regulations, the permeability of each cargo compartment or part of a compartment shall be as follows:

Spaces

Permeability
at draught ds

Permeability
at draught dp

Permeability
at draught dl
Dry cargo spaces 0.70 0.80 0.95
Container spaces 0.70 0.80 0.95
Ro-ro spaces 0.90 0.90 0.95
Cargo liquids 0.70 0.80 0.95

3 Other figures for permeability may be used if substantiated by calculations.

Regulation 8

---CHUNK---

SOURCE: MSC.216%2882%29.pdf
Container spaces 0.70 0.80 0.95
Ro-ro spaces 0.90 0.90 0.95
Cargo liquids 0.70 0.80 0.95

3 Other figures for permeability may be used if substantiated by calculations.

Regulation 8
Special requirements concerning passenger ship stability

1 A passenger ship intended to carry 400 or more persons shall have watertight subdivision abaft the collis ion bulkhead so that s i = 1 for the three loading conditions on which is based the calculation of the subdivision index and for a damage involving all the compartments within 0.08L measured from the forward perpendicular.

2 A passenger ship intended to carry 36 or more persons is to be capable of withstanding damage along the side shell to an extent specified in paragraph 3. Compliance with this regulation is to be achieved by demonstrating that s i, as defined in regulation 7-2, is not less than 0.9 for the three loading conditions on which is based the calculation of the subdivision index.

---CHUNK---

SOURCE: MSC.216%2882%29.pdf
regulation 7-2, is not less than 0.9 for the three loading conditions on which is based the calculation of the subdivision index.

3 The damage extent to be assumed when demonstrating compliance with paragraph 2, is to be dependent on both N as defined in regulation 6, and Ls as defined in regulation 2, such that:

.1 the vertical extent of damage is to extend from the ships moulded baseline to a position up to 12.5 m above the position of the deepest subdivision draught as defined in regulation 2, unless a lesser vertical extent of damage were to give a lower value of si, in which case this reduced extent is to be used;

.2 where 400 or more persons are to be carried, a damage length of 0.03L s but not less than 3 m is to be assumed at any position along the side shell, in conjunction with a penetr ation inboard of 0.1 B but not less than 0.75 m measured inboard from the ship side, at right angle to the centreline at the

level of the deepest subdivision draught;

---CHUNK---

SOURCE: MSC.216%2882%29.pdf
conjunction with a penetr ation inboard of 0.1 B but not less than 0.75 m measured inboard from the ship side, at right angle to the centreline at the level of the deepest subdivision draught;

.3 where less than 400 persons are carried, damage length is to be assumed at any position along the shell side betw een transverse watertight bulkheads provided that the distance between two adjacent transverse watertight bulkheads is not less than the assume d damage length. If the distance between adjacent transverse watertight bulkheads is less than the assumed damage length, only one of these bulkheads shall be considered effective for the purpose of demonstrating compliance with paragraph 2;
RESOLUTION MSC.216(82)
(adopted on 8 December 2006)
AMENDMENTS TO THE INTERNATIONAL CONVENTION FOR THE SAFETY OF LIFE AT SEA, 1974, AS AMENDED-

.4 where 36 persons are carried, a damage length of 0.015 Ls but not less

---CHUNK---