.4 where 36 persons are carried, a damage length of 0.015 Ls but not less than 3 m is to be assumed, in co njunction with a penetration inboard of 0.05B but not less than 0.75 m; and

.5 where more than 36, but fewer than 400 persons are carried the values of damage length and penetration inboard, used in the dete rmination of the assumed extent of damage, are to be obtained by linear interpolation between the values of damage length and penetration which apply for ships carrying 36 persons and 400 persons as specified in subparagraphs .4 and .2.

Regulation 8-1
System capabilities after a flooding casualty on passenger ships

1 Application

This regulation applies to passenger ships constructed on or after 1 July 2010 to which regulation II-2/21 applies.

2 Availability of essential system s in case of flooding damage

---CHUNK---

SOURCE: MSC.216%2882%29.pdf
This regulation applies to passenger ships constructed on or after 1 July 2010 to which regulation II-2/21 applies.

2 Availability of essential system s in case of flooding damage

A passenger ship shall be designed so that the systems specified in regulation II-2/21.4 remain operational when the ship is subject to flooding of any single watertight compartment.

PART B-2
SUBDIVISION, WATERTIGHT AND WEATHERTIGHT INTEGRITY

Regulation 9
Double bottoms in passenger ships and cargo ships other than tankers

1 A double bottom shall be fitted extending from the collision bulkhead to the afterpeak bulkhead, as far as this is practicable and compatible with the design and proper working of the ship.

2 Where a double bottom is required to be fitted the inner bottom shall be continued out to the ship's sides in such a manner as to protect the bottom to the turn of the bilge. Such protection will be deemed satisfactory if the inner bottom is not lower at any part

---CHUNK---

SOURCE: MSC.216%2882%29.pdf

out to the ship's sides in such a manner as to protect the bottom to the turn of the bilge. Such protection will be deemed satisfactory if the inner bottom is not lower at any part than a plane parallel with the keel line and which is located not less than a vertical distance h measured from the keel line, as calculated by the formula:

h = B/20

However, in no case is the value of h to be less than 760 mm, and need not be taken as more than 2,000 mm.

3 Small wells constructed in the double bottom in connection with drainage arrangements of holds, etc., shall not extend downward more than necessary. A well extending to the outer bottom is, however, permitted at the afte r end of the shaft tunnel. Other wells (e.g., for lubricating oil under main engines) may be permitted by the Administration if satisfied that the arrange ments give protection equivalent to that afforded by a double bottom complying with this regulation. In no case shall the vertical

---CHUNK---

SOURCE: MSC.216%2882%29.pdf
Administration if satisfied that the arrange ments give protection equivalent to that afforded by a double bottom complying with this regulation. In no case shall the vertical distance from the bottom of such a well to a plane coinciding with the keel line be less than 500 mm.
RESOLUTION MSC.216(82)
(adopted on 8 December 2006)
AMENDMENTS TO THE INTERNATIONAL CONVENTION FOR THE SAFETY OF LIFE AT SEA, 1974, AS AMENDED-

4 A double bottom need not be fitted in way of watertight tanks, including dry tanks of moderate size, provided the safety of the ship is not impaired in the event of bottom or side damage.

5 In the case of passenger ships to which th e provisions of regulation 1.5 apply and which are engaged on regular se rvice within the limits of a short in ternational voyage as defined in regulation III/3.22, the Administration may permit a double bottom to be dispensed with if satisfied th at the fitting of a double bottom in that part would not be

---CHUNK---

SOURCE: MSC.216%2882%29.pdf
defined in regulation III/3.22, the Administration may permit a double bottom to be dispensed with if satisfied th at the fitting of a double bottom in that part would not be compatible with the design and proper working of the ship.

6 Any part of a passenger ship or a cargo ship that is not fitted with a double bottom in accordance with paragraphs 1, 4 or 5 shall be capable of withstanding bottom damages, as specified in paragraph 8, in that part of the ship.

7 In the case of unusual bottom arrangement s in a passenger ship or a cargo ship, it shall be demonstrated that the ship is capable of withstanding bottom damages as specified in paragraph 8.

8 Compliance with paragraphs 6 or 7 is to be achieved by demonstrating that si, when calculated in accordance with regulatio n 7-2, is not less than 1 for all service conditions when subject to a bottom damage assumed at any position along the ships

---CHUNK---

SOURCE: MSC.216%2882%29.pdf
when calculated in accordance with regulatio n 7-2, is not less than 1 for all service conditions when subject to a bottom damage assumed at any position along the ships bottom and with an extent specified in subparagraph .2 for the affected part of the ship:

.1 Flooding of such spaces shall not render emergency power and lighting, internal communication, signals or ot her emergency devices inoperable in other parts of the ship.

.2 Assumed extent of damage shall be as follows:

For 0.3 L from the forward perpendicular of the ship	Any other part of the ship
Longitudinal extent	1/3 L2/3 or 14.5 m, whichever is less	1/3 L2/3 or 14.5 m, whichever is less
Transverse extent	B/6 or 10 m, whichever is less	B/6 or 5 m, whichever is less
Vertical extent, measured from the keel line	B/20 or 2 m, whichever is less	B/20 or 2 m, whichever is less

.3 If any damage of a lesser extent than the maximum damage specified in

---CHUNK---

SOURCE: MSC.216%2882%29.pdf
Vertical extent,
measured from
the keel line
B/20 or 2 m, whichever is less B/20 or 2 m, whichever is less

.3 If any damage of a lesser extent than the maximum damage specified in subparagraph .2 would result in a mo re severe condition, such damage should be considered.

9 In case of large lower ho lds in passenger ships, the Administration may require an increased double bottom height of not more than B /10 or 3 m, whichever is less, measured from the keel line. Alternativel y, bottom damages may be calculated for these areas, in accordance with paragraph 8, but assuming an increased vertical extent.

RESOLUTION MSC.216(82)
(adopted on 8 December 2006)
AMENDMENTS TO THE INTERNATIONAL CONVENTION FOR THE SAFETY OF LIFE AT SEA, 1974, AS AMENDED-34 -

Regulation 10
Construction of watertight bulkheads

1 Each watertight subdivision bulkhead, whether transverse or longitudinal, shall be

---CHUNK---

SOURCE: MSC.216%2882%29.pdf
Regulation 10
Construction of watertight bulkheads

1 Each watertight subdivision bulkhead, whether transverse or longitudinal, shall be constructed having scantlings as specified in regulation 2.17. In all cases, watertight subdivision bulkheads shall be capable of supporting at least the pressure due to a head of water up to the bulkhead deck.

2 Steps and recesses in watertight bulkheads shall be as strong as the bulkhead at the place where each occurs.

Regulation 11
Initial testing of watertight bulkheads, etc.