SOURCE: MSC.216%2882%29.pdf
receive the special consideration of the Administration.

11.3 Where trunkways in connection with refr igerated cargo and ventilation or forced draught trunks are carried th rough more than one watert ight bulkhead, the means of closure at such openings shall be operated by power and be cap able of being closed from a central position situated above the bulkhead deck.

Regulation 13-1
Openings in watertight bulkheads and internal decks in cargo ships

1 The number of openings in watertight s ubdivisions is to be kept to a minimum compatible with the design and proper workin g of the ship. Where penetrations of watertight bulkheads and internal decks are necessary for access, piping, ventilation, electrical cables, etc., arrangements are to be made to maintain the watertight integrity. The Administration may permit relaxation in the watertightness of openings above the freeboard deck, provided that it is demonstrated that any progressive flooding can be

---CHUNK---

SOURCE: MSC.216%2882%29.pdf
The Administration may permit relaxation in the watertightness of openings above the freeboard deck, provided that it is demonstrated that any progressive flooding can be easily controlled and that the safety of the ship is not impaired.

RESOLUTION MSC.216(82)
(adopted on 8 December 2006)
AMENDMENTS TO THE INTERNATIONAL CONVENTION FOR THE SAFETY OF LIFE AT SEA, 1974, AS AMENDED-41 -

2 Doors provided to ensure the watertight integrity of internal openings which are used while at sea are to be sliding watertight doors capable of being remotely closed from the bridge and are also to be operable locally from each side of the bulkhead. Indicators are to be provided at the control position showing whether the doors are open or closed, and an audible alarm is to be provided at the door closure. The power, control and indicators are to be operable in the event of ma in power failure. Particular attention is to

---CHUNK---

SOURCE: MSC.216%2882%29.pdf
and an audible alarm is to be provided at the door closure. The power, control and indicators are to be operable in the event of ma in power failure. Particular attention is to be paid to minimizing the eff ect of control system failure. Each power-operated sliding watertight door shall be provided with an in dividual hand-operated mechanism. It shall be possible to open and close the door by hand at the door itself from both sides.

3 Access doors and access hatch covers normally closed at sea, intended to ensure the watertight integrity of internal openings, shall be provided with means of indication locally and on the bridge showing whether these doors or hatch covers are open or closed. A notice is to be affixed to each such door or hatch cover to the effect that it is not to be left open.

4 Watertight doors or ramps of satisfactor y construction may be fitted to internally

---CHUNK---

SOURCE: MSC.216%2882%29.pdf
A notice is to be affixed to each such door or hatch cover to the effect that it is not to be left open.

4 Watertight doors or ramps of satisfactor y construction may be fitted to internally subdivide large cargo spaces, provided that the Administration is satisfied that such doors or ramps are essential. These doors or ramps may be hinged, rolling or sliding doors or ramps, but shall not be remotely controll ed. Should any of the doors or ramps be accessible during the voyage, they shall be fitted with a device which prevents unauthorized opening.

5 Other closing appliances which are kept pe rmanently closed at sea to ensure the watertight integrity of internal openings sha ll be provided with a notice which is to be affixed to each such closing appliance to the eff ect that it is to be kept closed. Manholes fitted with closely bolted covers need not be so marked.

Regulation 14
Passenger ships carrying goods vehicles and accompanying personnel

---CHUNK---

SOURCE: MSC.216%2882%29.pdf
fitted with closely bolted covers need not be so marked.

Regulation 14
Passenger ships carrying goods vehicles and accompanying personnel

1 This regulation applies to passenger ships designed or adapted for the carriage of goods vehicles and accompanying personnel.

2 If in such a ship the total numbe r of passengers which include personnel accompanying vehicles does not exceed 12 + Ad/25, where Ad = total deck area (square metres) of spaces available for the stowage of goods vehicles and where the clear height at the stowage position and at the entrance to such spaces is not less than 4 m, the provisions of regulations 13.9.1 and 13.9.2 in respect of watertight doors apply except that the doors may be fitted at any level in watertight bulkheads dividing cargo spaces. Additionally, indicators are required on the navigation bridge to show automatically when each door is closed and all door fastenings are secured.

---CHUNK---

SOURCE: MSC.216%2882%29.pdf
Additionally, indicators are required on the navigation bridge to show automatically when each door is closed and all door fastenings are secured.

3 The ship may not be certified for a higher number of passengers than assumed in paragraph 2, if a watertight door has been fitted in accordance with this regulation.

Regulation 15
Openings in the shell plating below the bulkhead deck of passenger ships
and the freeboard deck of cargo ships

1 The number of openings in the shell plating shall be reduced to the minimum compatible with the design and proper working of the ship.

RESOLUTION MSC.216(82)
(adopted on 8 December 2006)
AMENDMENTS TO THE INTERNATIONAL CONVENTION FOR THE SAFETY OF LIFE AT SEA, 1974, AS AMENDED-42 -

2 The arrangement and efficiency of the means for closing any opening in the shell plating shall be consistent with its intende d purpose and the position in which it is fitted and generally to the satisfaction of the Administration.

---CHUNK---

SOURCE: MSC.216%2882%29.pdf
plating shall be consistent with its intende d purpose and the position in which it is fitted and generally to the satisfaction of the Administration.

3.1 Subject to the requirements of the In ternational Conventio n on Load Lines in force, no sidescuttle shall be fitted in such a position that its sill is below a line drawn parallel to the bulkhead deck at side and having its lowest point 2.5% of the breadth of the ship above the deepest subdivision draught, or 500 mm, whichever is the greater.

3.2 All sidescuttles the sills of which are below the bulkhead deck of passenger ships and the freeboard deck of cargo ships, as permitted by paragraph 3.1, shall be of such construction as will effectively prevent any person opening them without the consent of the master of the ship.

4 Efficient hinged inside deadlights so arranged that they can be easily and effectively closed and secured watertight, shall be fitted to all sidescuttles except that

---CHUNK---

SOURCE: MSC.216%2882%29.pdf
the master of the ship.

4 Efficient hinged inside deadlights so arranged that they can be easily and effectively closed and secured watertight, shall be fitted to all sidescuttles except that abaft one eighth of the ship's length from the forward perpendicular and above a line drawn parallel to the bulkhead deck at si de and having its lowest point at a height of 3.7 m plus 2.5% of the br eadth of the ship above the de epest subdivision draught, the deadlights may be portable in passenger ac commodation other than that for steerage passengers, unless the deadlights are require d by the International Convention on Load Lines in force to be permanently attached in their proper positions. Such portable deadlights shall be stowed adjacent to the sidescuttles they serve.

5.1 No sidescuttles shall be fitted in any spaces which are appropriated exclusively to the carriage of cargo or coal.

---CHUNK---

SOURCE: MSC.216%2882%29.pdf
deadlights shall be stowed adjacent to the sidescuttles they serve.

5.1 No sidescuttles shall be fitted in any spaces which are appropriated exclusively to the carriage of cargo or coal.

5.2 Sidescuttles may, however, be fitted in spaces appropriated alternatively to the carriage of cargo or passengers, but they shal l be of such construction as will effectively prevent any person opening them or their deadlights without the consent of the master.

6 Automatic ventilating sidescuttles shall not be fitted in the shell plating below the bulkhead deck of passenger ships and the fr eeboard deck of cargo ships without the special sanction of the Administration.

7 The number of scuppers, sanitary discharges and other similar openings in the shell plating shall be reduced to the mini mum either by making each discharge serve for as many as possible of the sanitary and other pipes, or in any other satisfactory manner.

---CHUNK---

SOURCE: MSC.216%2882%29.pdf
shell plating shall be reduced to the mini mum either by making each discharge serve for as many as possible of the sanitary and other pipes, or in any other satisfactory manner.

8.1 All inlets and discharges in the shell plating shall be fitted with efficient and accessible arrangements for preventing the accidental admission of water into the ship.