and/or area specified regarding the presence of the materials listed in appendix 1 by document analysis should be entered in the List of equipment, system and/or area for visual check);

- List of equipment, system and/or ar ea for sampling check (any equipment, system and/or area which cannot be specified regarding the presence of the materials listed in appendix 1 by document or visual analysis should be entered in the List of equipment, system and/or area as requiring sampling check.
A sampling check is the taking of samples to identify the presence or absence of Hazardous Material contained in the equipment, systems, and/or areas, by suitable and generally accepted methods such as laboratory analysis); and

- List of equipment, system and/or area classed as "potentially containing Hazardous Material" (any equipment, system and/or area which cannot be specified regarding the presence of the materials listed in appendix 1 by

---CHUNK---

SOURCE: MEPC.197(62).pdf
- List of equipment, system and/or area classed as "potentially containing Hazardous Material" (any equipment, system and/or area which cannot be specified regarding the presence of the materials listed in appendix 1 by document analysis may be entered in the List of equipment, system and/or area classed as "potentially containing Hazardous Material" without the sampling check. The prerequisite for this classification is a comprehensible justification such as the impossibility of conducting sampling without compromising the safety of the ship and its operational efficiency).

Visual/sampling checkpoints should be all points where:

- the presence of materials to be considered for the Inventory Part I as listed in appendix 1 is likely;

- the documentation is not specific; or

- materials of uncertain composition were used.
RESOLUTION MEPC.197(62)
Adopted on 15 July 2011
2011 GUIDELINES FOR THE DEVELOPMENT OF THE INVENTORY
OF HAZARDOUS MATERIALSMEPC 62/24
Annex 3, page 6

I:\MEPC\62\24.doc
4.2.4 Onboard visual/sampling check (Step 4)

The onboard visual/sampling check should be carried out in accordance with the

---CHUNK---

SOURCE: MEPC.197(62).pdf
OF HAZARDOUS MATERIALSMEPC 62/24
Annex 3, page 6

4.2.4 Onboard visual/sampling check (Step 4)

The onboard visual/sampling check should be carried out in accordance with the visual/sampling check plan. When a sampling check is carried out, samples should be taken and the sample points should be clearly marked on the ship plan and the sample results referenced. Materials of the same kind may be sampled in a representative manner. Such materials are to be checked to ensure that they are of the same kind. The sampling check should be carried out drawing upon expert assistance.

Any uncertainty regarding the presence of Hazardous Materials should be clarified by a visual/sampling check. Checkpoints should be documented in the ship's plan and may be supported by photographs.

If the equipment, system and/or area of the ship are not accessible for a visual check or sampling check, they should be classified as " potentially containing Hazardous Material". The prerequisite for such classification should be the same prerequisite as in section 4.2.3. Any equipment, system and/or area classed as "potentially containing Hazardous Material"

---CHUNK---

SOURCE: MEPC.197(62).pdf
The prerequisite for such classification should be the same prerequisite as in section 4.2.3. Any equipment, system and/or area classed as "potentially containing Hazardous Material" may be investigated or subjected to a sampling check at the request of the shipowner during a later survey (e.g., during repair, refit or conversion).

4.2.5 Preparation of Part I of the Inventory and related documentation (Step 5)

If any equipment, system and/or area is classed as either "containing Hazardous Material" or "potentially containing Hazardous Material", their approximate quantity and location should be listed in Part I of the Inventory. These two categories should be indicated separately in the remarks column of the Inventory of Hazardous Materials.

4.2.6 Testing methods

Samples may be tested by a variety of methods. "Indicative" or "field tests" may be used when:

the likelihood of a hazard is high;
the test is expected to indicate that the hazard exists; and
the sample is being tested by "specific testing" to show that the hazard is present.

Indicative or field tests are quick, inexpensive and useful onboard the ship or on site, but they

---CHUNK---

SOURCE: MEPC.197(62).pdf
the sample is being tested by "specific testing" to show that the hazard is present.

Indicative or field tests are quick, inexpensive and useful onboard the ship or on site, but they

cannot be accurately reproduced or repeated, and cannot identify the hazard specifically, and therefore cannot be relied upon except as "indicators".

In all other cases, and in order to avoid disput e, "specific testing" should be used. Specific tests are repeatable, reliable and can demonstrate definitively whether a hazard exists or not. They will also provide a known type of the hazard. The methods indicated are found qualitative and quantitative appropriate and only testing methods to the same effect can be used. Specific tests are to be carried out by a suitably accredited laboratory, working to international standards or equivalent, which will provide a written report that can be relied upon by all parties.

Specific test methods for appendix 1 materials are provided in appendix 9.

For example ISO 17025.
RESOLUTION MEPC.197(62)
Adopted on 15 July 2011
2011 GUIDELINES FOR THE DEVELOPMENT OF THE INVENTORY

---CHUNK---

SOURCE: MEPC.197(62).pdf
For example ISO 17025.
RESOLUTION MEPC.197(62)
Adopted on 15 July 2011
2011 GUIDELINES FOR THE DEVELOPMENT OF THE INVENTORY
OF HAZARDOUS MATERIALSMEPC 62/24
Annex 3, page 7

I:\MEPC\62\24.doc
4.2.7 Diagram of the location of Hazardous Materials on board a ship

Preparation of a diagram showing the location of the materials listed in Table A is recommended in order to help Ship Recycling Facilities gain a visual understanding of the Inventory.

4.3 Maintaining and updating Part I of the Inventory during operations

4.3.1 Part I of the Inventory should be appropriately maintained and updated, especially after any repair or conversion or sale of a ship.

4.3.2 Updating of Part I of the Inventory in the event of new installation

If any machinery or equipment is added to, removed or replaced or the hull coating is renewed, Part I of the Inventory should be updated according to the requirements for new ships as stipulated in subsections 4.1.2 to 4.1.4. Updating is not required if identical parts or coatings are installed or applied.

4.3.3 Continuity of Part I of the Inventory

---CHUNK---

ships as stipulated in subsections 4.1.2 to 4.1.4. Updating is not required if identical parts or coatings are installed or applied.

4.3.3 Continuity of Part I of the Inventory

Part I of the Inventory should belong to the ship and the continuity and conformity of the information it contains should be confirmed, es pecially if the flag, owner or operator of the ship changes.

4.4 Development of Part II of the Inventory (operationally generated waste)

4.4.1 Once the decision to recycle a ship has been taken, Part II of the Inventory should be developed before the final survey, taking into account that a ship destined to be recycled shall conduct operations in the period prior to entering the Ship Recycling Facility in a manner that minimizes the amount of cargo residues, fuel oil and wastes remaining on board (regulation 8.2).

4.4.2 Operationally generated wastes to be listed in the Inventory

If the wastes listed in Part II of the Inventory provided in "Table C (Potentially hazardous items)" of appendix 1 are intended for delivery with the ship to a Ship Recycling Facility, the