https://edocs.imo.org/Final Documents/English/MEPC 68-21-ADD.1 (E).doc
4.3 Maintaining and updating part I of the Inventory during operations

4.3.1 Part I of the Inventory should be appropriately maintained and updated, especially after any repair or conversion or sale of a ship.

4.3.2 Updating of part I of the Inventory in the event of new installation

If any machinery or equipment is added to, removed or replaced or the hull coating is renewed, part I of the Inventory should be updated according to the requirements for new ships as stipulated in paragraphs 4.1.2 to 4.1.4. Updating is not required if identical parts or coatings are installed or applied.

4.3.3 Continuity of part I of the Inventory

Part I of the Inventory should belong to the ship and the continuity and conformity of the information it contains should be confirmed, especially if the flag, owner or operator of the ship changes.

---CHUNK---

SOURCE: MEPC.269(68).pdf
Part I of the Inventory should belong to the ship and the continuity and conformity of the information it contains should be confirmed, especially if the flag, owner or operator of the ship changes.

4.4 Development of part II of the Inventory (operationally generated waste)

4.4.1 Once the decision to recycle a ship has been taken, part II of the Inventory should be developed before the final survey, taking into account that a ship destined to be recycled shall conduct operations in the period prior to entering the Ship Recycling Facility in a manner that minimizes the amount of cargo residues, fuel oil and wastes remaining on board (regulation 8.2 of the Convention).

4.4.2 Operationally generated wastes to be listed in the Inventory

If the wastes listed in part II of the Inventory provided in table C (Potentially hazardous items) of appendix 1 are intended for delivery with the ship to a ship recycling facility, the quantity of the operationally generated wastes should be estimated and their approximate quantities and locations should be listed in part II of the Inventory.

4.5 Development of part III of the Inventory (stores)

---CHUNK---

SOURCE: MEPC.269(68).pdf
the operationally generated wastes should be estimated and their approximate quantities and locations should be listed in part II of the Inventory.

4.5 Development of part III of the Inventory (stores)

4.5.1 Once the decision to recycle has been taken, part III of the Inventory should be developed before the final survey, taking into account the fact that a ship destined to be recycled shall minimize the wastes remaining on board (regulation 8.2 of the Convention).

Each item listed in part III should correspond to the ship's operations during its last voyage.

4.5.2 Stores to be listed in the Inventory

If the stores to be listed in part III of the Inventory provided in table C of appendix 1 are to be delivered with the ship to a s hip recycling facility, the unit (e.g. capacity of cans and cylinders), quantity and location of the stores should be listed in part III of the Inventory.

4.5.3 Liquids and gases sealed in ship's machinery and equipment to be listed in the Inventory

If any liquids and gases listed in table C of appendix 1 are integral in machinery and

---CHUNK---

SOURCE: MEPC.269(68).pdf
4.5.3 Liquids and gases sealed in ship's machinery and equipment to be listed in the Inventory

If any liquids and gases listed in table C of appendix 1 are integral in machinery and equipment on board a ship, their approximate quantity and location should be listed in part III of the Inventory. However, small amounts of lubricating oil, anti-seize compounds and grease which are applied to or injected into machinery and equipment to maintain normal performance do not fall within the scope of this provision. For subsequent completion of

part III of the Inventory during the recycling preparation processes, the quantity of liquids and gases listed in table C of appendix 1 required for normal operation, including the related pipe system volumes, should be prepared and documented at the design and construction stage . This information belongs to the ship, and continuity of this information should be maintained

---CHUNK---

SOURCE: MEPC.269(68).pdf
system volumes, should be prepared and documented at the design and construction stage . This information belongs to the ship, and continuity of this information should be maintained if the flag, owner or operator of the ship changes.

4.5.4 Regular consumable goods to be listed in the Inventory

Regular consumable goods, as provided in table D of appendix 1 should not be listed in part I or part II but should be listed in part III of the Inventory if they are to be delivered with the ship to a Ship Recycling Facility. A general description including the name of item (e.g. TV set), manufacturer, quantity and location should be entered in part III of the Inventory. The check on materials provided for in paragraphs 4.1.2 and 4.1.3 of the se guidelines does not apply to regular consumable goods.

4.6 Description of location of hazardous materials on board

The locations of hazardous materials on board should be described and identified using the name of location (e.g. second floor of engine-room, bridge DK, APT, No.1 cargo tank , frame number) given in the plans (e.g. general arrangement, fire and safety plan, machinery arrangement or tank arrangement).

---CHUNK---

SOURCE: MEPC.269(68).pdf
name of location (e.g. second floor of engine-room, bridge DK, APT, No.1 cargo tank , frame number) given in the plans (e.g. general arrangement, fire and safety plan, machinery arrangement or tank arrangement).

4.7 Description of approximate quantity of hazardous materials

In order to identify the approximate quantity of hazardous materials, the standard unit used for hazardous materials should be kg, unless other units (e.g. m 3 for materials of liquid or gases, m 2 for materials used in floors or walls) are considered more appropriate .
An approximate quantity should be rounded up to at least two significant figures.

5 REQUIREMENTS FOR ASCERTAINING THE CONFORMITY OF THE INVENTORY

5.1 Design and construction stage

The conformity of part I of the Inventory at the design and construction stage should be ascertained by reference to the collected Supplier's Declaration of Conformity described in section 7 and the related Material Declarations collected from suppliers.

5.2 Operational stage

Shipowners should implement the following measures in order to ensure the conformity of part I of the Inventory:

---CHUNK---

SOURCE: MEPC.269(68).pdf
section 7 and the related Material Declarations collected from suppliers.

5.2 Operational stage

Shipowners should implement the following measures in order to ensure the conformity of part I of the Inventory:

.1 to designate a person as responsible for maintaining and updating the Inventory (the designated person may be employed ashore or on board);

.2 the designated person, in order to implement paragraph 4.3.2, should establish and supervise a system to ensure the necessary updating of the Inventory in the event of new installation;

.3 to maintain the Inventory including dates of changes or new deleted entries and the signature of the designated person; and

.4 to provide related documents as required for the survey or sale of the ship.
RESOLUTION MEPC.269(68)
(adopted on 15 May 2015)
2015 GUIDELINES FOR THE DEVELOPMENT OF THE
INVENTORY OF HAZARDOUS MATERIALSMEPC 68/21/Add.1
Annex 17, page 10

https://edocs.imo.org/Final Documents/English/MEPC 68-21-ADD.1 (E).doc
6 MATERIAL DECLARATION

6.1 General

Suppliers to the shipbuilding industry should identify and declare whether or not the materials

---CHUNK---

SOURCE: MEPC.269(68).pdf
Annex 17, page 10

https://edocs.imo.org/Final Documents/English/MEPC 68-21-ADD.1 (E).doc
6 MATERIAL DECLARATION