Part II
Operationally generated waste

| No. | Location1 | Name of item (classification in appendix 1) and detail (if any) of the item | Approximate quantity | | Remarks |
|---|---|---|---|---|---|
| 1 | Garbage locker | Garbage (food waste) | 35.00 | kg | |
| 2 | Bilge tank | Bilgewater | 15.00 | m3 | |
| 3 | No.1 cargo hold | Dry cargo residues (iron ore) | 110.00 | kg | |
| 4 | No.2 cargo hold | Waste oil (sludge) (crude) | 120.00 | kg | |
| 5 | No.1 ballast tank | Ballast water | 2,500.00 | m3 | |
| | | Sediments | 250.00 | kg | |

1 The location of a part II or part III item should be entered in order based on its location, from a lower level to an upper level and from a fore part to an aft part. The location of
part I items is recommended to be described similarly, as far as practicable.
RESOLUTION MEPC.269(68)
(adopted on 15 May 2015)
2015 GUIDELINES FOR THE DEVELOPMENT OF THE
INVENTORY OF HAZARDOUS MATERIALSMEPC 68/21/Add.1
Annex 17, page 19

---CHUNK---

SOURCE: MEPC.269(68).pdf
part I items is recommended to be described similarly, as far as practicable.
RESOLUTION MEPC.269(68)
(adopted on 15 May 2015)
2015 GUIDELINES FOR THE DEVELOPMENT OF THE
INVENTORY OF HAZARDOUS MATERIALSMEPC 68/21/Add.1
Annex 17, page 19

https://edocs.imo.org/Final Documents/English/MEPC 68-21-ADD.1 (E).doc
Part III
Stores
III-1 - Stores

| No. | Location1 | Name of item (classification in appendix 1) | Unit quantity | Figure | Approximate quantity | | Remarks2) |
|---|---|---|---|---|---|---|---|
| | | | m3 | | | | |
| | | | kg | | | | |
| | | | kg | | | | |
| | Details are shown in the attached list. | | | | | | |
| 5 | Paint stores | Paint, xx Co., #600 | 20.00 | kg | 5 | pcs 100.00 kg | Cadmium containing. |

1 The location of a part II or part III item should be entered in order based on its location, from a lower level to an upper l evel and from a fore part to an aft
part. The location of part I items is recommended to be described similarly, as far as practicable.
2 In column "Remarks" for part III items, if hazardous materials are integrated in products, the approximate amount of the cont ents should be shown as
far as possible.

RESOLUTION MEPC.269(68)
(adopted on 15 May 2015)
2015 GUIDELINES FOR THE DEVELOPMENT OF THE

---CHUNK---

SOURCE: MEPC.269(68).pdf
far as possible.

RESOLUTION MEPC.269(68)
(adopted on 15 May 2015)
2015 GUIDELINES FOR THE DEVELOPMENT OF THE
INVENTORY OF HAZARDOUS MATERIALSMEPC 68/21/Add.1
Annex 17, page 20

https://edocs.imo.org/Final Documents/English/MEPC 68-21-ADD.1 (E).doc

III-2 Liquids sealed in ship's machinery and equipment

| No. | Type of liquids (classification in appendix 1) | Name of machinery or equipment | Location | Approximate quantity | Remarks |
|---|---|---|---|---|---|
| 1 | Hydraulic oil | Deck crane hydraulic oil system | Upper deck | 15.00 m3 | |
| | | Deck machinery hydraulic oil system | Upper deck and bosun store | 200.00 m3 | |
| | | Steering gear hydraulic oil system | Steering gear room | 0.55 m3 | |
| 2 | Lubricating oil | Main engine system | Engine-room | 0.45 m3 | |
| 3 | Boiler water treatment | Boiler | Engine-room | 0.20 m3 | |

III-3 Gases sealed in ship's machinery and equipment

| No. | Type of gases (classification in appendix 1) | Name of machinery or equipment | Location | Approximate quantity | Remarks |
|---|---|---|---|---|---|
| 1 | HFC | AC system | AC room | 100.00 kg | |
| 2 | HFC | Refrigerated provision chamber machine | AC room | 50.00 kg | |

RESOLUTION MEPC.269(68)
(adopted on 15 May 2015)
2015 GUIDELINES FOR THE DEVELOPMENT OF THE

---CHUNK---

SOURCE: MEPC.269(68).pdf
1 HFC AC system AC room 100.00 kg
2 HFC Refrigerated provision chamber machine AC room 50.00 kg

RESOLUTION MEPC.269(68)
(adopted on 15 May 2015)

https://edocs.imo.org/Final Documents/English/MEPC 68-21-ADD.1 (E).doc

III-4 Regular consumable goods potentially containing hazardous materials

| No. | Location16 | Name of item | Quantity | Remarks |
|---|---|---|---|---|
| 1 | Accommodation | Refrigerators | 1 | |
| 2 | Accommodation | Personal computers | 2 | |

16 The location of a part II or part III item should be entered in order based on its location, from a lower level to an upper level and from a fore part to an aft part. The location of part I items is recommended to be described similarly, as far as practicable.

RESOLUTION MEPC.269(68)
(adopted on 15 May 2015)


https://edocs.imo.org/Final Documents/English/MEPC 68-21-ADD.1 (E).doc
APPENDIX 3

EXAMPLE OF THE DEVELOPMENT PROCESS FOR PART I

---CHUNK---

SOURCE: MEPC.269(68).pdf


https://edocs.imo.org/Final Documents/English/MEPC 68-21-ADD.1 (E).doc
APPENDIX 3

EXAMPLE OF THE DEVELOPMENT PROCESS FOR PART I
OF THE INVENTORY FOR NEW SHIPS

1 OBJECTIVE OF THE TYPICAL EXAMPLE

This example has been developed to give guidance and to facilitate understanding of the development process for part I of the Inventory of Hazardous Materials for new ships.

2 DEVELOPMENT FLOW FOR PART I OF THE INVENTORY

Part I of the Inventory should be developed using the following three steps. However, the

order of these steps is flexible and can be changed depending on the schedule of shipbuilding:

.1 collection of hazardous materials information;

.2 utilization of hazardous materials information; and

.3 preparation of the Inventory (by filling out standard format).

3 COLLECTION OF HAZARDOUS MATERIALS INFORMATION

3.1 Data collection process for hazardous materials

Materials Declaration (MD) and Supplier's Declaration of Conformity (SDoC) for products

---CHUNK---

SOURCE: MEPC.269(68).pdf
3 COLLECTION OF HAZARDOUS MATERIALS INFORMATION

3.1 Data collection process for hazardous materials

Materials Declaration (MD) and Supplier's Declaration of Conformity (SDoC) for products from suppliers (tier 1 suppliers) should be requested and collected by the shipbuilding yard. Tier 1 suppliers may request from their suppliers (tier 2 suppliers) the relevant information if they cannot develop the MD based on the information available. Thus the collection of data on hazardous materials may involve the entire shipbuilding supply chain (Figure 1).