https://edocs.imo.org/Final Documents/English/MEPC 68-21-ADD.1 (E).doc
Equipment Component of equipment
Light ballasts (component within fluorescent
light fixtures)

Plasticizers
Felt under septum plates on top of hull
bottom

2.2.3.4 Ozone depleting substances

The indicative list for ozone depleting substances is shown below. Ozone depleting substances have been controlled according to the Montreal Protocol and MARPOL Convention. Although

---CHUNK---

SOURCE: MEPC.269(68).pdf
bottom

2.2.3.4 Ozone depleting substances

The indicative list for ozone depleting substances is shown below. Ozone depleting substances have been controlled according to the Montreal Protocol and MARPOL Convention. Although
almost all substances have been banned since 1996, HCFC can still be used until 2020.

Materials Component of equipment Period for use of ODS in
Japan
CFCs (R11, R12) Refrigerant for refrigerators Until 1996
CFCs Urethane formed material Until 1996
Blowing agent for insulation of
LNG carriers
Until 1996
Halons Extinguishing agent Until 1994
Other fully halogenated
CFCs
The possibility of usage in
ships is low
Until 1996
Carbon tetrachloride The possibility of usage in
ships is low
Until 1996
1,1,1-Trichloroethane
(methyl chloroform)
The possibility of usage in
ships is low
Until 1996
HCFC (R22, R141b) Refrigerant for refrigerating
machine
It is possible to use it until 2020
HBFC The possibility of usage in

ships is low
Until 1996
Methyl bromide The possibility of usage in
ships is low
Until 2005

2.2.3.5 Organotin compounds

---CHUNK---

SOURCE: MEPC.269(68).pdf
machine
It is possible to use it until 2020
HBFC The possibility of usage in
ships is low
Until 1996
Methyl bromide The possibility of usage in
ships is low
Until 2005

2.2.3.5 Organotin compounds

Organotin compounds include tributyl tins (TBT), triphenyl tins (TPT) and tributyl tin oxide (TBTO). Organotin compounds have been used as anti-fouling paint on ships' bottoms and the International Convention on the Control of Harmful Anti-Fouling Systems on Ships (AFS Convention) stipulates that all ships shall not apply or re-apply organotin compounds after 1 January 2003, and that, after 1 January 2008, all ships shall either not bear such compounds on their hulls or shall bear a coating that forms a barrier preventing such compounds from leaching into the sea. The above-mentioned dates may have been extended by permission of the Administration bearing in mind that the AFS Convention entered into force on 17 September 2008.

2.2.4 Materials listed in table B

For existing ships it is not obligatory for materials listed in table B to be listed in part I of the Inventory. However, if they can be identified in a practical way , they should be listed in the

---CHUNK---

SOURCE: MEPC.269(68).pdf
2.2.4 Materials listed in table B

For existing ships it is not obligatory for materials listed in table B to be listed in part I of the Inventory. However, if they can be identified in a practical way , they should be listed in the Inventory, because the information will be used to support ship recycling processes. The Indicative list of materials listed in table B is shown below:
RESOLUTION MEPC.269(68)
(adopted on 15 May 2015)
2015 GUIDELINES FOR THE DEVELOPMENT OF THE
INVENTORY OF HAZARDOUS MATERIALSMEPC 68/21/Add.1
Annex 17, page 34

Materials Component of equipment
Cadmium and cadmium compounds Plating film, bearing
Hexavalent chromium compounds Plating film
Mercury and mercury compounds Fluorescent light, mercury lamp, mercury cell,
liquid-level switch, gyro compass, thermometer,
measuring tool, manganese cell, pressure sensors,
light fittings, electrical switches, fire detectors
Lead and lead compounds Corrosion resistant primer, solder (almost all
electric appliances contain solder), paints,
preservative coatings, cable insulation, lead
ballast, generators

---CHUNK---

SOURCE: MEPC.269(68).pdf
light fittings, electrical switches, fire detectors
Lead and lead compounds Corrosion resistant primer, solder (almost all
electric appliances contain solder), paints,
preservative coatings, cable insulation, lead
ballast, generators
Polybrominated biphenyls (PBBs) Non-flammable plastics
Polybrominated diphenyl ethers
(PBDE)
Non-flammable plastics
Polychlorinated naphthalenes Paint, lubricating oil
Radioactive substances Refer to appendix 10
Certain shortchain chlorinated paraffins Non-flammable plastics

3 STEP 2  ASSESSMENT OF COLLECTED INFORMATION

Preparation of a checklist is an efficient method for developing the Inventory for existing ships in order to clarify the results of each step. Based on collected information including the indicative list mentioned in step 1, all equipment, systems, and/or areas on board assumed to contain hazardous materials listed in tables A and B should be included in the checklist. Each listed equipment, system, and/or area on board should be analysed and assessed for its hazardous materials content.

The existence and volume of hazardous materials may be judged and calculated from the

---CHUNK---

SOURCE: MEPC.269(68).pdf
Each listed equipment, system, and/or area on board should be analysed and assessed for
its hazardous materials content.

The existence and volume of hazardous materials may be judged and calculated from the Spare parts and tools list and the maker's drawings. The existence of asbestos contained in floors, ceilings and walls may be identified from Fire Protection Plans, while the existence of TBT in coatings can be identified from the International Anti-Fouling System Certificate, Coating scheme and the History of Paint.

Example of weight calculation

No. Hazardous

Materials
Location/equipment/
component
Reference Calculation
1.1-2 TBT Flat bottom/paint History of
coatings

1.2-1 Asbestos Main engine/
exh. pipe packing
Spare parts and
tools list
250 g x 14 sheet = 3.50 kg
1.2-3 HCFC Ref. provision plant Maker's drawings 20 kg x 1 cylinder = 20 kg
1.2-4 Lead Batteries Maker's drawings 6kg x 16 unit = 96 kg
1.3-1 Asbestos Engine-room ceiling Accommodation
plan

When a component or coating is determined to contain hazardous materials, a "Y" should be entered in the column for "Result of document analysis" in the checklist, to denote

---CHUNK---