"Remarks" column of the Inventory.

---CHUNK---

SOURCE: MEPC.379(80).pdf
"potentially containing hazardous material", their approximate quantity and location should be listed in part I of the Inventory . These two categories should be indicated separately in the "Remarks" column of the Inventory.

4.2.10 Testing methods

4.2.10.1 Samples may be tested by a variety of methods. "Indicative" or "field tests" may be used when:

.1 the likelihood of a hazard is high;

.2 the test is expected to indicate that the hazard exists; and

.3 the sample is being tested by "specific testing" to show that the hazard is present.

4.2.10.2 Indicative or field tests are quick, inexpensive and useful on board the ship or on-site, but they cannot be accurately reproduced or repeated, and cannot identify the hazard specifically, and therefore cannot be relied upon except as "indicators".

4.2.10.3 In all other cases, and in order to avoid dispute, "specific testing" should be used. Specific tests are repeatable, reliable and can demonstrate definitively whether a hazard exists or not. They will also provide a known type of the hazard. The methods indicated are found

---CHUNK---

SOURCE: MEPC.379(80).pdf
Specific tests are repeatable, reliable and can demonstrate definitively whether a hazard exists or not. They will also provide a known type of the hazard. The methods indicated are found qualitative and quantita tive appropriate and only testing methods to the same effect can be used. Specific tests are to be carried out by a suitably accredited laboratory, working to international standards 2 or equivalent, which will provide a written report that can be relied upon by all parties.

4.2.10.4 Specific test methods for appendix 1 materials are provided in appendix 9.

4.2.11 Diagram of the location of hazardous materials on board a ship

Preparation of a diagram showing the location of the materials listed in table A is recommended in order to help ship recycling facilities gain a visual understanding of the Inventory.

2 For example ISO 17025.

---CHUNK---

SOURCE: MEPC.379(80).pdf

I:\MEPC\80\MEPC 80-17-Add.1.docx
4.3 Maintaining and updating part I of the Inventory during operations

4.3.1 Part I of the Inventory should be appropriately maintained and updated, especially after any repair or conversion or sale of a ship.

4.3.2 Updating of part I of the Inventory in the event of new installation

If any machinery or equipment is added to, removed or replaced or the hull coating is renewed, part I of the Inventory should be updated according to the requirements for new ships as stipulated in paragraphs 4.1.2 to 4.1.4. Updating is not required if identical parts or coatings are installed or applied.

4.3.3 Continuity of part I of the Inventory

Part I of the Inventory should belong to the ship and the continuity and conformity of the information it contains should be confirmed, especially if the flag, owner or operator of the ship changes.

4.4 Development of part II of the Inventory (operationally generated waste)

4.4.1 Once the decision to recycle a ship has been taken, part II of the Inventory should be

---CHUNK---

SOURCE: MEPC.379(80).pdf
changes.

4.4 Development of part II of the Inventory (operationally generated waste)

4.4.1 Once the decision to recycle a ship has been taken, part II of the Inventory should be developed before the final survey, taking into account that a ship destined to be recycled shall conduct operations in the period prior to entering the ship recycling facility in a manner that minimizes the amount of cargo residues, fuel oil and wastes remaining on board (regulation 8.2 of the Convention).

4.4.2 Operationally generated wastes to be listed in the Inventory

If the wastes listed in part II of the Inventory provided in table C (Potentially hazardous items) of appendix 1 are intended for delivery with the ship to a ship recycling facility, the quantity of the operationally generated wastes should be estimated and their approximate quantities and locations should be listed in part II of the Inventory.

4.5 Development of part III of the Inventory (stores)

4.5.1 Once the decision to recycle has been taken, part III of the Inventory should be developed before the final survey, taking into account the fact that a ship destined to be

---CHUNK---

SOURCE: MEPC.379(80).pdf
4.5 Development of part III of the Inventory (stores)

4.5.1 Once the decision to recycle has been taken, part III of the Inventory should be developed before the final survey, taking into account the fact that a ship destined to be recycled shall minimize the wastes remaining on board (regulation 8.2 of the Convention). Each item listed in part III should correspond to the ship's operations during its last voyage.

4.5.2 Stores to be listed in the Inventory

If the stores to be listed in part III of the Inventory provided in table C of appendix 1 are to be delivered with the ship to a ship recycling facility, the unit (e.g. capacity of cans and cylinders), quantity and location of the stores should be listed in part III of the Inventory.

4.5.3 Liquids and gases sealed in ship's machinery and equipment to be listed in the Inventory

If any liquids and gases listed in table C of appendix 1 are integral in machinery and equipment on board a ship, their approximate quantity and location should be listed in part III of the Inventory. However, small amounts of lubricating oil, anti-seize compounds and grease which

---CHUNK---

SOURCE: MEPC.379(80).pdf
on board a ship, their approximate quantity and location should be listed in part III of the Inventory. However, small amounts of lubricating oil, anti-seize compounds and grease which are applied to or injected into machinery and equipment to maintain normal performance do not fall within the scope of this provision. For subsequent completion of part III of the Inventory

during the recycling preparation processes, the quantity of liquids and gases listed in table C of appendix 1 required for normal operation, including the related pipe system volumes, should be prepared and documented at the design and construction stage. This information belongs to the ship, and continuity of this information should be maintained if the flag, owner or operator of the ship changes.

4.5.4 Regular consumable goods to be listed in the Inventory

Regular consumable goods, as provided in table D of appendix 1 should not be listed in part I

---CHUNK---

SOURCE: MEPC.379(80).pdf
of the ship changes.

4.5.4 Regular consumable goods to be listed in the Inventory

Regular consumable goods, as provided in table D of appendix 1 should not be listed in part I or part II but should be listed in part III of the Inventory if they are to be delivered with the ship to a ship recycling facility. A general description including the name of item (e.g. TV set), manufacturer, quantity and location should be entered in part III of the Inventory. The check on materials provided for in paragraphs 4.1.2 and 4.1.3 of these guidelines does not apply to regular consumable goods.

4.6 Description of location of hazardous materials on board

The locations of hazardous materials on board should be described and identified using the name of location (e.g. second floor of engine -room, bridge DK, APT, No.1 cargo tank , frame number) given in the plans (e.g. general arrangement, fire and safety plan, machinery arrangement or tank arrangement).

4.7 Description of approximate quantity of hazardous materials

In order to identify the approximate quantity of hazardous materials, the standard unit used for

---CHUNK---

SOURCE: MEPC.379(80).pdf