Fax: XXXX-XXXX
Email: abcdefg@hijk.co.net
Check schedule Visual check dd, mm, 20XX
Sampling check dd, mm, 20XX
Site of check XX shipyard, No. Dock
In charge of check XXXX XXXX
Check engineer XXXX XXXX, YYYY YYYY, ZZZZ ZZZZ
Sampling engineer Person with specialized knowledge of sampling
Sampling method and anti-scattering
measure for asbestos
Wet the sampling location prior to cutting and allow it

---CHUNK---

SOURCE: MEPC.379(80).pdf
Check engineer XXXX XXXX, YYYY YYYY, ZZZZ ZZZZ
Sampling engineer Person with specialized knowledge of sampling
Sampling method and anti-scattering
measure for asbestos
Wet the sampling location prior to cutting and allow it
to harden after cutting to prevent scatter.
Notes: Workers performing sampling activities shall
wear protective equipment.
Sampling of fragments of paints Paints suspected to contain TBT should be collected
and analysed from load line, directly under bilge keel
and flat bottom near amidships.
Laboratory QQQQ QQQQ
Chemical analysis method Method by ISO/DIS 22262-1 Bulk materials Part 1:
Sampling and qualitative determination of asbestos in
commercial bulk materials and ISO/CD 22262-2 Bulk
materials Part 2: Quantitative determination of
asbestos by gravimetric and microscopic methods.
ICP Luminous analysis (TBT)
Location of visual/sampling check Refer to lists for visual/sampling check

---CHUNK---

SOURCE: MEPC.379(80).pdf
RESOLUTION MEPC.379(80) (adopted on 7 July 2023)
2023 GUIDELINES FOR THE DEVELOPMENT OF THE INVENTORY OF HAZARDOUS MATERIALS MEPC 80/17/Add.1
Annex 18, page 40

I:\MEPC\80\MEPC 80-17-Add.1.docx

Listing for equipment, system and/or area for visual check
See attached "Analysis and definition of scope of investigation for sample ship"

List of equipment, system and/or area for sampling check
Location
Equipment,
machinery and/or
zone
Name of
parts Materials
Result of
doc.
checking
Upper deck Back deck ceilings Engine-room
ceiling
Asbestos Unknown
Engine-room Exhaust gas pipe Insulation Asbestos Unknown
Engine-room Pipe/flange Gasket Asbestos Unknown

Refer to attached "Analysis and definition of scope of investigation for sample ship" and
"Location plan of hazardous materials for sample ship"

List of equipment, system and/or area classed as PCHM
Location
Equipment,
machinery and/or
zone
Name of part Material
Result of
doc.
checking
Floor Propeller cap Gasket Asbestos PCHM
Engine-room Air operated shut-off
valve
Gland
packing
Asbestos PCHM

---CHUNK---

SOURCE: MEPC.379(80).pdf
Location
Equipment,
machinery and/or
zone
Name of part Material
Result of
doc.
checking
Floor Propeller cap Gasket Asbestos PCHM
Engine-room Air operated shut-off
valve
Gland
packing

Asbestos PCHM

Refer to attached "Analysis and definition of scope of investigation for sample ship" and "Location plan of hazardous materials for sample ship"

This plan is established in accordance with the guidelines for the development of the Inventory of Hazardous Materials

Document checkdate/place
dd, mm, 20XX at XX Lines Co. Ltd.

Preparation date of plandd. mm, 20XX

RESOLUTION MEPC.379(80) (adopted on 7 July 2023)
2023 GUIDELINES FOR THE DEVELOPMENT OF THE INVENTORY OF HAZARDOUS MATERIALS MEPC 80/17/Add.1
Annex 18, page 41

I:\MEPC\80\MEPC 80-17-Add.1.docx
5 STEP 4 ONBOARD VISUAL/SAMPLING CHECK

5.1 The visual/sampling check should be conducted according to the plan. Checkpoints should be marked in the ship's plan or recorded with photographs.

5.2 A person taking samples should be protected by the appropriate safety equipment

---CHUNK---

SOURCE: MEPC.379(80).pdf
5.1 The visual/sampling check should be conducted according to the plan. Checkpoints should be marked in the ship's plan or recorded with photographs.

5.2 A person taking samples should be protected by the appropriate safety equipment relevant to the suspected type of hazardous materials encountered. Appropriate safety precautions should also be in place for passengers, crew members and other persons on board, to min imize the potential exposure to hazardous materials. Safety precautions could include the posting of signs or other verbal or written notification for personnel to avoid such areas during sampling. The personnel taking samples should ensure compliance with relevant national regulations.

5.3 The results of visual/sampling checks should be recorded in the checklist. Any equipment, systems and/or areas of the ship that cannot be accessed for checks should be classified as "potentially containing hazardous material". In this case, the entry in the "Result of check" column should be "PCHM".

6 STEP 5 PREPARATION OF P ART I OF THE INVENTORY AND RELATED

DOCUMENTATION

6.1 Development of part I of the Inventory

---CHUNK---

SOURCE: MEPC.379(80).pdf
of check" column should be "PCHM".

6 STEP 5 PREPARATION OF P ART I OF THE INVENTORY AND RELATED DOCUMENTATION

6.1 Development of part I of the Inventory

The results of the check and the estimated quantity of hazardous materials should be recorded on the checklist. Part I of the Inventory should be developed with reference to the checklist.

6.2 Development of location diagram of hazardous materials

With respect to part I of the Inventory, the development of a location diagram of hazardous materials is recommended in order to help the ship recycling facility gain a visual understanding of the Inventory.

RESOLUTION MEPC.379(80) (adopted on 7 July 2023)