AMENDMENTS TO THE INTERNATIONAL CONVENTION FOR THE SAFETY OF LIFE AT SEA, 1974
Regulation Y/8_1 Ship reporting systems
1 The following new regulation V/B - l is added:
"Regulation 8-1
Ship reporting system s
(a) Ship reporting systems contribute to safety of life at sea, saf ety and efficiency of navigation, and protection of the marine envi ronment .

---CHUNK---

SOURCE: MSC.31(63).pdf
1 The following new regulation V/B - l is added:
"Regulation 8-1
Ship reporting system s
(a) Ship reporting systems contribute to safety of life at sea, saf ety and efficiency of navigation, and protection of the marine envi ronment .
A ship reporting system. when adopt ed and implement ed in accordan ce with the guidelines and criteria developed by the Organization pur sua n t to this regulation. shall be used by all ships. or certain cat egorie s of ships or ships carrying certain cargoes, in accordance with the provi si o ns of eac h system so adopted.
(b) The Organization is recognized as the only interna t ional body for developing guidelines, criteria and regulations on an internation a l level for ship reporting systems. Contracting Governments s h a l l refer proposa ls for the adoption of ship reporting systems to the Organizatio n . The Org anization wil l collate and disseminate to Contracting Governmen ts a l l relevan t i nfo rmation with regard to any adopted ship reporting system.
(c) This regulation and its associated guidelines an d criteria do no t apply to any warship, naval auxiliary or other vessel owned o r opera t ed by a

---CHUNK---

SOURCE: MSC.31(63).pdf
with regard to any adopted ship reporting system.
(c) This regulation and its associated guidelines an d criteria do no t apply to any warship, naval auxiliary or other vessel owned o r opera t ed by a Contracting Government and used, for the time being , only on government non-commercial service ; however, such ships are encouraged to par tic ipate in ship reporting systems that have been adopted in acco rdan ce with this regUlation.
(d) The initiation of action for establishing a ship reporting system is the responsibility of the Government or Governments con ce rned. In developing such systems , pro v isions of the guidelines and criteria de veloped by the Organization shall be taken into account.
(e) Ship reporting systems not submitted to the Organization for adoption do not necessarily need to comply with this regulation. Howeve r, Governments implementing such systems are encouraged to follow, wherever possible, the guidelines and criteria developed by the Organization. Contracting Governments may submit such systems to the Organization for recognition.
(f) Where two or more Governments have a common interest in a particular

---CHUNK---

SOURCE: MSC.31(63).pdf
guidelines and criteria developed by the Organization. Contracting Governments may submit such systems to the Organization for recognition.
(f) Where two or more Governments have a common interest in a particular area, they should formulate proposals for a co-ordinated ship reporting system on the basis of agreement between them. Before proceeding with a proposal fo r adoption of a ship reporting system, the Organization shall disseminate details of the proposal to those Governments which have a common interest in the area covered by the proposed system. Where a co-ordinated ship reporting system is adopted and established, it shall have un i form pr oc edure s an d opera.tions.
RESOLUTION MSC.31(63)
adopted on 23 May 1994
ADOPTION OF AMENDMENTS TO THE INTERNATIONAL CONVENTION FOR THE SAFETY OF LIFE AT SEA, 1974 - 4 -
(g) After adoption of a ship reporting system in accordance with this regulation, the Government or Government s con cern ed shall take al l measu res necessary for the promulgation of any information needed for the eff i c ient an d eff ecti ve use of the system. Any adopted ship rep ort ing system shall have the

---CHUNK---

SOURCE: MSC.31(63).pdf
regulation, the Government or Government s con cern ed shall take al l measu res necessary for the promulgation of any information needed for the eff i c ient an d eff ecti ve use of the system. Any adopted ship rep ort ing system shall have the capability of interaction and the ability to assist s hips with information when nece ssary. Such systems shall be oper ated in accor dan ce wi th th e guidelines and c riteria developed by the Or gan iz at i on pursu a nt to t hi s regulation .
(h) The master of a ship s ha l l comp ly wi t h the req u irements of adop ted s hi p reporting syste ms and report to the appropriate auth or ity a l l i nformation required in ac cordance with the p rovis i ons o f each suc h sys tem.
(i) Al l adopted ship r e po rt ing sys t ems and a ctions taken to enf or ce complian ce with those systems sha l l b e consistent wit h internati onal la\>,', including the releva nt pr ov i s ions of the United Natio ns Convention on the Law of the Sea. .
(j) Noth i ng in this regulation or i n its associated guide lin es and c r ite ri a s hall prejudice the rights and duties of Gover nments under intern ationa l law,

---CHUNK---

SOURCE: MSC.31(63).pdf
Law of the Sea. .
(j) Noth i ng in this regulation or i n its associated guide lin es and c r ite ri a s hall prejudice the rights and duties of Gover nments under intern ationa l law, or the legal regime of international stra i ts.
(k) The participation of ships in accordance with the provision s of adopted ship reporting s ystems s hall be free of c ha rge to the s hip s concer ned .
(1) The Orga nization shall ensure that adopted ship repo rti ng sy s tems a re reviewed under the guideline s and c riteria develope d by the Organizat io n."
Regulation y/ lS _l _ Emergency towing arrangements gn tanker s
2 The f ollowi ng new regulation V/15 - 1 is added:
" Regulat ion 15 - 1

Emergen cy towing a rrangements on tankers
(a) For the purpose of this reg ul ation, tankers include oil tanke r s as defined in regulation 11 - 1 / 2.12; chemical tan ker s as defined in regulation V11 /B .2 and gas carriers as defined in re gul ation V11 /1 l . 2 .
(b) An emergency tow i ng arrangement shall be fitte d at both end s on boar d all tankers of not less than 20;000 tonnes deadweight as defined in regulation 11-1/3.21 constru c ted on or after 1 January 1996. Fo r tankers

---CHUNK---

SOURCE: MSC.31(63).pdf
(b) An emergency tow i ng arrangement shall be fitte d at both end s on boar d all tankers of not less than 20;000 tonnes deadweight as defined in regulation 11-1/3.21 constru c ted on or after 1 January 1996. Fo r tankers
constructed before 1 Janua ry 1996, such an arrangement shall be fitted at the first scheduled dry-docking after 1 January 1996, but not later than 1 January 1999. The design and construction of the towing arrangement sha l l be approved by the Administration , based on the guide l ines developed by the Organization."
RESOLUTION MSC.31(63)
adopted on 23 May 1994
ADOPTION OF AMENDMENTS TO THE INTERNATIONAL CONVENTION FOR THE SAFETY OF LIFE AT SEA, 1974 - 5 -
ANNEX 2
AMENDMENTS TO THE INTE:RNATIONAL CONVENTION FOR THE SAFETY OF LI~E AT SEA. 1974
Regulatign II_VIS - Arrangements fOf oil fuel. lubricating oil and other flammable gils
1 The following text is added after the title:
"(Paragraphs 2.9 to 2.12 of this regulation apply to all ships)"
2 The following Dew subparagraphs .9 to .12 are added after existing subparagraph .8 of paragraph 2:
".9 All external high pressure fuel delivery lines bet~een the high

---CHUNK---

SOURCE: MSC.31(63).pdf
"(Paragraphs 2.9 to 2.12 of this regulation apply to all ships)"
2 The following Dew subparagraphs .9 to .12 are added after existing subparagraph .8 of paragraph 2:
".9 All external high pressure fuel delivery lines bet~een the high
pressure fuel pumps and fuel injector s shall be protected with a jacketed piping system capable of containing fuel from a high pressure line failure. A jacketed pip e incorporates a n outer pipe into whi c h the high pressure fu el pipe is placed form ing a permanent assembly. The jack eted piping system shal l include a means for collection of leakages and arrangements shall be provided for an alarm to be given of a fuel l ine failure,
. 10 All surfaces with temperatures above 220·C which may be imp inged as a result of a fuel system failure shall be proper l y i nsu lated .
11 Oil fuel lines shall be screened or otherwise suitably pro tected to avoid as far as practicable oil spray or oil leakage s onto hot surfaces, into machinery air intakes, or other sources of ignition. The number of joints in such piping system s shal l be

kept to a minimum .
. 12 Ships constructed before 1 July 1998 sh a ll comply wit h the

---CHUNK---

SOURCE: MSC.31(63).pdf
hot surfaces, into machinery air intakes, or other sources of
ignition. The number of joints in such piping system s shal l be
kept to a minimum .
. 12 Ships constructed before 1 July 1998 sh a ll comply wit h the
requirements of paragraphs 2.9 to Z.ll not later than 1 July Z003,
ezcept that a suitable enclosure on engine s having an output of
375 kW or less having fuel injection pumps se rving more than one
injector may be used as an alternative to the jackete d piping
system in paragrapb 2.9. "
3 The words "Z.7 and 2.6" in the 8zisting parag raph 3 are rep laced
by "2.7. 2.6, 2.10 and 2.11".
4 The words "2.4 and 2.6" in the existing paragraph 4 are replaced
by "Z.4. 2.6, 2.10 and 2. 11".
5 The ezisting paragraph 5.1 is deleted, and paragraphs 5.2 and 5.3 are
r enumber ed 5,1 and 5.2 .
Regulatign V/3 _ Informotion required in danger mes sages
6 In paraqraph (b). the phrase "Tropical storms (hurricane s in the Wes t