a list to be approved by the Administration. Pressures at which the pressure relief valves, including those valves required by 8.3, have been set should also be stated on the list. A copy of the list should be permanently kept on board by the master.
15.3 Chapter XV applies to all ships regardless of the date of construction. ,.
2 The following words are added at the end of existing paragraph 8.2.17: "at the maximum allowable filling limit (FL)".
W/1648n/EWP
RESOLUTION MSC.34(63)
adopted on 23 May 1994
ADOPTION OF AMENDMENTS TO THE CODE FOR THE CONSTRUCTION AND EQUIPMENT OF SHIPS CARRYING LIQUEFIED GASES IN BULK MSC 63/23/Add.l
ANNEX 5
Page 4

---CHUNK---

SOURCE: MSC.34(63).pdf
W/1648n/EWP
RESOLUTION MSC.34(63)
adopted on 23 May 1994
ADOPTION OF AMENDMENTS TO THE CODE FOR THE CONSTRUCTION AND EQUIPMENT OF SHIPS CARRYING LIQUEFIED GASES IN BULK MSC 63/23/Add.l
ANNEX 5
Page 4
3 The following new paragraphs 8.2.IS and 8.2.19 are added after existing paragraph 8.2.17:
"S.2.18 The adequacy of the vent system fitted on tanks loaded in accordance with 15.1.5 is to be demonstrated using the guidelines developed by the Organization~. A relevant certificate should be permanently kept on board the ship. For the purposes of this paragraph, vent system means:
(a) the tank outlet and the piping to the pressure relief valve;
(b) the pressure relief valve;
(c) the piping from the pressure relief valve to the location of discharge to the atmosphere and including any interconnections and piping which joins other tanks.
8.2.19 Paragraphs 8.2.17 and 8.2.18 apply, where applicable, to all ships regardless of the date of construction."
Refer to the guidelines to be developed by the Organization.
W/164Sn/EWP
RESOLUTION MSC.34(63)
adopted on 23 May 1994
ADOPTION OF AMENDMENTS TO THE CODE FOR THE CONSTRUCTION AND EQUIPMENT OF SHIPS CARRYING

---CHUNK---

SOURCE: MSC.34(63).pdf
Refer to the guidelines to be developed by the Organization.
W/164Sn/EWP
RESOLUTION MSC.34(63)

adopted on 23 May 1994
ADOPTION OF AMENDMENTS TO THE CODE FOR THE CONSTRUCTION AND EQUIPMENT OF SHIPS CARRYING LIQUEFIED GASES IN BULK RESOLUTION MSC.34(63)
adopted on 23 May 1994
ADOPTION OF AMENDMENTS TO THE CODE FOR THE CONSTRUCTION AND EQUIPMENT OF SHIPS CARRYING LIQUEFIED GASES IN BULK

---CHUNK---

SOURCE: MSC.35(63).pdf
RESOLUTION MSC.35(63)
(adopted on 20 May 1994)
ADOPTION OF GUIDELINES FOR EMERGENCY TOWING ARRANGEMENTS ON TANKERS ANNEX 7
RESOLUTION MSC.35(63)
(adopted on 20 May 1994)
ADOPTION OF GUIDELINES FOR EMERGENCY TOWING ARRANGEMENTS ON TANKERS
THE MARITIME SAFETY COMMITTEE,
MSC 63/23/Add.1
RECALLING Article 28(b) of the Convention on the International Maritime Organization concerning the functions of the Committee,
RECALLING ALSO that the Assembly, at its thirteenth session, when adopting resolution A.535(13) concerning Recommendation on emergency towing requirements for tankers, requested the Committee to keep the Recommendation under review, in particular in respect to new towing concepts which may be introduced and to report as necessary to the Assembly,
NOTING that tankers, including oil tankers, gas carriers and chemical tankers, in emergencies such as complete mechanical breakdowns, may need to be towed out of danger, and that technologically advanced towing arrangements have been developed since the adoption of resolution A.535(13), whose provisions need revision to incorporate new towing concepts,

---CHUNK---

SOURCE: MSC.35(63).pdf
towed out of danger, and that technologically advanced towing arrangements have been developed since the adoption of resolution A.535(13), whose provisions need revision to incorporate new towing concepts,
NOTING ALSO that the new regulation V/15-1 of the International Convention for the Safety of Life at Sea, 1974, as adopted by the Committee in May 1994, requires that all tankers of not less than 20,000 tonnes deadweight shall be fitted with an emergency towing arrangement, the design and construction of which shall be approved by the Administration based on the Guidelines developed by the Organization,
HAVING CONSIDERED the recommendation made by the Sub-Committee on Ship Design and Equipment at its thirty-seventh session,
1. ADOPTS the Guidelines for Emergency Towing Arrangements on Tankers, the text of which is set out in the Annex to the present resolution and which supersedes resolution A.535(13);
2. RECOMMENDS that all Governments concerned take appropriate steps to implement the Guidelines.

---CHUNK---

SOURCE: MSC.35(63).pdf
implement the Guidelines.
WII648n/EWP
RESOLUTION MSC.35(63)
(adopted on 20 May 1994)
ADOPTION OF GUIDELINES FOR EMERGENCY
TOWING ARRANGEMENTS ON TANKERS MSC 63/23/Add.l
ANNEX 7
Page 2
1 PURPOSE
ANNEX
GUIDELINES FOR EMERGENCY TOWING
ARRANGEMENTS ON TANKERS
1.1 Under regulation V/15-1 of the 1974 SOLAS Convention, as amended by resolution MSC.31(63) in 1994, new and existing tankers of 20,000 tonnes deadweight and above shall be fitted with an emergency towing arrangement, the design and construction of which shall be approved by the Administration, based on the Guidelines developed by the Organization.
1.2 The present Guidelines are intended to provide standards for the design and construction of emergency towing arrangements which Administrations are recommended to implement.
1.3 For existing tankers fitted with the emergency towing arrangements in accordance with resolution A.535(13), the existing towing arrangements forward of the ship may be retained, but the towing arrangements aft of the ship should be upgraded to comply with the requirements of the present Guidelines.
2 REQUIREMENTS FOR THE ARRANGEMENTS AND COMPONENTS
2.1 General

---CHUNK---

SOURCE: MSC.35(63).pdf
of the ship may be retained, but the towing arrangements aft of the ship should be upgraded to comply with the requirements of the present Guidelines.
2 REQUIREMENTS FOR THE ARRANGEMENTS AND COMPONENTS
2.1 General
The emergency towing arrangements should be so designed as to facilitate salvage and emergency towing operations on tankers primarily to reduce the risk of pollution. The arrangements should at all times be capable of rapid deployment in the absence of main power on the ship to be towed and easy connection to the towing vessel. Figure 1 shows arrangements which may be used as reference.
2.2 Towing components
The major components of the towing arrangements should consist of the following:

Forward of ship''' Aft of ship
Pick-up gear
Towing pennant
Chafing gear
Fairlead
Strongpoint
Roller pedestal
optional
optional
Yes
Yes
Yes
Yes
See paragraph 3.1.4.
W/1648n/EWP
Yes
Yes
Depending on design
Yes
Yes
Depending on design
Strength requirements
Yes