and the certificate will be reissued.
2 The traditional method of regulating ships should not be accepted as being the only possible way of providing an appropriate level of safety. Nor should it be assumed that another approach, using different criteria, could not be applied. Over a long period of years, numerous new designs of marine vehicles have been developed and have been in service. While these do not fully comply with the provisions of the international conventions relating to conventional ships built of steel, they have demonstrated an ability to operate at an equivalent level of safety when engaged on restricted voyages under restricted operational weather conditions and with approved maintenance and supervision schedules.

---CHUNK---

SOURCE: MSC.36(63).pdf
operate at an equivalent level of safety when engaged on restricted voyages under restricted operational weather conditions and with approved maintenance and supervision schedules.
3 This Code has been derived from the previous Code of Safety for Dynamically Supported Craft (DSC) adopted by IMO in 1977. The Code recognized that safety levels can be significantly enhanced by the infrastructure associated with regular service on a particular route, whereas the conventional ship safety philosophy relies on the ship being self-sustaining with all necessary emergency equipment being carried on board. This revised Code has been prepared in recognition of the growth in size and types of high speed craft now existing and is intended to facilitate future research and development of fast sea transportation in order that they may be accepted internationally.
4 The safety philosophy of this Code is based on the management and reduction of risk as well as the traditional philosophy of passive protection in the event of an accident. Management of risk through accommodation arrangement, active safety systems, restricted operation, quality management

---CHUNK---

SOURCE: MSC.36(63).pdf
reduction of risk as well as the traditional philosophy of passive protection in the event of an accident. Management of risk through accommodation arrangement, active safety systems, restricted operation, quality management and human factors engineering should be considered in evaluating safety equivalent to current conventions. Application of mathematical analysis should be encouraged to assess risk and determine the validity of safety measures.
5 The Code takes into account that a high speed craft is of a light displacement compared with a conventional ship. This displacement aspect is the essential parameter to obtain fast and competitive sea transportation and consequently this Code allows for use of non-conventional shipbuilding materials, provided that a safety standard at least equivalent to conventional ships is achieved.
W/1576n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT MSC 631231 Add. 2

6 To clearly distinguish such craft, criteria based on speed and volumetric Froude number have been used to delineate those craft to which this Code

---CHUNK---

SOURCE: MSC.36(63).pdf
FOR HIGH SPEED CRAFT MSC 631231 Add. 2
ANNEX 18
Page 10
6 To clearly distinguish such craft, criteria based on speed and volumetric Froude number have been used to delineate those craft to which this Code applies from other, more conventional, craft.
7 The Code requirements also reflect the additional hazards which may be caused by the high speed compared with conventional ship transportation. Thus, in addition to the normal requirements including life-saving appliances, evacuation facilities, etc., provided in case of an accident occurring, further emphasis is placed on reducing the risk of hazardous situations ar~s~ng. Some advantages result from the high speed craft concept, i.e. the light displacement provides a large reserve buoyancy in relation to displacement, reducing the hazards addressed by the International Load Line Convention. The consequences of other hazards such as of collision at high speed are balanced by more stringent navigational and operational requirements and specially developed accommodation provisions.
8 The above-mentioned safety concepts were originally reflected in the Code

---CHUNK---

SOURCE: MSC.36(63).pdf
speed are balanced by more stringent navigational and operational requirements and specially developed accommodation provisions.
8 The above-mentioned safety concepts were originally reflected in the Code of Safety for Dynamically Supported Craft. The development of novel types and sizes of craft has led to the development of pressures within the maritime industry for craft which are not dynamically supported cargo craft, passenger craft carrying larger numbers of passengers or operating further afield than permitted by that Code to be certified according to those concepts. Additionally, improvements of maritime safety standards since 1977 were required to be reflected in the revisions of the Code to maintain safety equivalence with conventional ships.
9 Accordingly, two differing principles of protection and rescue were developed.
10 The first of these recognizes the craft which were originally foreseen at the time of development of the DSC Code. Where rescue assistance is readily available and the total number of passengers is limited, a reduction in passive and active protection may be permitted. Such craft are called

---CHUNK---

SOURCE: MSC.36(63).pdf
the time of development of the DSC Code. Where rescue assistance is readily available and the total number of passengers is limited, a reduction in passive and active protection may be permitted. Such craft are called

"assisted craft" and form the basis for "category A passenger craft" of this Code.

11 The second concept recognizes the further development of high speed craft into larger craft. Where rescue assistance is not readily available or the number of passengers is unlimited, additional passive and active safety precautions are required. These additional requirements provide for an area of safe refuge on board, redundancy of vital systems, increased watertight and structural integrity and full fire-extinguishing capability. Such craft are called "unassisted craft" and form the basis for "cargo craft" and "category B passenger craft" of this Code.

12 These two concepts of the Code have been developed as a unified document on the basis that an equivalent level of safety to that normally expected on ships complying with the International Convention for the Safety of Life at Sea is achieved. Where the application of new technology or design indicates

---CHUNK---

SOURCE: MSC.36(63).pdf

on the basis that an equivalent level of safety to that normally expected on ships complying with the International Convention for the Safety of Life at Sea is achieved. Where the application of new technology or design indicates an equivalent safety level to the strict application of the Code, the Administration is permitted to formally recognize such equivalence.

13 It is important that an Administration, in considering the suitability of a high speed craft under this Code, should apply all sections of the Code because non-compliance with any part of the Code could result in an imbalance which would adversely affect the safety of the craft, passengers and crew. For a similar reason, modifications to existing craft; which may have an effect on safety, should be approved by the Administration.

14 In developing the Code, it has been considered desirable to ensure that high speed craft do not impose unreasonable demands on existing users of the

---CHUNK---

SOURCE: MSC.36(63).pdf

effect on safety, should be approved by the Administration.
14 In developing the Code, it has been considered desirable to ensure that high speed craft do not impose unreasonable demands on existing users of the environment or conversely suffer unnecessarily through lack of reasonable accommodation by existing users. Whatever burden of compatibility there is, it should not necessarily be laid wholly on the high speed craft.

CHAPTER 1 - GENERAL COMMENT AND REQUIREMENTS
1.1 General comments
This Code should be applied as a complete set of comprehensive requirements. It contains requirements for the design and construction of high speed craft engaged on international voyages, the equipment which should be provided and the conditions for their operation and maintenance. The basic aim of the Code is to set levels of safety which are equivalent to those of conventional ships required by the International Convention for the Safety of Life at Sea, 1974, as amended,

---CHUNK---

SOURCE: MSC.36(63).pdf
maintenance. The basic aim of the Code is to set levels of safety which are equivalent to those of conventional ships required by the International Convention for the Safety of Life at Sea, 1974, as amended, (SOLAS Convention) and International Convention on Load Lines, 1966 (Load Line Convention) by the application of constructional and equipment standards in conjunction with strict operational controls.
1.2 General reguiremen~
The application of the provisions of this Code is subject to the