following general requirements that:
.1 the Code will be applied in its entirety;
.2 the management of the company operating the craft exercises strict control over its operation and maintenance by a quality management system"';
.3 the management ensures that only persons qualified to operate the specific type of craft used on the intended route are employed;
.4 the distances covered and the worst intended conditions in which operations are permitted will be restricted by the imposition of operational limits;
.5 the craft will at all times be in reasonable proximity to a place of refuge;
.6 adequate communications facilities, weather forecasts and

---CHUNK---

SOURCE: MSC.36(63).pdf
operations are permitted will be restricted by the imposition of operational limits;
.5 the craft will at all times be in reasonable proximity to a place of refuge;
.6 adequate communications facilities, weather forecasts and maintenance facilities are available within the area of operation;
.7 in the intended area of operation there will be suitable rescue facilities readily available;
.8 areas of high fire risk such as machinery spaces and special category spaces are protected with fire-resistant materials and fire-extinguishing systems to ensure, as far as is practicable, containment and rapid extinguishing of fire;
.9 efficient facilities are provided for the rapid and safe evacuation of all persons into survival craft;
.10 that all passengers and crew are provided with seats;
Refer to the International Safety Management (ISM) Code adopted by the Organization by resolution A.74l(18).
W/1576n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT MSC 63/23/Add.2
ANNEX 18
Page 13
.11 that no enclosed sleeping berths for passengers are provided;

---CHUNK---

SOURCE: MSC.36(63).pdf
W/1576n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT MSC 63/23/Add.2
ANNEX 18
Page 13
.11 that no enclosed sleeping berths for passengers are provided;

.12 where the Administration has made a comprehensive review of the adequacy of the fire safety measures and evacuation procedures for the crew accommodation, sleeping berths for crew may be permitted.
1. 3 Application
1.3.1 This Code applies to high speed craft which are engaged in international voyages.
1.3.2 This Code applies to:
1. 3.3
1. 3.4
1. 3.5
.1 passenger craft which do not proceed in the course of their voyage more than 4 h at operational speed from a place of refuge when fully laden; and
.2 cargo craft of 500 gross tonnage and upwards which do not proceed in the course of their voyage more than 8 h at operational speed from a place of refuge when fully laden.
This Code, unless expressly provided otherwise, does not apply to:
.1 craft of war and troopcraft;
.2 craft not propelled by mechanical means;
.3 wooden craft of primitive built;
.4 pleasure craft not engaged in trade; and
.5 fishing craft.

---CHUNK---

SOURCE: MSC.36(63).pdf
This Code, unless expressly provided otherwise, does not apply to:
.1 craft of war and troopcraft;
.2 craft not propelled by mechanical means;
.3 wooden craft of primitive built;
.4 pleasure craft not engaged in trade; and
.5 fishing craft.
This Code does not apply to craft solely navigating the Great Lakes of North America and the River St. Lawrence as far east as a straight line drawn from Cap des Rosiers to West Point, Anticosti Island and, on the north side of Anticosti Island, the 63rd meridian.
The application of this Code should be verified by the Administration and be acceptable to the Governments of the States to which the craft will be operating.
1.4 Definitions
1.4.1
1. 4.2
For the purpose of this Code, unless expressly provided otherwise, the terms used therein have the meanings defined in the following paragraphs. Additional definitions are given in the general parts of the various chapt.ers.
"Administration" means the Government of the State whose flag the craft is entitled to fly.
"Air-cushion vehicle" (ACV) is a craft such that the whole or a significant part of its weight can be supported, whether at rest or

---CHUNK---

SOURCE: MSC.36(63).pdf

chapt.ers.
"Administration" means the Government of the State whose flag the craft is entitled to fly.
"Air-cushion vehicle" (ACV) is a craft such that the whole or a significant part of its weight can be supported, whether at rest or in motion, by a continuously generated cushion of air dependent for its effectiveness on the proximity of the surface over which the craft operates.
W/1576n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT MSC 63/23/Add.2
ANNEX 18
Page 14
1.4.3
1.4.4
1.4.5
1.4.6
1.4.7
1.4.8
1.4.9
1. 4 .10
"Auxiliary machinery spaces" are spaces containing internal combustion engines of power output up to and including 110 kW driving generators, sprinkler, drencher or fire pumps, bilge pumps, etc., oil filling stations, switchboards of aggregate capacity exceeding 800 kW, similar spaces and trunks to such spaces.
"Auxiliary machinery spaces having little or no fire risk" are spaces such as refrigerating, stabilizing, ventilation and air conditioning machinery, switchboards of aggregate capacity 800 kW or less, similar spaces and trunks to such spaces.

---CHUNK---

SOURCE: MSC.36(63).pdf
"Auxiliary machinery spaces having little or no fire risk" are spaces such as refrigerating, stabilizing, ventilation and air conditioning machinery, switchboards of aggregate capacity 800 kW or less, similar spaces and trunks to such spaces.
"Base port" is a specific port identified in the route operational manual and provided with:
.1 appropriate facilities providing continuous radio communications with the craft at all times while in ports and at sea;
.2 means for obtaining a reliable weather forecast for the corresponding region and its due transmission to all craft in operation;
.3 for a category A craft, access to facilities provided with approp~iate rescue and survival equipment; and
.4 access to craft maintenance services with appropriate equipment.
"Base port State" means the State in which the base port is located.
"Breadth (B)" means breadth of the broadest part of the moulded watertight envelope of the rigid hull, excluding appendages, at or below the design waterline in the displacement mode with no lift

or propulsion machinery active.
"Cargo craft" is any high speed craft other than passenger craft,

---CHUNK---

SOURCE: MSC.36(63).pdf
watertight envelope of the rigid hull, excluding appendages, at
or below the design waterline in the displacement mode with no lift
or propulsion machinery active.
"Cargo craft" is any high speed craft other than passenger craft,
and which is capable of maintaining the main functions and safety
systems of unaffected spaces, after damage in anyone compartment
on board.
"Cargo spaces" are all spaces other than special category spaces
used for cargo and trunks to such spaces.
"Category A craft" is any high speed passenger craft:
. 1 operating on a route where it has been demonstrated to the
satisfaction of the flag and port States that there is a high
probability that in the event of an evacuation at any point of
the route, all passengers and crew can be rescued safely within
the least of:
the time to prevent persons in survival craft from exposure
causing hypothermia in the worst intended conditions,