the time appropriate with respect to environmental
conditionS and geographical features of the route, or
4 h; and
.2 carrying not more than 450 passengers.
WII576n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY

---CHUNK---

SOURCE: MSC.36(63).pdf
conditionS and geographical features of the route, or
4 h; and
.2 carrying not more than 450 passengers.
WII576n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT 1.4.11
1. 4.12
1.4.13
1. 4 .14
1. 4 .15
1. 4 .16
1.4.17
1. 4 .18
1.4.19
1. 4.20
1. 4.21
MSC 63/23/Add.2
ANNEX 18
Page 15
"Category B craft" is any high speed passenger craft, other than a category A craft, with machinery and safety systems arranged such that, in the event of damage disabling any essential machinery and safety systems in one compartment, the craft retains the capability to navigate safely.
"Continuously manned control station" is a control station which is continuously manned by a responsible member of the crew while the craft is in normal service.
"Control stations" are those spaces in which the craft's radio or navigating equipment or the emergency source of power and emergency switchboard are located, or where the fire recording or fire control equipment is centralized, or where other functions essential to the safe operation of the craft such as propulsion control, public

---CHUNK---

SOURCE: MSC.36(63).pdf
switchboard are located, or where the fire recording or fire control
equipment is centralized, or where other functions essential to the
safe operation of the craft such as propulsion control, public
address, stabilization systems, etc., are located.

"Convention" means the International Convention for the Safety of Life at Sea, 1974, as amended.
"Crew accommodation" are those spaces allocated for the use of the crew, and include cabins, sick bays, offices, lavatories, lounges and similar spaces.
"Critical design conditions" means the limiting specified conditions chosen for design purposes, which the craft should keep in displacement mode. Such conditions should be more severe than the worst intended conditions by a suitable margin to provide for adequate safety in survival condition.
"Design waterline" means the waterline corresponding to the maximum operational weight of the craft with no lift or propulsion machinery active and is limited by the requirements of chapters 2 and 3.
"Displacement mode" means the regime, whether at rest or in motion, where the weight of the craft is fully or predominantly supported by hydrostatic forces.

---CHUNK---

SOURCE: MSC.36(63).pdf
active and is limited by the requirements of chapters 2 and 3.
"Displacement mode" means the regime, whether at rest or in motion, where the weight of the craft is fully or predominantly supported by hydrostatic forces.
"Failure mode and effect analysis (FMEA)" is an examination, in accordance with annex 4, of the craft's systems and equipment to determine whether any reasonably probable failure or improper operation can result in a hazardous or catastrophic effect.
"Flap" means an element formed as integrated part of, or an extension of, a foil, used to adjust the hydro - or aerodynamic lift of the foil.
"Flashpoint" means a flashpoint determined by a test using the closed cup apparatus referenced in the International Maritime Dangerous Goods (IMDG) Code.
W/1576n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT  MSC 63/23/Add.2
ANNEX 18
Page 16
1. 4.22
1.4.23
1. 4.24
1.4.25
1.4.26
1. 4.27
1.4.28
1. 4.29
1.4.30
1.4.31
1.4.32
1.4.33
"Foil" means a profiled plate or three dimensional construction at

which hydrodynamic lift is generated when the craft is under way.

---CHUNK---

SOURCE: MSC.36(63).pdf
Page 16
1. 4.22
1.4.23
1. 4.24
1.4.25
1.4.26
1. 4.27
1.4.28
1. 4.29
1.4.30
1.4.31
1.4.32
1.4.33
"Foil" means a profiled plate or three dimensional construction at which hydrodynamic lift is generated when the craft is under way.
"Fully submerged foil" means a foil having no lift components piercing the surface of the water in the foil-borne mode.
"High speed craft" is a craft capable of a maximum speed in metres per second (m/s) equal to or exceeding:
where:
3.7 VO.1667
V displacement corresponding to the design waterline (m3 ).
"Hydrofoil boat" is a craft which is supported above the water surface in non-displacement mode by hydrodynamic forces generated on foils.
"Length (L)" means the overall length of the underwater watertight envelope of the rigid hull, excluding appendages, at or below the design waterline in the displacement mode with no lift or propulsion maChinery active.
"Lightweight" is the displacement of the craft in tonnes without cargo, fuel, lubricating oil, ballast water, fresh water and feedwater in tanks, consumable stores, passengers and crew and their effects.

---CHUNK---

SOURCE: MSC.36(63).pdf
maChinery active.
"Lightweight" is the displacement of the craft in tonnes without cargo, fuel, lubricating oil, ballast water, fresh water and feedwater in tanks, consumable stores, passengers and crew and their effects.
"Machinery spaces" are spaces containing internal combustion engines with aggregate total power output of more than 110 kW, generators, oil fuel units, propulsion machinery, major electrical machinery and similar spaces and trunks to such spaces.
"Maximum operational weight" means the overall weight up to which operation in the intended mode is permitted by the Administration.

"Maximum speed" is the speed achieved at the maximum continuous propulsion power for which the craft is certified at maximum operational weight and in smooth water.
"Muster station" is an area where passengers can be gathered in the event of an emergency, given instructions and prepared to abandon the craft, if necessary. The passenger spaces may serve as muster stations if all passengers can be instructed there and prepared to abandon the craft.
"Non-displacement mode" means the normal operational regime of a

---CHUNK---

SOURCE: MSC.36(63).pdf
the craft, if necessary. The passenger spaces may serve as muster stations if all passengers can be instructed there and prepared to abandon the craft.
"Non-displacement mode" means the normal operational regime of a
craft when non-hydrostatic forces substantially or predominantly support the weight of the craft.
"Oil fuel unit" is the equipment used for the preparation of oil fuel for delivery to an oil-fired boiler, or equipment used for the preparation for delivery of heated oil to an internal combustion engine, and includes any oil pressure pumps, filters and heaters