dealing with oil at a pressure of more than 0.18 N/mm2 .
W/1576n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT 1. 4.34
1.4.35
1.4.36
1.4.37
1.4.38
1.4.39
1.4.40
1. 4.41
1. 4.42
1. 4.43
1.4.44
"Open vehicle spaces" are spaces:
.1 to which any passengers carried have access;
MSC 63/23/Add.2
ANNEX 18
Page 17
. 2 intended for carriage of motor vehicles with fuel in their
tanks for their own propulsion; and
.3 either open at both ends, or open at one end and provided with

---CHUNK---

SOURCE: MSC.36(63).pdf
MSC 63/23/Add.2
ANNEX 18
Page 17
. 2 intended for carriage of motor vehicles with fuel in their
tanks for their own propulsion; and
.3 either open at both ends, or open at one end and provided with
adequate natural ventilation effective over their entire length
through permanent openings in the side plating or deckhead or
from above.
"Operating comparment" means the enclosed area from which the
navigation and control of the craft is exercized.
"Operating station" means a confined area of the operating
compartment equipped with nece.sary means for navigation,
manoeuvring and communication, and from where the functions of
navigating, manoeuvring, communication, commanding, conning and
lookout are carried out.
"Operational speed" is 90% of the maximum speed.
"Organization" means the International Maritime Organization.
"Passenger" is every person other than:
.1 the master and members of the crew or other persons employed
or engaged in any capacity on board a craft on the business of
that craft; and
.2 a child under one year of age.
"Passenger craft" is a craft which carries more than twelve
passengers.

---CHUNK---

SOURCE: MSC.36(63).pdf
or engaged in any capacity on board a craft on the business of that craft; and
.2 a child under one year of age.
"Passenger craft" is a craft which carries more than twelve passengers.
"Place of refuge" is any naturally or artificially sheltered area which may be used as a shelter by a craft under conditions likely to endanger its safety.
"Public spaces" are those spaces allocated for the passengers and include bars, kiosks, smoke rooms, main seating areas, lounges, dining rooms, recreation rooms, lobbies, lavatories and similar permanently enclosed spaces allocated for passengers.
"Service spaces" are those enclosed spaces used for pantries containing food warming equipment but no cooking facilities with exposed heating surfaces, lockers, sales shops, store-rooms and enclosed baggage rooms.
"Significant wave height" is the average height of the one third highest observed wave heights over a given period.
W/1576n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT MSC 63/23/Add.2
ANNEX IS
Page IS
1. 4.45
1. 4.46
1.4.41
1. 4.48

---CHUNK---

SOURCE: MSC.36(63).pdf
W/1576n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT MSC 63/23/Add.2
ANNEX IS
Page IS
1. 4.45
1. 4.46
1.4.41
1. 4.48
"Special category spaces" are those enclosed spaces intended for the carriage of motor vehicles with fuel in their tanks for their own propUlsion, into and from which such vehicles can be driven and to which passengers have access, including spaces intended for the carriage of cargo vehicles.
"Surface effect ship" (SES) is an air-cushion vehicle whose cushion is totally or partially retained by permanently immersed hard

structures.
"Transitional mode" means the regime between displacement and non-displacement modes.
"Worst intended conditions" means the specified environmental conditions within which the intentional operation of the craft is provided for in the certification of the craft. This should take into account parameters such as the worst conditions of wind force allowable, significant wave height (including unfavourable combinations of length and direction of waves), minimum air temperature, visibility and depth of water for safe operation

---CHUNK---

SOURCE: MSC.36(63).pdf
force allowable, significant wave height (including unfavourable combinations of length and direction of waves), minimum air temperature, visibility and depth of water for safe operation and such other parameters as the Administration may require in considering the type of craft in the area of operation.
1.5 Surveys
1.5.1 Each craft should be subject to the surveys specified below:
1. 5. 2
.1 an initial survey before the craft is put in service or before the certificate is issued for the first time;
.2 a renewal survey at intervals specified by the Administration but not exceeding 5 years except where 1.S.5 or 1.S.10 is applicable;
.3 a periodical survey within three months before or after each anniversary date of the certificate; and
.4 an additional survey as the occasion arises.
The surveys referred to in 1.5.1 should be carried out as follows:
.1 the initial survey should include:
.1.1 an appraisal of the assumptions made and limitations proposed in relation to loadings, environment, speed and manoeuvrability;
.1.2 an appraisal of the data supporting the safety of the design obtained as appropriate from calculations, tests and trials;
.1.3
.1.4

---CHUNK---

SOURCE: MSC.36(63).pdf
proposed in relation to loadings, environment, speed and manoeuvrability;
.1.2 an appraisal of the data supporting the safety of the design obtained as appropriate from calculations, tests and trials;
.1.3
.1.4
a failure mode and effect analysis as required by this Code;
an investigation into the adequacy of the various manuals

to be supplied to the craft; and
W/1516n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT
1.5.3
1.5.4
1.5.5
1.5.6
.1.5
MSC 63/23/Add.2
ANNEX 18
Page 19
a complete inspection of the structure, safety equipment,
radio installations and other equipment, fittings,
arrangements and materials to ensure that they comply with
the requirements of the Code, are in satisfactory
condition and are fit for the service for which the craft
is intended;
.2 the renewal and periodical surveys should include a complete
inspection of the structure, including the outside of the
craft's bottom and related items, safety equipment, radio