substantial reduction of stability occurs during this transition.

---CHUNK---

SOURCE: MSC.36(63).pdf
time to pass from the displacement mode to the non-displacement mode and vice versa should be minimized unless it is demonstrated that no substantial reduction of stability occurs during this transition.
2.5.2 Hydrofoil craft should comply with the relevant provisions of annex 6.
2.6 Buoyancy and stability in the d i splacement mode following damage
2.6.1 The requirements of this section apply to all permitted conditions of loading.
2.6.2 For the purpose of making dwnage stability calculations the volume and surface permeabilities should be in general as follows:
2.6.3
Spaces Permeability
Appropriated to cargo or stores 60
Occupied by accommodation 95
Occupied by machinery 85
Intended for liquids 0 or 95*
Appropriated for cargo vehicles 90
Void spaces 95
~ whichever results in the more severe requirements.
Notwithstanding 2.6.2, permeability determined by direct calculation should be used where a more onerous condition results, and may be used where a less onerous condition results from that provided according to 2.6.2.
W/1576n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY

---CHUNK---

SOURCE: MSC.36(63).pdf
used where a less onerous condition results from that provided according to 2.6.2.
W/1576n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT MSC 63/23/Add.2
ANNEX 18
Page 30
2.6.4
2.6.5
2.6.6
2.6.7
2.6.8
Administrations may permit the use of low density foam or other media to provide buoyancy in void spaces, provided that satisfactory evidence is provided that any such proposed medium is the most suitable alternative and is:

.1 of closed cell form if foam, or otherwise impervious to water absorption;
.2 structurally stable under service conditions;
.3 chemically inert in relation to structural materials with which it is in contact or other substances with which the medium is likely to be in contact (reference is made to 7.4.3.7); and
.4 properly secured in place and easily removable for inspection of the void spaces.
Any damage of a lesser extent than that postulated in 2.6.6 to 2.6.8, as applicable, which would result in a more severe condition, should also be investigated. The shape of the damage should be assumed to be a parallelepiped.

---CHUNK---

SOURCE: MSC.36(63).pdf
Any damage of a lesser extent than that postulated in 2.6.6 to 2.6.8, as applicable, which would result in a more severe condition, should also be investigated. The shape of the damage should be assumed to be a parallelepiped.
The following side damages should be assumed anywhere on the periphery of the craft:
.1 the longitudinal extent of damage should be O.lL, or 3 m + 0.03L or 11 m, whichever is the least;
.2 the transverse extent of penetration into the craft should be 0.2B or 0.05L or 5 m, whichever is the least. However, where the craft is fitted with inflated skirts or with non-buoyant side structures, the transverse extent of penetration should be at least 0.12 of the width of the main buoyancy hull or tank structure; and
.3 the vertical extent of damage should be taken for the full depth of the craft.
Subject to 2.6.8, bottom damages should be assumed anywhere on the bottom of the craft as follows:
.1 the longitudinal extent of damage should be O.lL or 3 m + 0.03L or 11 m, whichever is the least;
.2 the transverse extent of damage should be the full breadth of the bottom of the craft or 7 m, whichever is the less, as shown in figure 2.6.7.2; and

---CHUNK---

SOURCE: MSC.36(63).pdf
3 m + 0.03L or 11 m, whichever is the least;
.2 the transverse extent of damage should be the full breadth of the bottom of the craft or 7 m, whichever is the less, as shown in figure 2.6.7.2; and
.3 the vertical extent of penetration into the craft should be 0.02B or 0.5 m, whichever is the less.
In the case of a category B craft, the length of the assumed damage specified in 2.6.7 should be increased by 50% in the case of damage in the forward 0.5L of the craft.
W/1576n/pp/EWP

RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT t
CNIUll
W/1576n/pp/EWP
8
I
~UL~ 8 .... .,.' ." .0'rTI1'"
Oil C.aA,..,.
I a
/.
I
tJ.~ ...
I, rHII D".,.AMC. II '-,u rH".
7 1'7""'1C~.s
Figure 2.6.7.2

I
I
I
MSC 63/23/l\.dd.2
ANNEX 18
Page 31
I
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT MSC 63/23/Add.2
ANNEX 18
Page 32
2.7.1 Every craft on completion of build should be inclined and the elements of its stability determined. When an accurate inclining is not practical the lightship displacement and centre of gravity

---CHUNK---

SOURCE: MSC.36(63).pdf
ANNEX 18
Page 32
2.7.1 Every craft on completion of build should be inclined and the elements of its stability determined. When an accurate inclining is not practical the lightship displacement and centre of gravity should be determined by a lightweight survey and accurate calculation.
2.7.2
2.7.3
2.7.4
2.7.5
2.7.6
2.7.7
The master should be supplied by the owner with reliable information relating to the stability of the craft in accordance with the following provisions of this paragraph. The information relating to

stability should, before issue to the master, be submitted to the Administration for approval, together with a copy thereof for their retention and should incorporate such additions and amendments as the Administration may in any particular case require.
Where any alterations are made to a craft so as materially to affect the stability information supplied to the master, amended stability information should be provided. If necessary, the craft should be re-inclined.
A report of each inclining or lightweight survey carried out in accordance with this chapter and of the calculation therefrom of

---CHUNK---

SOURCE: MSC.36(63).pdf
information should be provided. If necessary, the craft should be re-inclined.
A report of each inclining or lightweight survey carried out in accordance with this chapter and of the calculation therefrom of
the lightship condition particulars should be submitted to the Administration for approval, together with a copy for their retention. The approved report should be placed on board the craft by the owner in the custody of the master and should incorporate such additions and amen&nents as the Administration may in any