when calculating the craft's stability.
Following any inclining or lightweight survey the master should be

---CHUNK---

SOURCE: MSC.36(63).pdf
Page 35
particulars so obtained from time to time should be used by the
master in substitution for such previously approved particulars
when calculating the craft's stability.
Following any inclining or lightweight survey the master should be
supplied with amended stability information if the Administration
so requires. The information so supplied should be submitted to the
Administration for approval, together with a copy thereof for their
retention and should incorporate such additions and amendments as
the Administration may in any particular case require.
PART C - REQUIREMENTS FOR CARGO CRAFT
2.15 Buoyancy and stability in the displacemen t mode f ollowing damage
Following any of the postulated damages detailed in 2.6.5 to 2.6.7,
the craft in still water should have sufficient buoyancy and positive
stability to simultaneously ensure that:
.1 after flooding has ceased and a state of equilibrium has been
reached the final waterline is 150 mm below the level of any opening
through which further flooding could take place;
.2 the angle of inclination of the craft from the horizontal does
not normally exceed 15 0 in any direction. However, where this is

---CHUNK---

SOURCE: MSC.36(63).pdf
through which further flooding could take place;
.2 the angle of inclination of the craft from the horizontal does
not normally exceed 15 0 in any direction. However, where this is
clearly impractical, angles of inclination up to 20 0 immediately
after damage but reducing to 15
0
within 15 min may be permitted
provided that efficient non-slip deck surfaces and suitable holding
points, e.g., holes, bars, etc., are provided;
.3 there is a positive freeboard from the damage waterline to survival
craft embarkation positions;
.4 essential emergency equipment, emergency radios, power supplies and
public address systems needed for organizing the evacuation remain
accessible and operational;
.5 the residual stability of multihull craft complies with the
appropriate criteria as laid out in annex 7; and
.6 the residual stability of any other craft meets the requirements of
regulation 11-1/8 of the Convention.
2.16 Inclining
Where it is satisfied by lightweight survey, weighing or other
demonstration, that the lightweight of a craft is closely similar to
that of another craft of the series to which 2.7.1 has been applied,

---CHUNK---

SOURCE: MSC.36(63).pdf
2.16 Inclining
Where it is satisfied by lightweight survey, weighing or other demonstration, that the lightweight of a craft is closely similar to that of another craft of the series to which 2.7.1 has been applied, the Administration may waive the requirement of 2.7.1 for craft to be inclined. In this regard, a craft which lies ,.,ithin the parameters of 2.14.1, when compared with a craft of the series which has been inclined, should be regarded as being closely similar to that craft.
W/1576n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT MSC 63/23/Add.2
ANNEX 18
Page 36
3.1 General
CHAPTER 3 - STRUCTURES
This chapter covers those elements of hull and superstructure which provide longitudinal and other primary and local strength of the craft as a whole and also other important components such as foils and skirts which are directly associated with the hull and superstructure.
3.2 Materials
Materials used for the hull and superstructure and the other features referred to in 3.1 should be adequate for the intended use of the craft.
3.3 Structural strength

---CHUNK---

SOURCE: MSC.36(63).pdf
which are directly associated with the hull and superstructure.
3.2 Materials
Materials used for the hull and superstructure and the other features referred to in 3.1 should be adequate for the intended use of the craft.
3.3 Structural strength
The structure should be capable of withstanding the static and dynamic loads which can act on the craft under all operating conditions in which the craft is permitted to operate, without such loading resulting in inadmissible deformation and loss of watertightness or interfering with the safe operation of the craft.
3.4 Cyclic loads
Cyclic loads, including those from vibrations which can occur on the craft should not:
.1 impair the integrity of structure during the anticipated service life of the craft or the service life agreed with the Administration;
.2 hinder normal functioning of machinery and equipment; and
.3 impair the ability of the crew to carry out its duties.
3.5 Design criteria
The Administration should be satisfied that the choice of design conditions, design loads and accepted safety factors corresponds to the intended operating conditions for which certification is sought.
3.6 Trials

---CHUNK---

SOURCE: MSC.36(63).pdf
3.5 Design criteria
The Administration should be satisfied that the choice of design conditions, design loads and accepted safety factors corresponds to the intended operating conditions for which certification is sought.
3.6 Trials
If the Administration consider it necessary, it should require full-scale trials to be undertaken in which loadings are determined. Cognizance should be taken of the results where these indicate that loading assumptions of structural calculations have been inadequate.
W/1576n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT MSC 63/23/Add.2
ANNEX 18
Page 37
CHAPTER 4 - ACCOMMODATION AND ESCAPE MEASURES
4.1 General
4.1.1 Passenger and crew accommodation should be designed and arranged so as to protect the occupants from unfavourable environmental conditions and to minimize the risk of injury to occupants during normal and emergency conditions.
4.1.2 Spaces accessible to passengers should not contain controls, electrical equipment, high temperature parts and pipelines, rotating assemblies or other items, from which injury to passengers could

---CHUNK---

SOURCE: MSC.36(63).pdf
normal and emergency conditions.
4.1.2 Spaces accessible to passengers should not contain controls, electrical equipment, high temperature parts and pipelines, rotating assemblies or other items, from which injury to passengers could result, unless such items are adequately shielded, isolated, or otherwise protected.
4.1.3 Passenger accommodation should not contain operating controls unless the operating controls are so protected and located that their operation by a crew member should not be impeded by passengers during normal and emergency conditions.
4.1.4 Windows in passenger and crew accommodation should be of adequate strength and suitable for the worst intended conditions specified in the Permit to Operate and be made of material which will not break into dangerous fragments if fractured.
4.1.5 The public spaces, crew accommodation and the equipment therein should be designed so that each person making proper use of these facilities will not suffer injury during craft's normal and emergency start, stop and manoeuvring in normal cruise and in failure or maloperation conditions.
4.2 Public address and infor mation syste m

---CHUNK---

SOURCE: MSC.36(63).pdf
facilities will not suffer injury during craft's normal and emergency start, stop and manoeuvring in normal cruise and in failure or maloperation conditions.

4.2 Public address and infor mation syste m

4.2.1 A general emergency alarm system should be provided. The alarm should be audible throughout all the accommodation and normal crew working spaces and open decks, and the sound pressure level should be at least 10 dB(A) above ambient noise levels underway in normal cruise operation. The alarm should continue to function after it has been triggered until it is normally turned off or is temporarily interrupted by a message on the public address system.

4.2.2 There should be a public address system covering all areas where passengers and crew have access, escape routes, and places of embarkation into survival craft. The system should be such that flooding or fire in any compartment does not render other parts of the system inoperable.

4.2.3

4.2.4

All passenger craft should be equipped with illuminated or luminous notices or video information system(s) visible to all sitting passengers, in order to notify them of safety measures.