---CHUNK---

SOURCE: MSC.36(63).pdf
the system inoperable.
4.2.3
4.2.4
All passenger craft should be equipped with illuminated or luminous notices or video information system(s) visible to all sitting passengers, in order to notify them of safety measures.
The master should, by means of 4.2.3, be able to request passengers "please be seated" when he finds this appropriate to safeguard passengers and always when the safety level 2 according to table 1 of annex 3, is exceeded.
W/1576n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT MSC 63/23/Add.2
ANNEX 18
Page 38
4.2.5 Emergency instructions including a general diagram of the craft showing the location of all exits, routes of evacuation, emergency equipment, life-saving equipment and illustration of lifejacket donning should be available to each passenger and placed near each passenger's seat.
4.3 Design acceleration levels
4.3.1
4.3.2
4.3.3
For passenger craft, superimposed vertical accelerations above 1.0 g at longitudinal centre of gravity should be avoided unless special precautions are taken with respect to passenger safety.

---CHUNK---

SOURCE: MSC.36(63).pdf
4.3 Design acceleration levels
4.3.1
4.3.2
4.3.3
For passenger craft, superimposed vertical accelerations above 1.0 g at longitudinal centre of gravity should be avoided unless special precautions are taken with respect to passenger safety.
Passenger craft should be designed for the collision load with respect to the safety in, and escape from, the public spaces, crew accommodation and escape routes, including in way of life-saving appliances and emergency source of power. The size and type of craft together with speed, displacement and building material should (be taken into consideration when the collision load is determined.
The collision design condition should be based on head-on collision at operational speed with a vertical rock with maximum 2 m height above the waterline.
Taking into consideration the provisions of 4.3.2, the collision

load should be determined by:
gcoll = 1. 2(L)
g.Ll
where the load P should be taken as the lesser of:
P and
P = 9000.M.CL (CH (T + 2»1/2
where the hull material factor M should be taken as:
M = 1.3 for high tensile steel
M 1.00 for aluminium alloy
M = 0.95 for mild steel
M = 0.8 for fibre reinforced plastics

---CHUNK---

SOURCE: MSC.36(63).pdf
P and
P = 9000.M.CL (CH (T + 2»1/2
where the hull material factor M should be taken as:
M = 1.3 for high tensile steel
M 1.00 for aluminium alloy
M = 0.95 for mild steel
M = 0.8 for fibre reinforced plastics
where the length factor cL of the craft is:
(165 + L)
245
where the height factor cH of the craft is:
W/1576n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT 4.3.4
Factor cH Catamaran/surface
effect ship
cH I + 2 + f (!212)
20
where : f=O for T + 2 < 0 - HT
where: f=1 for 0 > T + 2 ~ 0 - HT
where : f=2 for T + 2 ~ 0
T
MSC 63/2.3/-A-dd.2
ANNEX 18
Page 39
Monohulll Air-cushion
hydrofoil vehicle
± 2 + f{O O) i
20 4
T + 2 < 0 --
T + 2 ~ 0 HT > 2
-- HT 2
where the kinetic energy of the craft at speed V is:
E = 1 1l.V 2 (kNm)
"2
where the main particulars of the craft are:
L

o
T
1l
V
g
=
=
=
=
=
=
craft length as defined in chapter I (m)
craft depth from the underside of keel amidships to the top of the effective hull girder (m)
buoyancy tank clearance to skirt tip (m, (negative» for air-cushion vehicles; lifted clearance from keel to water

---CHUNK---

SOURCE: MSC.36(63).pdf
craft depth from the underside of keel amidships to the top of the effective hull girder (m)
buoyancy tank clearance to skirt tip (m, (negative» for air-cushion vehicles; lifted clearance from keel to water surface (m, (negative» for hydrofoils; and craft draught to the underside of keel amidships for all other craft (m)
minimum height from tunnel or wet-deck bottom to the top of the effective hull girder on catamarans and surface effect ships and 0 for air-cushion vehicle (m)
craft displacement, being the mean of the lightweight and maximum operational weight (t)
operational speed of craft (m/s)
gravitational acceleration = 9.806 (m/s2)
For hydrofoils, if the result is greater than the deceleration, gcoll should be taken as:
where:
F = failure load of bow foil assembly applied at the operational waterline (kN)
As an alternative to the requirements of 4.3.3, collision deceleration may be determined by carrying out collision load analysis of the craft in accordance with the assumptions of 4.3.2. If the collision accelerations are determined by both use of the formula referred to in 4.3.3 and the collision load analysis, the

---CHUNK---

SOURCE: MSC.36(63).pdf
analysis of the craft in accordance with the assumptions of 4.3.2. If the collision accelerations are determined by both use of the formula referred to in 4.3.3 and the collision load analysis, the lower resulting value may be used as the collision deceleration.
W/1516n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)

4.3.5 Compliance with the provisions of 4.1.5 and 4.3.1 should be shown for the actual type of craft, as described in annex 8.
4.3.6 Limiting sea states for operation of the craft should be given in normal operation condition and in the worst intended conditions, at operational speed and at reduced speed as necessary. Operational information should be available on board for guidance, or the craft should have an instrument system for on-line check of operational performance. As a minimum, the system should measure accelerations in three axes close to the longitudinal craft centre of gravity.
4.4 Accommodation design
4.4.1 The public spaces and crew accommodation of high speed craft should

---CHUNK---

SOURCE: MSC.36(63).pdf
performance. As a minimum, the system should measure accelerations in three axes close to the longitudinal craft centre of gravity.
4.4 Accommodation design
4.4.1 The public spaces and crew accommodation of high speed craft should