be located and designed to protect passengers and crew under the collision design condition. In this respect, these spaces should not be located within a distance of:
4.4.2
4.4.3
4.4.4
4.4.5
4.4.6
20. gcoll
of the extreme forward end of the top of the effective hull girder of the craft, where the terms V and gcoll are as defined in 4.3.3. For this purpose gcoll need not be taken as less than 3, and should not be taken as greater than 12.
The accommodation should be designed according to the guidelines given in table 4.4.2 and to performance requirements given in annex 9, or by other methods which have been proven to give equal protective qualities.
Equipment and baggage in public spaces and in the operator's compartment should be positioned and secured so that they remain in the stowed position when exposed to the collision design acceleration according to 4.3.3 and 4.3.4.

---CHUNK---

SOURCE: MSC.36(63).pdf
Equipment and baggage in public spaces and in the operator's compartment should be positioned and secured so that they remain in the stowed position when exposed to the collision design acceleration according to 4.3.3 and 4.3.4.
Mountings of large masses such as main engines, auxiliary engines, lift fans, transmissions and electrical equipment should be proved by calculations to withstand the collision design acceleration according to 4.3.3 and 4.3.4 without fracturing.
Seats, life-saving appliances and items of substantial mass and their supporting structure should not deform or dislodge under any loads up to those specified in 4.3.3 and 4.3.4 in any manner that would impede subsequent rapid evacuation of passengers.
There should be adequate handholds on both sides of any passage to enable passengers to steady themselves while moving about.
W/1576n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT MSC 63/23/Add.2
ANNEX 18
Page 41
4.5 Seating construction
4.5.1 A seat should be provided for each passenger and crew member for which the craft is certified to carry.

---CHUNK---

SOURCE: MSC.36(63).pdf
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY

FOR HIGH SPEED CRAFT MSC 63/23/Add.2
ANNEX 18
Page 41
4.5 Seating construction
4.5.1 A seat should be provided for each passenger and crew member for which the craft is certified to carry.
4.5.2 Seats fitted in addition to those required under 4.5.1 and which are not permitted to be used in hazardous navigational situations or potentially dangerous weather or sea conditions, need not comply with 4.5 or 4.6. Such seats should be secured according to 4.4.5 and clearly identified as not being able to be used in hazardous situations.
4.5.3 The installation of seats should be such as to allow adequate access to any part of the accommodation space. In particular, they should not obstruct access to, or use of, any essential emergency equipment or means of escape.
4.5.4
4.5.5
4.5.6
Seats and their attachments, and the structure in the proximity of the seats, should be of a form and design, and so arranged, such as to minimize the possibility of injury and to avoid trapping of the passengers after the assumed damage in the collision design condition according to 4.4.1. Dangerous projections and hard edges

---CHUNK---

SOURCE: MSC.36(63).pdf
as to minimize the possibility of injury and to avoid trapping of the passengers after the assumed damage in the collision design condition according to 4.4.1. Dangerous projections and hard edges should be eliminated or padded.
Seat, seat belts, seat arrangement and adjacent parts such as tables should be designed for the actual collision design acceleration as specified in 4.3.3.
All seats, their supports and their deck attachments should have good energy absorbing characteristics and should meet the requirements of annex 9.
W/1576n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT MSC 63/23/Add.2
ANNEX 18
Page 42
Table 4.4.2 - Overview general design guidelines*
Design level 1: gcoll less than 3
1 Seat/Seat belts
1.1 Low or high seatback
1.2 No restrictions on seating direction
1.3 Sofas allowed
1.4 No seat belts requirement
2 Tables in general allowed
3 Padding of projecting objects

4 Kiosks, bars, etc., no special restrictions
5 Baggage, no special requirements
6 Large masses, restrainment and positioning
Design level 2: gcoll 3 to 12
1 Seat/Seat belts

---CHUNK---

SOURCE: MSC.36(63).pdf
2 Tables in general allowed
3 Padding of projecting objects
4 Kiosks, bars, etc., no special restrictions
5 Baggage, no special requirements
6 Large masses, restrainment and positioning
Design level 2: gcoll 3 to 12
1 Seat/Seat belts
1.1 High seatback with protective deformation and padding
1.2 Forward or backward seating direction
1.3 No sofas allowed as seat
1.4 Lap belt in seats when no protective structure forward
2 Tables with protective features allowed. Dynamic testing
3 Padding of projecting objects
4 Kiosk, bars, etc., on aft side of bulkheads, or other specially approved arrangements
5 Baggage placed with protection forward
6 Large masses, restrainment and positioning
Design level 3: gco11 above 12
1 Seat/Seat belts
1.1 High seatback with protective deformation and padding
1.2 Forward or backward seating direction
1.3 No sofas allowed
1.4 Seat belt when necessary to obtain required protection
No belts in backward facing seats
3 point belt or belt with shoulder harness in forward facing seats
2 No tables allowed
3 Padding of projecting objects, specially approved
4 Kiosk, bars, etc., specially approved

---CHUNK---

SOURCE: MSC.36(63).pdf
No belts in backward facing seats
3 point belt or belt with shoulder harness in forward facing seats
2 No tables allowed
3 Padding of projecting objects, specially approved
4 Kiosk, bars, etc., specially approved
5 Baggage placed with protection forward, specially approved
6 Large masses, restrainment and positioning, specially approved
Other arrangements may be employed if an equivalent level of safety is achieved.
W/l576n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY

4.6.1 One-hand-release safety belts of 3 point type or with shoulder harness should be provided for all seats from which the craft may be operated for all craft with the gcoll acceleration from the collision design acceleration exceeding 3g, as prescribed in 4.3.3.
4.6.2 Safety belts should be provided on passenger seats and crew seats, if necessary, to obtain the protective performance measures described in annex 9.
4.7 Exits and means of escape
4.7.1 For the same reason, easy, safe and quick access from the operating

---CHUNK---

SOURCE: MSC.36(63).pdf
if necessary, to obtain the protective performance measures described in annex 9.
4.7 Exits and means of escape
4.7.1 For the same reason, easy, safe and quick access from the operating compartment to the passenger accommodation should be provided. In order to ensure immediate assistance from the crew in an emergency