situation, the crew accommodation, including any cabins, should be located with due regard to easy, safe and quick access to the public spaces from inside the craft.
4.7.2 The design of the craft should be such that all occupants may safely evacuate the craft into survival craft under all emergency conditions, by day or by night. The positions of all exits which may be used in an emergency, and of all life-saving appliances, the practicability of the evacuation procedure, and the evacuation time to evacuate all passengers and. crew should be demonstrated.
4.7.3 Public spaces, evacuation routes, exits, lifejacket stowage, survival craft stowage, and the embarkation stations should be clearly and permanently marked and illuminated as required in chapter 12.
4.7.4 Each enclosed public space and similar permanently enclosed space

---CHUNK---

SOURCE: MSC.36(63).pdf
survival craft stowage, and the embarkation stations should be clearly and permanently marked and illuminated as required in chapter 12.
4.7.4 Each enclosed public space and similar permanently enclosed space allocated to passengers or crew should be provided with at least two exits arranged in the opposite ends of the space. Exits should be safely accessible and should provide a route to a normal point of boarding or disembarking from the craft.
4.7.5 Subdivision of public spaces to provide refuge in case of fire may be required in compliance with 7.4.4.1 and 7.11.1.
4.7.6 Exit doors should be capable of being readily operated from inside and outside the craft in daylight and in darkness. The means of operation should be obvious, rapid and of adequate strength.
4.7.7 The closing, latching and locking arrangements for exits should be such that it is readily apparent to the appropriate crew member when the doors are closed and in a safe operational condition, either in direct view or by an indicator. The design of external doors should be such as to eliminate the possibility of jamming by ice or debris.

---CHUNK---

SOURCE: MSC.36(63).pdf
the doors are closed and in a safe operational condition, either in direct view or by an indicator. The design of external doors should be such as to eliminate the possibility of jamming by ice or debris.
4.7.8 The craft should have a sufficient number of exits which are suitable to facilitate the quick and unimpeded escape of persons wearing approved lifejackets in emergency conditions, such as collision damage or fire.
W/1576n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT MSC 63/23/Add.2
ANNEX 18
Page 44

4.7.9
4.7.10
4.7.11
4.7.12
4.7.13
4.7.14
4.7.15
Sufficient space for a crew member should be provided adjacent to exits for ensuring the rapid evacuation of passengers.
All exits, together with their means of opening, should be adequately marked for the guidance of passengers. Adequate marking should also be provided for the guidance of rescue personnel outside the craft.
Footholds, ladders, etc., provided to give access from the inside to exits, should be of rigid construction and permanently fixed in position. Permanent handholds should be provided whenever necessary

---CHUNK---

SOURCE: MSC.36(63).pdf
the craft.
Footholds, ladders, etc., provided to give access from the inside to exits, should be of rigid construction and permanently fixed in position. Permanent handholds should be provided whenever necessary to assist persons using exits, and should be suitable for conditions when the craft has developed any possible angles of list or trim.
At least two unobstructed evacuation paths should be available for the use of each person. Evacuation paths should be disposed such that adequate evacuation facilities will be available in the event of any likely damage or emergency conditions, and evacuation paths should have adequate lighting supplied from the main and emergency sources of power.
The dimensions of passages, doorways and stairways which form part of evacuation paths should be such as to allow easy movement of persons when wearing lifejackets. There should be no protrusions in evacuation paths which could cause injury, ensnare clothing, damage lifejackets or restrict evacuation of disabled persons.
Adequate notices should be provided to direct passengers to exits.
Provision should be made on board for embarkation stations to be

---CHUNK---

SOURCE: MSC.36(63).pdf
lifejackets or restrict evacuation of disabled persons.
Adequate notices should be provided to direct passengers to exits.
Provision should be made on board for embarkation stations to be properly equipped for evacuation of passengers into life-saving appliances. Such provision should include handholds, anti-skid treatment of the embarkation deck, and adequate space which is clear of cleats, bollards and similar fittings.
4.8 Evacuation time
4.8.1
4.8.2
The provisions for evacuation should be designed such that the

craft can be evacuated under controlled conditions in a time of one third of the structural fire protection time (SFP) provided in 7.4.2 for major fire hazard areas after subtracting a period of 7 min for initial detection and extinguishing action.

Evacuation time = (SFP - 7)

3

where:

SFP = structural fire protection time (min)

(min)

An evacuation procedure, including a critical path analysis, should be developed for the information of the Administration in connection with the approval of fire insulation plans and for assisting the owners and builders in planning the evacuation demonstration required in 4.8.3.

W/1576n/pp/EWP

---CHUNK---

SOURCE: MSC.36(63).pdf

be developed for the information of the Administration in connection with the approval of fire insulation plans and for assisting the owners and builders in planning the evacuation demonstration required in 4.8.3.

W/1576n/pp/EWP

RESOLUTION MSC.36(63)

(adopted on 20 May 1994)

ADOPTION OF THE INTERNATIONAL CODE OF SAFETY FOR HIGH SPEED CRAFT 4.8.3

4.8.4

The evacuation procedures should include:

MSC 63/23/Add.2

ANNEX 18

Page 45

.1 the emergency announcement made by the master;

.2 contact with base port;

.3 the donning of lifejackets;

.4 manning of survival craft and emergency stations;

.5 the shutting down of machinery and oil fuel supply lines;

.6 the order to evacuate;

.7 the deployment of survival craft and marine escape systems and rescue boats;

.8 the bowsing in of survival craft:

.9 the supervision of passengers;

.10 the orderly evacuation of passengers under supervision;

.11 crew checking that all passengers have left the craft:

.12 the evacuation of crew;

.13 releasing the survival craft from the craft; and

.14 the marshalling of survival craft by the rescue boat where provided.

Achievement of the required evacuation time (as ascertained in

---CHUNK---

SOURCE: MSC.36(63).pdf

.12 the evacuation of crew;
.13 releasing the survival craft from the craft; and
.14 the marshalling of survival craft by the rescue boat where provided.

Achievement of the required evacuation time (as ascertained in accordance with 4.8.1) should be verified by a practical demonstration conducted under controlled conditions in the presence of the Administration, and should be fully documented and verified for passenger craft by the Administration.

Evacuation demonstrations should be carried out with due concern for the problems of mass movement or panic acceleration likely to arise in an emergency situation when rapid evacuation is necessary. The evacuation demonstrations should be dry shod with the survival craft initially in their stowed positions and be conducted as follows:

.1 The evacuation time on a category A craft should be the time elapsed from the moment the first abandon craft announcement is given, with any passengers distributed in a normal voyage configuration, until the last person has embarked in a survival craft, and should include the time for passengers and crew to don lifej ackets .

---CHUNK---