SOURCE: MSC.36(63).pdf
is given, with any passengers distributed in a normal voyage configuration, until the last person has embarked in a survival craft, and should include the time for passengers and crew to don lifej ackets .
. 2 The evacuation time on a category B craft and cargo craft should be the time elapsed from the moment the order to abandon the craft is given, until the last person has embarked in a survival craft. Passengers and crew may be wearing lifejackets and prepared for evacuation, and they may be distributed among muster stations.
W/1576n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY FOR HIGH SPEED CRAFT MSC 63/23/Add.2
ANNEX 18
Page 46
4.8.5
4.8.6
4.8.1
4.8.8
4.8.9
4.8.10
4.8.11
.3 For all craft the evacuation time should include the time necessary to launch, inflate and secure the survival craft alongside ready for embarkation.
The evacuation time should be verified by an evacuation demonstration which should be performed using the survival craft and exits on one side, for which the critical path analysis indicates the greatest evacuation time, with the passengers and crew allocated to them.

---CHUNK---

SOURCE: MSC.36(63).pdf
demonstration which should be performed using the survival craft and exits on one side, for which the critical path analysis indicates the greatest evacuation time, with the passengers and crew allocated to them.
On craft where a half trial is impracticable, the Administration may consider a partial evacuation trial using a route which the critical path analysis shows to be the most critical.
The demonstration should be carried out in controlled conditions in the following manner in compliance with the evacuation plan .
. 1 The demonstration should commence with the craft afloat in harbour, in reasonably calm conditions, with all machinery and equipment operating in the normal seagoing condition .
. 2 All exits and doors inside the craft should be in the same position as they are under normal seagoing condition .
. 3 Safety belts, if required, should be fastened .
. 4 The evacuation routes for all passengers and crew should be such that no person need enter the water during the evacuation.

For passenger craft, a representative composition of persons with normal health, height and weight should be used in the

---CHUNK---

SOURCE: MSC.36(63).pdf
such that no person need enter the water during the evacuation.
For passenger craft, a representative composition of persons with normal health, height and weight should be used in the demonstration, and should consist of different sexes and ages so far as it is practicable and reasonable.
The persons, other than the crew selected for the demonstration, should not have been specially drilled for such a demonstration.
An emergency evacuation demonstration should be carried out for all new designs of high speed craft and for other craft where evacuation arrangements differ substantially from those previously tested.
The specific evacuation procedure followed during the craft's initial demonstration on which certification is based should be included in the craft operating manual together with the other evacuation procedures contained in 4.8.2. During the demonstration video recordings should be made both inside and outside the craft which should form an integral part of the training manual required by 18.2.
4.9 Baggage, stores, shops and car go compartments
4.9.1 Provision should be made to prevent shifting of baggage, stores

---CHUNK---

SOURCE: MSC.36(63).pdf
which should form an integral part of the training manual required by 18.2.
4.9 Baggage, stores, shops and car go compartments
4.9.1 Provision should be made to prevent shifting of baggage, stores and cargo compartment contents, having due regard to occupied compartments and .accelerations likely to arise. If safeguarding by positioning is not practicable, adequate means of restraint for baggage, stores and cargo should be provided. Shelves and overhead
W/1516n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT MSC 63/23/Add.2
ANNEX 18
Page 47
shelves for storage of carry-on baggage in passenger accommodation should be provided with adequate means to prevent the luggage from falling out in any conditions that may occur.
4.9.2 Controls, electric equipment, high temperature parts, pipelines or other items, the damage or failure of which could affect the safe operation of the craft or which may require access by crew members during a voyage, should not be located in baggage, store and cargo compartments unless such items are adequately protected so that they

---CHUNK---

SOURCE: MSC.36(63).pdf
operation of the craft or which may require access by crew members during a voyage, should not be located in baggage, store and cargo compartments unless such items are adequately protected so that they cannot be damaged or, where applicable, operated inadvertently by loading, unloading or by movement of the contents of the compartment.
4.9.3 Loading limits, if necessary, should be durably marked in those compartments.
4.9.4 Having regard to the purpose of the craft, the closures of the exterior openings of the luggage and cargo compartments as well as special category spaces should be appropriately weathertight.
4.10 Noise levels
4.10.1 The noise level in crew and passengers' accommodations should be kept as low as possible to enable the public address system to be heard, and should not in general exceed 75 dB(A).
4.10.2 The maximum noise level in the operating compartment should not in general exceed 65 dB(A) to facilitate communication within the compartment and external radiocommunications.
W/1576n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT MSC 63/23/Add.2
ANNEX 18
Page 48

---CHUNK---

SOURCE: MSC.36(63).pdf
compartment and external radiocommunications.
W/1576n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT MSC 63/23/Add.2
ANNEX 18
Page 48
CHAPTER 5 - DIRECTIONAL CONTROL SYSTEMS
5.1 General
5.1.1 Craft should be provided with means for directional control of adequate strength and suitable design to enable the craft's heading and direction of travel to be effectively controlled to the maximum extent possible in the prevailing conditions and craft speed without undue physical effort at all speeds and in all conditions for which the craft is to be certificated. The performance should be verified in accordance with annex 8.
5.1.2 Directional control may be achieved by means of air or water rudders, foils, flaps, steerab1e propellers or jets, yaw control ports or side thrusters, differential propulsive thrust, variable geometry of the craft or its lift system components or by a combination of these devices.
5.1.3 For the purpose of this chapter, a directional control system includes any steering device or devices, any mechanical linkages

---CHUNK---

SOURCE: MSC.36(63).pdf
geometry of the craft or its lift system components or by a combination of these devices.

5.1.3 For the purpose of this chapter, a directional control system includes any steering device or devices, any mechanical linkages and all power or manual devices, controls and actuating systems.

5.1.4 Attention is drawn to the possibility of interaction between directional control systems and stabilization systems. Where such interaction occurs or where dual purpose components are fitted, the requirements of 12.5 and chapters 16 and 17 should also be complied with as applicable.

5.2 Reliability

5.2.1 The probability of total failure of all directional control systems should be extremely remote when the craft is operating normally, i.e., excluding emergency situations such as grounding, collision or a major fire.

5.2.2

5.2.3

5.2.4

A design incorporating a power drive or an actuation system