FOR HIGH SPEED CRAFT MSC 63/23/Add.2
ANNEX 18
Page 52
CHAPTER 7 - FIRE SAFETY
PART A - GENERAL
7.1 General requirements
7.1.1 The following basic principles underlay the provisions in this

---CHUNK---

SOURCE: MSC.36(63).pdf
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT MSC 63/23/Add.2
ANNEX 18
Page 52
CHAPTER 7 - FIRE SAFETY
PART A - GENERAL
7.1 General requirements
7.1.1 The following basic principles underlay the provisions in this
chapter and are embodied therein as appropriate, having regard to the category of craft and the potential fire hazard involved:
7.1.2
.1 maintenance of the main functions and safety systems of the craft, including propulsion and control, fire detection, alarms and extinguishing capability of unaffected spaces, after fire in anyone compartment on board;
.2 division of the passenger accommodation area for category B craft, in such a way that the occupants of any compartment can escape to an alternative safe area or compartment in case of fire;
.3 subdivision of the craft by fire-resisting boundaries;
.4 restricted use of combustible materials and materials generating smoke and toxic gases in a fire;
.5 detection, containment and extinction of any fire in the space of origin;
.6 protection of means of escape and access for fire fighting; and
.7 immediate availability of fire-extinguishing appliances.

---CHUNK---

SOURCE: MSC.36(63).pdf
.5 detection, containment and extinction of any fire in the space of origin;
.6 protection of means of escape and access for fire fighting; and
.7 immediate availability of fire-extinguishing appliances.
The requirements in this chapter are based on the following conditions:
.1 Where a fire is detected, the crew immediately puts into action the fire-fighting procedures, informs the base port of the accident and prepares for the escape of passengers to alternative safe area or compartment, or, if necessary, for the evacuation of passengers .
. 2 The use of fuel with a flashpoint below 43°C is not recommended. However, fuel with a lower flashpoint, but not

lower than 35°C, may be used in gas turbines only subject to compliance with the provisions specified in 7.5.1 to 7.5.6 .
. 3 The repair and maintenance of the craft is carried out in accordance with the requirements given in chapters 18 and 19 of this Code .
. 4 Enclosed spaces such as cinemas, discotheques, and similar spaces are not permitted. Refreshment kiosks which do not contain cooking facilities with exposed heating surfaces may be permitted. Galleys, if fitted, should be ~n full

---CHUNK---

SOURCE: MSC.36(63).pdf
. 4 Enclosed spaces such as cinemas, discotheques, and similar spaces are not permitted. Refreshment kiosks which do not contain cooking facilities with exposed heating surfaces may be permitted. Galleys, if fitted, should be ~n full
compliance with chapter 11-2 of the Convention.
W/1576n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT n MSC 63/23/Add.2 ANNEX 18
Page 53
.5 Dangerous goods may be carried provided the relevant provisions of regulations 11-2153 and 54 of the Convention are complied with .
. 6 Passenger access to vehicle spaces is prohibited during the voyage except when accompanied by a crew member responsible for fire safety. Only authorized crew members should be permitted to enter cargo spaces at sea.
7.2 Defini tions
7.2.1 "Fire-resisting divisions" are those divisions formed by bulkheads and decks which comply with the following:
7.2.2
.1 They should be constructed of non-combustible or fire-restricting materials which by insulation or inherent fire-resisting properties satisfy the requirements of 7.2.1.2 to 7.2.1.6 .
. 2 They should be suitably stiffened .

---CHUNK---

SOURCE: MSC.36(63).pdf
7.2.2
.1 They should be constructed of non-combustible or fire-restricting materials which by insulation or inherent fire-resisting properties satisfy the requirements of 7.2.1.2 to 7.2.1.6 .
. 2 They should be suitably stiffened .
. 3 They should be so constructed as to be capable of preventing the passage of smoke and flame up to the end of the appropriate fire protection time .
. 4 Where required, they should maintain load-carrying capabilities up to the end of the appropriate fire protection time .

. 5 They should have thermal properties such that the average temperature on the unexposed side will not rise more than 139°C above the original temperature, nor will the temperature, at anyone point, including any joint, rise more than 180°C above the original temperature during the appropriate fire protection time .
. 6 A test in accordance with the test procedures for a prototype bulkhead and deck should be required to ensure that it meets the above requirements.
"Fire-restricting materials" are those materials which have properties complying with the standards developed by the Organization* with respect to the following:

---CHUNK---

SOURCE: MSC.36(63).pdf
the above requirements.
"Fire-restricting materials" are those materials which have properties complying with the standards developed by the Organization* with respect to the following:
.1 they should have low flame-spread characteristics;
.2 limit heat flux, due regard being paid to the risk of ignition of furniture in the compartment;
.3 limited rate of heat release, due regard being paid to the risk of spread of fire to an adjacent compartment; and
.4 gas and smoke should not be emitted in quantities that could be dangerous to the occupants of the craft.
* Standards should be further developed by the Organization.
W/1576n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT MSC 63/23/Add.2
ANNEX 18
Page 54
7.2.3
7.2.4
7. 2.5
7.2.6
7.2.7
7.2.8
"Local fire", the standards for compliance with 7.2.2.2 are to be developed by the Organization* as applicable to surface materials on bulkheads, wall, and ceiling linings including their supporting structure as considered necessary.
"Non-combustible material" is a material which neither burns nor

---CHUNK---

SOURCE: MSC.36(63).pdf
developed by the Organization* as applicable to surface materials on bulkheads, wall, and ceiling linings including their supporting structure as considered necessary.
"Non-combustible material" is a material which neither burns nor

gives off flammable vapours in sufficient quantity for self-ignition when heated to approximately 750°C, this being determined to the satisfaction of the Administration by an established test procedure.** Any other material is a combustible material.
"A standard fire test" is one in which specimens of the relevant bulkheads, decks or other constructions are exposed in a test furnace by specified test method according to the standards*** developed by the Organization.
Where the words "steel or other equivalent material" occur, "equivalent material" means any non-combustible material which, by itself or due to insulation provided, has structural and integrity properties equivalent to steel at the end of the applicable exposure to the standard fire test (e.g., aluminium alloy with appropriate insulation).
"Low flame-spread" means that the surface thus described will adequately restrict the spread of flame, this being determined by

---CHUNK---

SOURCE: MSC.36(63).pdf
to the standard fire test (e.g., aluminium alloy with appropriate insulation).
"Low flame-spread" means that the surface thus described will