of the division.
1 The upper side of the decks of special category spaces need not be insulated.
2 Where adjacent spaces are in the same alphabetical category and a note 2 appears, a bulkhead or deck between such spaces need not be fitted if deemed unnecessary by the Administration. For example, a bulkhead need not be required between two store-rooms. A bulkhead is, however, required between a machinery space and a special category space even though both spaces are in the same category.

---CHUNK---

SOURCE: MSC.36(63).pdf
not be required between two store-rooms. A bulkhead is, however, required between a machinery space and a special category space even though both spaces are in the same category.
3 No structural fire protection requirements, however, smoke-tight non-combustible or fire-restricting material is required.
4 Control stations which are also auxiliary machinery spaces should be provided with 30 min structural fire protection.
5 There are no special requirements for material or integrity of boundaries where only a dash appears in the tables.
6 The fire protection time is 0 min and the time for prevention of passage of smoke and flame is 30 min as determined by the first 30 min of the standard fire test.
7 When steel construction is used, fire-resisting divisions need not comply with 7. 2 . 1. 5
8 When steel construction is used, fire-resisting divisions adjacent to void spaces need not comply with 7.2.1.5.
W/1576n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT MSC 53/23/Add.2
ANNEX 18
Page 59
7.4 S t ruc t u r al f ire pro tec tion
7.4.1 Main structure
7.4.1.1
7.4.1.2
7.4.1.3
7.4.2

---CHUNK---

SOURCE: MSC.36(63).pdf
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT MSC 53/23/Add.2
ANNEX 18
Page 59
7.4 S t ruc t u r al f ire pro tec tion
7.4.1 Main structure

7.4.1.1
7.4.1.2
7.4.1.3
7.4.2
7.4.2.1
7.4.2.2
7.4.2.3
The requirements below apply to all craft irrespective of construction material. The structural fire protection times for separating bulkheads and decks should be in accordance with tables 7.4-1 and 7.4-2, and the structural fire protection times are all based on providing protection for a period of 60 min as referred to in 4.8.1. If any other lesser structural fire protection time is determined for category A craft and cargo craft by 4.8.1, then the times given below in 7.4.2.2 and 7.4.2.3 may be amended pro-rata. In no case should the structural fire protection time be less than 30 min.
In using tables 7.4-1 and 7.4-2, it should be noted that the title of each category is intended to be typical rather than restricted. For determining the appropriate fire integrity standards to be applied to boundaries between adjacent spaces, where there is doubt

---CHUNK---

SOURCE: MSC.36(63).pdf
of each category is intended to be typical rather than restricted. For determining the appropriate fire integrity standards to be applied to boundaries between adjacent spaces, where there is doubt as to their classification for the purpose of this section, they should be treated as spaces within the relevant category having the most stringent boundary requirement.
The hull, superstructure, structural bulkheads, decks, deckhouses and pillars should be constructed of approved non-combustible materials having adequate structural properties. The use of other fire-restricting materials may be permitted provided the requirements of this chapter are complied with (including a test procedure, developed by the Organization*, for structural strength of composites at elevated temperatures).
Fire-resisting divisions
Areas of major and moderate fire hazard should be enclosed by fire-resisting divisions complying with the requirements of 7.2.1 except where the omission of any such division would not affect the safety of the craft. These requirements need not apply to those parts of the structure in contact with water at the lightweight

---CHUNK---

SOURCE: MSC.36(63).pdf
except where the omission of any such division would not affect the safety of the craft. These requirements need not apply to those parts of the structure in contact with water at the lightweight condition, but due regard should be given to the effect of temperature of hull in contact with water and heat transfer from any uninsulated structure in contact with water to insulated structure

above the water.
Fire-resisting bulkheads and decks should be constructed to resist exposure to the standard fire test for a period of 30 min for areas of moderate fire hazard and 50 min for areas of major fire hazards except as provided in 7.4.1.1.
Main load-carrying structures within major and moderate fire hazard areas should be arranged to distribute load such that there will be no collapse of the construction of the hull and superstructure when it is exposed to fire for the appropriate fire protection time. The load-carrying structure should also comply with the requirements of 7.4.2.4 and 7.4.2.5.
* Standards should be developed by the Organization.
W/1575n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY

---CHUNK---

SOURCE: MSC.36(63).pdf
7.4.2.4 and 7.4.2.5.
* Standards should be developed by the Organization.
W/1575n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT MSC 63/23/Add.2
ANNEX 18
Page 60
7.4.2.4
7.4.2.5
7.4.2.6
7.4.3
7.4.3.1
7.4.3.2
7.4.3.3
If the structures specified in 7.4.2.3 are made of aluminium alloy their installation should be such that the temperature of the core does not rise more than 200°C above the ambient temperature in accordance with the times in 7.4.1.1 and 7.4.2.2.
If the structures specified in 7.4.2.3 are made of combustible material, their insulation should be such that their temperatures will not rise to a level where deterioration of the construction will occur during the exposure to the composite standard fire test developed by the Organization to such an extent that the load-carrying capability, in accordance with the times in 7.4.1.1 and 7.4.2.3, will be impaired.
The construction of all doors, and door frames in fire-resisting divisions, with the means of securing them when closed, should provide resistance to fire as well as to the passage of smoke and

---CHUNK---

SOURCE: MSC.36(63).pdf

and 7.4.2.3, will be impaired.
The construction of all doors, and door frames in fire-resisting divisions, with the means of securing them when closed, should provide resistance to fire as well as to the passage of smoke and flame equivalent to that of the bulkheads in which they are situated. Watertight doors of steel need not be insulated. Also, where a fire-resisting division is penetrated by pipes, ducts, controls, electrical cables or for other purposes, arrangements and necessary testing should be made to ensure that the fire-resisting integrity of the division is not impaired.
Restricted use of combustible materials
All separating divisions, ceilings or linings if not a fire-resisting division, should be of non-combustible or fire-restricting materials.
Where insulation is installed in areas in which it could come into contact with any flammable fluids or their vapours, its surface should be impermeable to such flammable fluids or vapours.
The exposed surfaces of vapour barriers and adhesives used in conjunction with insulation materials should have low flame-spread characteristics.
Furniture and furnishings in public spaces and crew accommodation

---CHUNK---