SOURCE: MSC.36(63).pdf
The exposed surfaces of vapour barriers and adhesives used in conjunction with insulation materials should have low flame-spread characteristics.
Furniture and furnishings in public spaces and crew accommodation should comply with the following standards:
.1 all case furniture is constructed entirely of approved non-combustible or fire-restricting materials, except that a combustible veneer with a calorific value not exceeding 45 MJ/m 2 may be used on the exposed surface of such articles;
.2 all other furniture such as chairs, sofas and tables is constructed with frames of non-combustible or fire-restricting materials;
.3 all draperies, curtains and other suspended textile materials have qualities of resistance to the propagation of flame in accordance with standards* developed by the Organization;
Refer to the Recommendation on test method for determining the resistance to flame of vertically supported textiles and films, adopted by the Organization by resolution A.47l(XII), and amendments to the recommendation adopted by resolution A.563(14).
W/1576n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY

---CHUNK---

SOURCE: MSC.36(63).pdf
Organization by resolution A.47l(XII), and amendments to the recommendation adopted by resolution A.563(14).
W/1576n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT 7.4.3.4
7.4.3.5
7.4.3.6
7.4.3.7
7.4.3.8
MSC 63/23/Add.2
ANNEX 18
Page 61
.4 all upholstered furniture has qualities of resistance to the ignition and propagation of flame in accordance with standards* developed by the Organization;
.5 all bedding components comply with the standards** developed by the Organization; and
.6 all deck finish materials comply with the standards*** developed by the O~ganization.
The following surfaces should, as a minimum standard be constructed of materials having low flame-spread characteristics:
.1 exposed surfaces in corridors and stairway enclosures, and of bulkheads, wall and ceiling linings in all accommodation and

service spaces and control stations;
.2 concealed or inaccessible spaces in accommodation, service spaces and control stations.
Any thermal and acoustic insulation material, if not in compliance with 7.2.1 or 7.2.2, should be of non-combustible material.

---CHUNK---

SOURCE: MSC.36(63).pdf
.2 concealed or inaccessible spaces in accommodation, service spaces and control stations.
Any thermal and acoustic insulation material, if not in compliance with 7.2.1 or 7.2.2, should be of non-combustible material.
Materials used in the craft, when exposed to fire, should not emit smoke or toxic gases in quantities that could be dangerous to humans as determined in tests of a standard developed by the Organization.
Void compartments, where low density combustible materials are used to provide buoyancy, should be protected from adjacent fire hazard areas by fire-resisting divisions, in accordance with tables 7.4-1 and 7.4-2. Also, the space and closures to it should be gastight but it should be ventilated to atmosphere.
In compartments where smoking is allowed, suitable non-combustible ash containers should be provided. In compartments where smoking is not allowed, adequate notices should be displayed.
* Refer to the Recommendation on fire test procedures for upholstered furniture, adopted by the Organization by resolution A.652(16).
** Refer to the Recommendation on fire test procedures for ignitability of

---CHUNK---

SOURCE: MSC.36(63).pdf
* Refer to the Recommendation on fire test procedures for upholstered furniture, adopted by the Organization by resolution A.652(16).
** Refer to the Recommendation on fire test procedures for ignitability of bedding components, adopted by the Organization by resolution A.688(17).
*** Refer to the Recommendation on improved fire test procedures for surface flammability of bulkhead, ceiling and deck finish materials, adopted by the Organization by resolution A.653(16) and the Recommendation on fire test procedures for ignitability of primary deck coverings, adopted by the Organization by resolution A.687(16).
W/1576n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY FOR HIGH SPEED CRAFT MSC 63/23/Add.2
ANNEX 18
Page 62
7.4.3.9 The exhaust gas pipes should be arranged so that the risk of fire is kept to a minimum. To this effect, the exhaust system should be insulated and all the compartments and structures which are contiguous with the exhaust system, or those which may be affected by increased temperatures caused by waste gases in normal operation or in an emergency, should be constructed of non-combustible

---CHUNK---

SOURCE: MSC.36(63).pdf
contiguous with the exhaust system, or those which may be affected
by increased temperatures caused by waste gases in normal operation
or in an emergency, should be constructed of non-combustible
material or be shielded and insulated with non-combustible material
to protect from high temperatures.
7.4.3.10 The design and arrangement of the exhaust manifolds or pipes should
be such as to ensure the safe discharge of exhaust gases.
7.4.4 Arrangement
7.4.4.1 Internal stairways which serve more than two decks of accommodation
should be enclosed at all levels with smoke-tight divisions of
non-combustible or fire-restricting materials, and where only two
decks are served, such enclosures should be provided on at least one
level. Stairways may be fitted in the open in a public space,
provided they lie wholly within such public space.
7.4.4.2 Lift trunks should be so fitted as to prevent the passage of smoke
and flame from one deck to another and should be provided with means
of closing so as to permit the control of draught and smoke.
7.4.4.3 In accommodation and service spaces, control stations, corridors and

---CHUNK---

SOURCE: MSC.36(63).pdf
and flame from one deck to another and should be provided with means
of closing so as to permit the control of draught and smoke.
7.4.4.3 In accommodation and service spaces, control stations, corridors and
stairways air spaces enclosed behind ceilings, panelling or linings
should be suitably divided by close fitting draught stops not more
than 14 m apart.
7.5 Fuel and other flammable fluid tanks and systems
7.5.1 Tanks containing fuel and other flammable fluids should be separated
from passenger, crew, and baggage compartments by vapour-proof
enclosures or cofferdams which are suitably ventilated and drained.
7.5.2 Fuel oil tanks should not be located in or contiguous to major fire
hazard areas. However, flammable fluids of a flashpoint not less
than 60°C may be located within such areas provided the tanks are
made of steel or other equivalent material.
7.5.3 Every oil fuel pipe which, if damaged, would allow oil to escape
from a storage, settling or daily service tank should be fitted
with a cock or valve directly on the tank capable of being closed
from a position outside the space concerned in the event of a fire

---CHUNK---

SOURCE: MSC.36(63).pdf
from a storage, settling or daily service tank should be fitted
with a cock or valve directly on the tank capable of being closed
from a position outside the space concerned in the event of a fire
occurring in the space in which such tanks are situated.
7.5.4 Pipes, valves and couplings conveying flammable fluids should be of
steel or such alternative material satisfactory to a standard*, in
respect of strength and fire integrity having regard to the

* Refer to Guidelines for materials other than steel for pipes adopted by the Organization by resolution A.753(18).
W/1576n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT 7.5.5
7.5.6
MSC 63/23/Add.2
ANNEX 18
Page 63
service pressure and the spaces in which they are installed. Wherever practicable, the use of flexible pipes should be avoided. Pipes, valves and couplings conveying flammable fluids should be arranged as far from hot surfaces or air intakes of engine installations, electrical appliances and other potential sources of ignition as is practicable and be located or shielded so that the

---CHUNK---

SOURCE: MSC.36(63).pdf
arranged as far from hot surfaces or air intakes of engine installations, electrical appliances and other potential sources of