endanger persons should not be permitted .
. 2 The necessary pipes for conveying fire-extinguishing medium into protected spaces should be provided with control valves so marked as to indicate clearly the spaces to which the pipes are led. Non-return valves should be installed in discharge lines between cylinders and manifolds. Suitable provision should be made to prevent inadvertent admission of the medium to any space .
. 3 The piping for the distribution of fire-extinguishing medium should be arranged and discharge nozzles so positioned that a uniform distribution of medium is obtained .

---CHUNK---

SOURCE: MSC.36(63).pdf
to any space .
. 3 The piping for the distribution of fire-extinguishing medium should be arranged and discharge nozzles so positioned that a uniform distribution of medium is obtained .
. 4 Means should be provided to close all openings which may admit air to, or allow gas to escape from, a protected space .
. 5 Where the volume of free air contained in air receivers in any space is such that, if released in such space in the event of fire, such release of air within that space would seriously affect the efficiency of the fixed fire-extinguishing system, the Administration should require the provision of an additional quantity of fire-extinguishing medium .
. 6 Means should be provided for automatically giving audible warning of the release of fire-extinguishing medium into any space in which personnel normally work or to which they have access. The alarm should operate for a suitable period before the medium is released .
. 7 The means of control of any fixed gas fire-extinguishing system should be readily accessible and simple to operate and should be grouped together in as few locations as possible at

---CHUNK---

SOURCE: MSC.36(63).pdf
the medium is released .
. 7 The means of control of any fixed gas fire-extinguishing system should be readily accessible and simple to operate and should be grouped together in as few locations as possible at
positions not likely to be cut off by a fire in a protected

space. At each location there should be clear instructions relating to the operation of the system having regard to the

safety of personnel .
. 8 Automatic release of fire-extinguishing medium should not be permitted .
. 9 Where the quantity of extinguishing medium is required to protect more than one space, the quantity of medium available need not be more than the largest quantity required for any one space so protected
. 10 Pressure containers required for the storage of fire-extinguishing medium should be located outside protected spaces in accordance with 7.7.6.1.13 .
11 Means should be provided for the crew to safely check the quantity of medium in the containers .

---CHUNK---

SOURCE: MSC.36(63).pdf
fire-extinguishing medium should be located outside protected spaces in accordance with 7.7.6.1.13 .
11 Means should be provided for the crew to safely check the quantity of medium in the containers .
. 12 Containers for the storage of fire-extinguishing medium and associated pressure components should be designed to pressure codes of practice to the satisfaction of the Administration having regard to their locations and maximum ambient temperatures expected in service .
. 13 When the fire-extinguishing medium is stored outside a protected space, it should be stored in a room which should be situated in a safe and readily accessible position and should be effectively ventilated. Any entrance to such a storage room should preferably be from the open deck and in any case should be independent of the protected space. Access doors should open outwards, and bulkheads and decks including doors and other means of closing any opening therein, which form the boundaries between such rooms and adjoining enclosed spaces, should be gas tight. Such storage rooms should be treated as control stations .
. 14 Spare parts for the system should be stored on board or at a

---CHUNK---

SOURCE: MSC.36(63).pdf
boundaries between such rooms and adjoining enclosed spaces, should be gas tight. Such storage rooms should be treated as control stations .
. 14 Spare parts for the system should be stored on board or at a base port.
Carbon dioxide systems
.1 For cargo spaces, the quantity of carbon dioxide available should, unless otherwise provided, be sufficient to give a minimum volume of free gas equal to 30% of the gross volume of the largest cargo space so protected in the craft .
. 2 For maChinery spaces, the quantity of carbon dioxide carried should be sufficient to give a minimum volume of free gas equal to the larger of the following volumes, either:

.2.1 40% of the gross volume of the largest machinery space so protected, the volume to exclude that part of the casing above the level at which the horizontal area of the casing is 40% or less of the horizontal area of the space concerned taken midway between the tank top and the lowest part of the casing; or
W/1576n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY FOR HIGH SPEED CRAFT MSC 63/23/Add.2
ANNEX 18
Page 72
7.7.7
7.7.8

---CHUNK---

SOURCE: MSC.36(63).pdf
the lowest part of the casing; or
W/1576n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY FOR HIGH SPEED CRAFT MSC 63/23/Add.2
ANNEX 18
Page 72
7.7.7
7.7.8
. 2.2 35% of the gross volume of the largest machinery space protected, including the casing;
provided that the above-mentioned percentages may be reduced to 35% and 30% respectively for cargo craft of less than 2,000 tons gross tonnage; provided also that if two or more machinery spaces are not entirely separate they should be considered as forming one space .
3 For the purpose of this paragraph the volume of free carbon dioxide should be calculated at 0.56 m3 /kg
4 For machinery spaces, the fixed piping system should be such that 85% of the gas can be discharged into the space within 2 min
. 5 Two separate controls should be provided for releasing carbon dioxide into a protected space and to ensure the activation of the alarm. One control should be used to discharge the gas from its storage containers. A second control should be used for opening the valve of the piping which conveys the gas into the protected spaces .

---CHUNK---

SOURCE: MSC.36(63).pdf
the alarm. One control should be used to discharge the gas from its storage containers. A second control should be used for opening the valve of the piping which conveys the gas into

the protected spaces .
. 6 The two controls should be located inside a release box clearly identified for the particular space. If the box containing the controls is to be locked, a key to the box should be in a break-glass type enclosure conspicuously located adjacent to the box.
Control stations, accommodation spaces and service spaces should be provided with portable fire extinguishers of appropriate types.
At least five portable extinguishers should be provided, and so positioned as to be readily available for immediate use. In addition, at least one extinguisher suitable for machinery space fires should be positioned outside each machinery space entrance.
Fire pumps, and appropriate associated equipment, or alternative effective fire-extinguishing systems should be fitted as follows:
.1 At least two independently driven pumps should be arranged. Each pump should have at least two thirds the capacity of a bilge pump as determined by 10.3.5 and 10.3.6 but not less

---CHUNK---

SOURCE: MSC.36(63).pdf
.1 At least two independently driven pumps should be arranged. Each pump should have at least two thirds the capacity of a