Ventilation ducts, including dampers should be made of steel or other equivalent material.

Scuppers, bilge pumping and drainage

In view of the serious loss of stability which could arise due to large quantities of water accumulating on the deck or decks consequent to the operation of the fixed pressure water-spraying system, scuppers should be fitted so as to ensure that such water is rapidly discharged directly overboard. Alternatively, pumping and

---CHUNK---

SOURCE: MSC.36(63).pdf

consequent to the operation of the fixed pressure water-spraying system, scuppers should be fitted so as to ensure that such water is rapidly discharged directly overboard. Alternatively, pumping and drainage facilities should be provided additional to the requirements of chapter 10.

Precautions against ignition of flammable vapours

On any deck or platform, if fitted, on which vehicles are carried and on which explosive vapours might be expected to accumulate, except platforms with openings of sufficient size permitting penetration of petrol gases downwards, equipment which may constitute a source of ignition of flammable vapours and, in particular, electrical equipment and wiring, should be installed at least 450 mm above the deck or platform. Electrical equipment installed at more than 450 mm above the deck or platform should be of a type so enclosed and protected as to prevent the escape of sparks. However, if the installation of electrical equipment and wiring at less than 450 mm above the deck or platform is necessary for the safe operation of the craft, such electrical equipment and wiring may be installed provided that it is of a type approved for

---CHUNK---

SOURCE: MSC.36(63).pdf

wiring at less than 450 mm above the deck or platform is necessary for the safe operation of the craft, such electrical equipment and wiring may be installed provided that it is of a type approved for use in an explosive petrol and air mixture.

Electrical equipment and wiring, if installed in an exhaust ventilation duct, should be of a type approved for use in explosive petrol and air mixtures and the outlet from any exhaust duct should be sited in a safe position, having regard to other possible sources of ignition.

7.9 Miscellaneous

7.9.1 There should be permanently exhibited, for the guidance of the master and officers of the craft, fire control plans showing clearly for each deck the following positions: the control stations, the sections of the craft which are enclosed by fire-resisting divisions together with particulars of the fire alarms, fire detection systems, the sprinkler installations, the fixed and portable fire-extinguishing appliances, the means of access to the various compartments and decks in the craft, the ventilating system including particulars of the master fan controls, the positions of

---CHUNK---

SOURCE: MSC.36(63).pdf
portable fire-extinguishing appliances, the means of access to the various compartments and decks in the craft, the ventilating system including particulars of the master fan controls, the positions of dampers and identification numbers of the ventilating fans serving each section of the craft, the location of the international shore connection, if fitted, and the position of all means of control referred to in 7.5.3, 7.6.2, 7.7.1 and 7.7.4. The text of such plans* should be in the official language of the flag State.
* Refer to Graphical symbols for fire control plans adopted by the Organization by resolution A.654(16).
W/1576n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY FOR HIGH SPEED CRAFT MSC 63/23/Add.2
ANNEX 18
Page 76
7.9.2
7.9.3
7.9.3.1
7.9.3.2
7.9.3.3
However, if the language is neither English nor French, a translation into one of those languages should be included.
A duplicate set of fire control plans or a booklet containing such plans should be permanently stored in a prominently marked weathertight enclosure outside the deckhouse for the assistance of

---CHUNK---

SOURCE: MSC.36(63).pdf
A duplicate set of fire control plans or a booklet containing such plans should be permanently stored in a prominently marked weathertight enclosure outside the deckhouse for the assistance of shore side fire-fighting personnel.
Openings in fire-resisting divisions
Except for the hatches between cargo, special category, store, and baggage spaces and between such spaces and the weather decks, all openings should be provided with permanently attached means of closing which should be at least as effective for resisting fires as the divisions in which they are fitted.
It should be possible for each door to be opened and closed from each side of the bulkhead by one person only.
Fire doors bounding major fire hazard areas and stairway enclosures should satisfy the following requirements:
.1 The doors should be self-closing and be capable of closing with an angle of inclination of up to 3.5 0 opposing closure, and should have an approximately uniform rate of closure of no more than 40 s and no less than 10 s with the craft in the upright position

. 2 Remote-controlled sliding or power-operated doors should be

---CHUNK---

SOURCE: MSC.36(63).pdf
and should have an approximately uniform rate of closure of
no more than 40 s and no less than 10 s with the craft in the
upright position
. 2 Remote-controlled sliding or power-operated doors should be
equipped with an alarm that sounds at least 5 s but no more
than 10 s before the door begins to move and continue sounding
until the door is completely closed. Doors designed to reopen
upon contacting an object in their paths should reopen
sufficiently to allow a clear passage of at least 0.75 m,
but no more than 1 m
. 3 All doors should be capable of remote and automatic release
from a continuously manned central control station, either
simultaneously or in groups, and also individually from a
position at both sides of the door. Indication should be
provided at the fire control panel in the continuously manned
control station whether each of the remote-controlled doors is
closed. The release mechanism should be so designed that the
door will automatically close in the event of disruption of
the control system or central power supply. Release switches
should have an on-off function to prevent automatic resetting

---CHUNK---

SOURCE: MSC.36(63).pdf
closed. The release mechanism should be so designed that the
door will automatically close in the event of disruption of
the control system or central power supply. Release switches
should have an on-off function to prevent automatic resetting
of the system. Hold-back hooks not subject to control station
release should be prohibited .
. 4 Local power accumulators for power-operated doors should be
provided in the immediate vicinity of the doors to enable the
doors to be operated at least ten times (fully opened and
closed) using the local controls.
W/1576n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT 7.9.3.4
MSC 63/23/Add.2
ANNEX 18
Page 77
.5 Double-leaf doors equipped with a latch necessary to their
fire integrity should have a latch that is automatically
activated by the operation of the doors when released by the
system .
. 6 Doors giving direct access to special category spaces which
are power-operated and automatically closed need not be
equipped with alarms and remote-release mechanisms required

in .2 and .3.

---CHUNK---

SOURCE: MSC.36(63).pdf
system .
. 6 Doors giving direct access to special category spaces which are power-operated and automatically closed need not be equipped with alarms and remote-release mechanisms required in .2 and .3.
The requirements for integrity of fire-resisting divisions of the outer boundaries facing open spaces of a craft should not apply to glass partitions, windows and sidescuttles. Similarly, the requirements for integrity of fire-resisting divisions facing open spaces should not apply to exterior doors in superstructures and deckhouses.
7.10 Fireman's outfits
7.10.1 All craft other than category A passenger craft should carry at least two fireman's outfits complying with the requirements of 7.10.3.
7.10.1.1 In addition, there should be provided in category B passenger craft for every 80 m, or part thereof, of the aggregate of the length of all passenger spaces and service spaces on the deck which carries