such spaces or, if there is more than one such deck, on the deck which has the largest aggregate of such length, two fireman's outfits and two sets of personal equipment, each set comprising the items stipulated in 7.10.3.1.1 to 7.10.3.1.3;

---CHUNK---

SOURCE: MSC.36(63).pdf
such spaces or, if there is more than one such deck, on the deck which has the largest aggregate of such length, two fireman's outfits and two sets of personal equipment, each set comprising the items stipulated in 7.10.3.1.1 to 7.10.3.1.3;
7.10.1.2 In category B passenger craft, for each pair of breathing apparatus there should be provided one water fog applicator which should be stored adjacent to such apparatus.
7.10.1.3 The Administration may require additional sets of personal equipment and breathing apparatus, having due regard to the size and type of the craft.
7.10.2 The fireman's outfits or sets of personal equipment should be
7.10.3
so stored as to be easily accessible and ready for use and, where more than one fireman's outfit or more than one set of personal equipment is carried, they should be stored in widely separated positions. In passenger craft, at least two fireman's outfits and one set of personal equipment should be available at anyone control station.
A fireman's outfit should consist of:
.1 Personal equipment comprising:
.1.1 protective clothing of material to protect the skin from the heat radiating from the fire and from burns and

---CHUNK---

SOURCE: MSC.36(63).pdf
station.
A fireman's outfit should consist of:
.1 Personal equipment comprising:
.1.1 protective clothing of material to protect the skin from the heat radiating from the fire and from burns and
scald.ing by steam or gases. The outer surface should be water-resistant:
W/1576n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY FOR HIGH SPEED CRAFT MSC 63/23/Add.2
ANNEX 18
Page 78
.2 boots and gloves of rubber or other electrically non-conductive material;
.3 a rigid helmet providing effective protection against impact;
.4 an electric safety lamp (hand lantern) of an approved type with a minimum burning period of 3 h; and

.5 an axe .
. 2 A breathing apparatus of an approved type which may be either:
.1 a smoke helmet or smoke mask which should be provided
with a suitable air pump and a length of air hose
sufficient to reach from the open deck, well clear of
hatch or doorway, to any part of the holds or machinery
spaces. If, in order to comply with this subparagraph,
an air hose exceeding 36 m in length would be necessary,
a self-contained breathing apparatus should be

---CHUNK---

SOURCE: MSC.36(63).pdf
hatch or doorway, to any part of the holds or machinery
spaces. If, in order to comply with this subparagraph,
an air hose exceeding 36 m in length would be necessary,
a self-contained breathing apparatus should be
substituted or provided in addition as determined by
the Administration; or
.2 a self-contained compressed-air-operated breathing
apparatus, the volume of air contained in the cylinders
of which should be at least 1,200 1, or other
self-contained breathing apparatus which should be
capable of functioning for at least 30 min. A number of
spare charges, suitable for use with the apparatus
provided, should be available on board .
. 3 For each breathing apparatus, a fireproof lifeline of
sufficient length and strength should be provided capable of
being attached by means of a snaphook to the harness of the
apparatus or to a separate belt in order to prevent the
breathing apparatus becoming detached when the lifeline is
operated.
PART B - REQUIREMENTS FOR PASSENGER CRAFT
7.11 Arrangement
7.11.1 For category B craft, the public spaces should be divided into zones
according to the following:

---CHUNK---

SOURCE: MSC.36(63).pdf
breathing apparatus becoming detached when the lifeline is
operated.
PART B - REQUIREMENTS FOR PASSENGER CRAFT
7.11 Arrangement
7.11.1 For category B craft, the public spaces should be divided into zones
according to the following:
.1 The craft should be divided into at least two zones. The mean
length of each zone should not exceed 40 m .
. 2 For the occupants of each zone there should be an alternative
safe area to which it is possible to escape in case of fire.
The alternative safe area should be separated from other
passenger zones by smoke-tight divisions of non-combustible
materials or fire-restricting materials extending from deck to
W/1576n/pp/EWP

deck. The alternative safe area can be another passenger zone provided the additional number of passengers may be accommodated in an emergency .
. 3 The alternative safe area should, as far as practicable, be located adjacent to the passenger zone it is intended to serve. There should be at least two exits from each passenger

---CHUNK---

SOURCE: MSC.36(63).pdf
accommodated in an emergency .
. 3 The alternative safe area should, as far as practicable, be located adjacent to the passenger zone it is intended to serve. There should be at least two exits from each passenger zone, located as far away from each other as possible, leading to the alternative safe area. Escape routes should be provided to enable all passengers and crew to be safely evacuated from the alternative safe area.
7.11.2 Category A craft need not be divided into zones.
7.11.3 Control stations, life-saving appliance stowage positions, escape routes and places of embarkation into survival craft should not, as far as practicable, be located adjacent to any major or moderate fire hazard areas.
7.12 Ventilation
The ventilation fans of each zone in the accommodation spaces should also be capable of being independently controlled from a continuously manned control station.
7.13 Fixed sprinkler s~
7.13.1 Public spaces and service spaces, storage rooms other than those containing flammable liquids, and similar spaces should be protected by a fixed sprinkler system meeting a standard developed by the

---CHUNK---

SOURCE: MSC.36(63).pdf
7.13 Fixed sprinkler s~
7.13.1 Public spaces and service spaces, storage rooms other than those containing flammable liquids, and similar spaces should be protected by a fixed sprinkler system meeting a standard developed by the Organization. Manually operated sprinkler systems should be divided into sections of appropriate size, and the valves for each section, start of sprinkler pump(s) and alarms should be operable from two spaces separated as widely as possible, one of which should be a continuously manned control station. In category B craft, no section of the system should serve more than one of the zones required in 7.11.
7.13.2 Plans of the system should be displayed at each operating station. Suitable arrangements should be made for the drainage of water

discharged when the system is activated.
W/1576n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT MSC 63/23/Add.2
ANNEX 18
Page 80
PART C - REQUIREMENTS FOR CARGO CRAFT
7.14 ~ntrol station
Control stations, life-saving appliances stowage positions, escape routes and places of embarkation into survival craft should be located

---CHUNK---

SOURCE: MSC.36(63).pdf
ANNEX 18
Page 80
PART C - REQUIREMENTS FOR CARGO CRAFT
7.14 ~ntrol station
Control stations, life-saving appliances stowage positions, escape routes and places of embarkation into survival craft should be located
adjacent to crew accommodation areas.