. 14 "Retro-reflective material" is a material which reflects in the opposite direction a beam of light directed on it

15 "Survival craft" is a craft capable of sustaining the lives of persons in distress from the time of abandoning the craft .

16 "Thermal protective aid" is a bag or suit of waterproof material with low thermal conductance.

Communications

Craft should be provided with the following radio life-saving appliances:

.1 at least three two-way VHF radiotelephone apparatus should be provided on every passenger high speed craft and on every

---CHUNK---

SOURCE: MSC.36(63).pdf

Communications

Craft should be provided with the following radio life-saving appliances:

.1 at least three two-way VHF radiotelephone apparatus should be provided on every passenger high speed craft and on every cargo high speed craft of 500 tons gross tonnage and upwards. Such apparatus should conform to performance standards not inferior to those adopted by the Organization.;

.2 at least one radar transponder should be carried on each side of every passenger high speed craft and of every cargo high speed craft of 500 tons gross tonnage and upwards. Such radar transponders should conform to performance standards not inferior to those adopted by the Organization.** The radar transponders should be stowed in such locations that they can be rapidly placed in any one of the 1iferafts. Alternatively, one radar transponder should be stowed in each survival craft.

* Refer to the Recommendation on performance standards for survival craft portable two-way VHF radiotelephone apparatus, adopted by the Organization by resolution A.605(15).

** Refer to the Recommendation on performance standards for survival craft

---CHUNK---

SOURCE: MSC.36(63).pdf

craft portable two-way VHF radiotelephone apparatus, adopted by the Organization by resolution A.605(15).

** Refer to the Recommendation on performance standards for survival craft radar transponders for use in search and rescue operations, adopted by the Organization by resolution A.697(17).

WI1687n/pp/EWP

RESOLUTION MSC.36(63)

(adopted on 20 May 1994)

ADOPTION OF THE INTERNATIONAL CODE OF SAFETY

FOR HIGH SPEED CRAFT MSC 62123/Add.2

ANNEX 18

Page 84

8.2.2

8.2.3

8.2.3.1
8.2.3.2
Craft should be provided with the following on-board communications and alarm systems:
.1 an emergency means comprising either fixed or portable equipment or both for two-way communications between emergency control stations, muster and embarkation stations and strategic positions on board; and
.2 a general emergency alarm system complying with the requirements of regulation III/50 of the Convention to be used for summoning passengers and crew to muster stations and to initiate the actions included in the muster list. The system should be supplemented by either a public address system or other suitable means of communication. The systems should be

---CHUNK---

SOURCE: MSC.36(63).pdf
for summoning passengers and crew to muster stations and to initiate the actions included in the muster list. The system should be supplemented by either a public address system or other suitable means of communication. The systems should be operable from the operating compartment.
Signalling eguipment
All craft should be provided with a portable daylight signalling lamp which is available for use in the operating compartment at all times and which is not dependent on the craft's main source of electrical power.
Craft should be provided with not less than 12 rocket parachute flares, complying with the requirements of regulation 111/35 of the Convention, stowed in or near the operating compartment.
8.3 Personal liLe - saying appliances
8.3.1 Where passengers or crew have access to exposed decks under normal operating conditions, at least one lifebuoy on each side of the c 'raft capable of quick release from the control compartment and from a position at or near where it is stowed, should be provided with a self-igniting light and a self-activating smoke signal. The positioning and securing arrangements of the self-activating smoke

---CHUNK---

SOURCE: MSC.36(63).pdf
a position at or near where it is stowed, should be provided with a self-igniting light and a self-activating smoke signal. The positioning and securing arrangements of the self-activating smoke signal should be such that it cannot be released or activated solely by the accelerations produced by collisions or groundings.
8.3.2 At least one lifebuoy should be provided adjacent to each normal exit from the craft and on each open deck to which passengers and crew have access, subject to a minimum of two being installed.
8.3.3 Lifebuoys fitted adjacent to each normal exit from the craft should be fitted with buoyant lines of at least 30 m in length.
8.3.4
8.3.5

Not less than half the total
with self-igniting lights.
self-igniting lights should
accordance with 8.3.3.
number of lifebuoys should be fitted
However, the lifebuoys provided with
not include those provided with lines in
A lifejacket complying with the requirements of regulation 111/32.1
or 111/32.2 of the Convention should be provided for every person on
board the craft and, in addition:
.1 a number of lifejackets suitable for children equal to at

---CHUNK---

SOURCE: MSC.36(63).pdf
A lifejacket complying with the requirements of regulation 111/32.1
or 111/32.2 of the Convention should be provided for every person on
board the craft and, in addition:
.1 a number of lifejackets suitable for children equal to at
least 10% of the number of passengers on board should be
provided or such greater number as may be required to provide
a lifejacket for each child;
W/l687n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT 8.3.6
8.3.7
MSC 62/23/Add.2
ANNEX 18
Page 85
.2 every passenger craft should carry lifejackets for not less
than 5% of the total number of persons on board. These
lifejackets should be stowed in conspicuous places on deck or
at muster stations:
.3 a sufficient number of lifejackets should be carried for
persons on watch and for use at remotely located survival
craft and rescue boat stations: and
.4 all lifejackets should be fitted with a light, which complies
with the requirements of regulation 111/32.3 of the Convention.
Lifejackets should be so placed as to be readily accessible and
their positions should be clearly indicated.

---CHUNK---

SOURCE: MSC.36(63).pdf
.4 all lifejackets should be fitted with a light, which complies
with the requirements of regulation 111/32.3 of the Convention.
Lifejackets should be so placed as to be readily accessible and
their positions should be clearly indicated.
An immersion suit, of an appropriate size, complying with the
requirements of regulation 111/33 of the Convention should be
provided for every person assigned to crew the rescue boat.
8.3.8 An immersion suit or anti-exposure suit should be provided for each

member of the crew assigned, in the muster list, to duties in an MES party for embarking passengers into survival craft. These immersion suits or anti-exposure suits need not be required if the craft is constantly engaged on voyages in warm climates where, in the opinion of the Administration, such suits are unnecessary.

8.4 Muster list, emergency instructions and manuals

8.4.1 Clear instructions to be followed in the event of an emergency should be provided for each person on board.

8.4.2 Muster lists complying with the requirements of regulation III/53 of the Convention should be exhibited in conspicuous places throughout

---CHUNK---

SOURCE: MSC.36(63).pdf

should be provided for each person on board.

8.4.2 Muster lists complying with the requirements of regulation III/53 of the Convention should be exhibited in conspicuous places throughout the craft including the control compartment, engine-room and crew accommodation spaces.

8.4.3 Illustrations and instructions in appropriate languages should be posted in public spaces and be conspicuously displayed at muster stations, at other passenger spaces and near each seat to inform passengers of: