8.4.4
8.4.5
.1 their muster station;
.2 the essential actions they must take in an emergency;
.3 the method of donning lifejackets.
Every passenger craft should have passenger muster stations:
.1 in the vicinity of, and which provide ready access for all the passengers to, the embarkation stations unless in the same location; and
.2 which have ample room for the marshalling and instruction of passengers.
A training manual complying with the requirements of 18.2.3 should be provided in each crew messroom and recreation room.
W/1687n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY FOR HIGH SPEED CRAFT MSC 62/23/Add.2

---CHUNK---

SOURCE: MSC.36(63).pdf
be provided in each crew messroom and recreation room.
W/1687n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY FOR HIGH SPEED CRAFT MSC 62/23/Add.2

8.5 ~erating instructions
8.5.1 Poster or signs should be provided on or in the vicinity of survival craft and their launching controls and should:
.1 illustrate the purpose of controls and the procedures for operating the appliance and give relevant instructions and warnings;
.2 be easily seen under emergency lighting conditions;
.3 use symbols in accordance with the recommendations of the Organization*.
8.6 Survival craft stowage
8.6.1 Survival craft should be securely stowed outside and as close as possible to the passenger accommodation and embarkation stations. The stowage should be such that each survival craft can be safely launched in a simple manner and remain secured to the craft during and subsequent to the launching procedure. The length of the securing lines and the arrangements of the bowsing lines should be such as to maintain the survival craft suitably positioned for

---CHUNK---

SOURCE: MSC.36(63).pdf
and subsequent to the launching procedure. The length of the securing lines and the arrangements of the bowsing lines should be such as to maintain the survival craft suitably positioned for

embarkation. The Administrations may permit the use of adjustable securing and/or bowsing lines at exits where more than one survival craft is used. The securing arrangements for all securing and bowsing lines should be of sufficient strength to hold the survival craft in position during the evacuation process.
8.6.2 Survival craft should be so stowed as to permit release from their securing arrangements at or near to their stowage position on the craft and from a position at or near to the operating compartment.
8.6.3 So far as is practicable, survival craft should be distributed in such a manner that there is an equal capacity on both sides of the craft.
8.6.4 The launching procedure for inflatable liferafts should, where practicable, initiate inflation. Where it is not practicable to provide automatic inflation of liferafts (for example, when the liferafts are associated with an MES), the arrangement should be such that the craft can be evacuated within the time specified

---CHUNK---

SOURCE: MSC.36(63).pdf
provide automatic inflation of liferafts (for example, when the liferafts are associated with an MES), the arrangement should be such that the craft can be evacuated within the time specified
in 4.8.1.
8.6.5 Survival craft should be capable of being launched and then boarded from the designated embarkation stations in all operational conditions and also in all conditions of flooding after receiving damage to the extent prescribed in chapter 2.
8.6.6 Survival craft launching stations should be in such positions as to ensure safe launching having particular regard to clearance from the propeller or waterjet and steeply overhanging portions of the hull.
Refer to Symbols related to life-saving appliances and arrangements, adopted by the Organization by resolution A.760(18).
W/1687n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY FOR HIGH SPEED CRAFT n
8.6.7
8.6.8
8.6.9
8.6.10
8.6.11
8.6.12
8.7
8.7.1
8.7.2
MSC 62/23/Add.2
ANNEX 18
Page 87
During preparation and launching, the survival craft and the area of water into which it is to be launched should be adequately

---CHUNK---

SOURCE: MSC.36(63).pdf
8.6.7
8.6.8
8.6.9
8.6.10
8.6.11
8.6.12
8.7
8.7.1
8.7.2
MSC 62/23/Add.2
ANNEX 18
Page 87
During preparation and launching, the survival craft and the area of water into which it is to be launched should be adequately illuminated by the lighting supplied from the main and emergency sources of electrical power required by chapter 12.
Means should be available to prevent any discharge of water on to survival craft when launched.
Each survival craft should be stowed:
.1 so that neither the survival craft nor its stowage arrangements will interfere with the operation of any other survival craft or rescue boat at any other launching station;
.2 in a state of continuous readiness:
.3 fully equipped; and
.4 as far as practicable, in a secure and sheltered position and protected from damage by fire and explosion.
Every liferaft should be stowed with its painter permanently attached to the craft and with a float free arrangement complying with the requirements of regulation III/38.6 of the Convention so that, as far as practicable, the liferaft floats free and, if inflatable, inflates automatically should the high speed craft sink.

---CHUNK---

SOURCE: MSC.36(63).pdf
with the requirements of regulation III/38.6 of the Convention so that, as far as practicable, the liferaft floats free and, if inflatable, inflates automatically should the high speed craft sink.
Rescue boats should be stowed:
.1 in a state of continuous readiness for launching in not more than 5 min;
.2 in a position suitable for launching and recovery; and
.3 so that neither the rescue boat nor its stowage arrangements will interfere with the operation of survival craft at any other launching station.
Rescue boats and survival craft should be secured and fastened to the deck so that they at least withstand the loads likely to arise due to a defined horizontal collision load for the actual craft, and the vertical design load at the stowage position.
Survival craft and rescue boat embarkation and recovery arrangements
Embarkation stations should be readily accessible from accommodation and work areas. If the designated muster stations are other than

the passenger spaces, the muster stations should be readily accessible from the passenger spaces, and the embarkation stations should be readily accessible from the muster stations.

---CHUNK---

SOURCE: MSC.36(63).pdf
the passenger spaces, the muster stations should be readily accessible from the passenger spaces, and the embarkation stations should be readily accessible from the muster stations.
Evacuation routes, exits and embarkation points should comply with the requirements of 4.7.
W/1687n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT MSC 62/23/Add.2
ANNEX 18
Page 88
8.7.3
8.7.4
8.7.5
8.7.6