8.7.7
8.8
8.9
8.9.1
8.9.2
Alleyways, stairways and exits giving access to the muster and embarkation stations should be adequately illuminated by lighting supplied from the main and emergency source of electrical power required by chapter 12.
Where davit-launched survival craft are not fitted, MES or equivalent means of evacuation should be provided in order to avoid persons entering the water to board survival craft. Such MES or equivalent means of evacuation should be so designed as to enable persons to board survival craft in all operational conditions and also in all conditions of flooding after receiving damage to the extent prescribed in chapter 2.

---CHUNK---

SOURCE: MSC.36(63).pdf
equivalent means of evacuation should be so designed as to enable persons to board survival craft in all operational conditions and also in all conditions of flooding after receiving damage to the extent prescribed in chapter 2.
Subject to survival craft and rescue boat embarkation arrangements being effective within the environmental conditions in which the craft is permitted to operate and in all undamaged and prescribed damage conditions of trim and heel, where the freeboard between the intended embarkation position and the waterline is not more than 1.5 m, the Administration may accept a system where persons board liferafts directly.
Rescue boat embarkation arrangements should be such that the rescue boat can be boarded and launched directly from the stowed position and recovered rapidly when loaded with its full complement of persons and equipment.
A safety knife should be provided at each MES embarkation station.
Li ne - throwing appliance
A line-throwing appliance complying with the requirements of regulation III/49 of the Convention should be provided.
Operational readiness . maintenance and inspections
Operational readiness

---CHUNK---

SOURCE: MSC.36(63).pdf
Li ne - throwing appliance
A line-throwing appliance complying with the requirements of regulation III/49 of the Convention should be provided.
Operational readiness . maintenance and inspections
Operational readiness
Before the craft leaves port and at all times during the voyage, all life-saving appliances should be in working order and ready for immediate use.
Maintenance

. 1 Instructions for on-board maintenance of life-saving appliances complying with the requirements of regulation III/52 of the Convention should be provided and maintenance should be carried out accordingly .
. 2 The Administration may accept, in lieu of the instructions required by .1, a shipboard planned maintenance programme which includes the requirements of regulation III/52 of the Convention.
W/1687n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT 8.9.3
8.9.4
8.9.5
8.9.6
8.9.7
Maintenance of falls
MSC 62/23/Add.2
ANNEX 18
Page 89
Falls used in launching should be turned end for end at intervals of not more than 30 months and be renewed when necessary due to

---CHUNK---

SOURCE: MSC.36(63).pdf
FOR HIGH SPEED CRAFT 8.9.3
8.9.4
8.9.5
8.9.6
8.9.7
Maintenance of falls
MSC 62/23/Add.2
ANNEX 18
Page 89
Falls used in launching should be turned end for end at intervals of not more than 30 months and be renewed when necessary due to
deterioration of the falls or at intervals of not more than five years, whichever is the earlier.
Spares and repair equipment
Spares and repair equipment should be provided for life-saving appliances and their components which are subject to excessive wear or consumption and need to be replaced regularly.
Weekly inspection
The following tests and inspections should be carried out weekly:
.1 all survival craft, rescue boats and launching appliances should be visually inspected to ensure that they are ready for use;
.2 all engines in rescue boats should be run ahead and astern for a total period of not less than 3 min provided the ambient temperature is above the minimum temperature required for starting the engine;
.3 the general emergency alarm system should be tested.

Monthly inspections
Inspection of the life-saving appliances, including survival craft

---CHUNK---

SOURCE: MSC.36(63).pdf
temperature is above the minimum temperature required for
starting the engine;
.3 the general emergency alarm system should be tested.
Monthly inspections
Inspection of the life-saving appliances, including survival craft
equipment should be carried out monthly using the checklist required
by regulation 111/52.1 of the Convention to ensure that they are
complete and in good order. A report of the inspection should be
entered in the log-book.
Servicing of inflatable liferafts, inflatable lifejackets and
inflated rescue boats
.1 Every inflatable liferaft, inflatable lifejacket and MES
should be serviced:
.1.1 at intervals not exceeding 12 months, provided where in
any case this is impracticable, the Administration may
extend this period by one month;
.1.2 at an approved servicing station which is competent to
service them, maintains proper servicing facilities and
uses only properly trained personnel.*
Refer to the Recommendation on conditions for the approval of servicing
stations for inflatable liferafts, adopted by the Organization by
resolution A.693(17).
W/1687n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)

---CHUNK---

SOURCE: MSC.36(63).pdf
Refer to the Recommendation on conditions for the approval of servicing
stations for inflatable liferafts, adopted by the Organization by
resolution A.693(17).
W/1687n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT MSC 62123/Add.2
ANNEX 18
Page 90
8.9.8
8.9.9
8.10
8.10.1
All repairs and maintenance of inflated rescue boats should be
carried out in accordance with the manufacturer's instructions.
Emergency repairs may be carried out on board the craft; however,
permanent repairs should be effected at an approved servicing
station.

Periodic servicing of hydrostatic release units
Hydrostatic release units should be serviced:
.1 at intervals not exceeding 12 months, provided where in any case this is impracticable, the Administration may extend this period by one 'month;
.2 at a servicing station which is competent to service them, maintains proper servicing facilities and uses only properly trained personnel.
Survival craft and resc ue boat~
All craft should carry:
.1 survival craft with sufficient capacity as will accommodate

---CHUNK---

SOURCE: MSC.36(63).pdf
maintains proper servicing facilities and uses only properly trained personnel.
Survival craft and resc ue boat~
All craft should carry:
.1 survival craft with sufficient capacity as will accommodate not less than 100% of the total number of persons the craft is certified to carry, subject to a minimum of two such survival craft being carried;