.2 in addition, survival craft with sufficient aggregate capacity to accommodate not less than 10% of the total number of persons the craft is certified to carry;
.3 in the event of anyone survival craft being lost or rendered unserviceable, sufficient survival craft to accommodate the total number of persons the craft is certified to carry;
.4 at least one rescue boat for retrieving persons from the water, but not less than one such boat on each side when the craft is certified to carry more than 450 passengers;
.5 craft of less than 20 m in length may be exempted from carrying a rescue boat, provided the craft meets all of the following requirements:
.5.1
.5.2
.5.3
the craft is arranged to allow a helpless person to be recovered from the water;
recovery of the helpless person can be observed from the

---CHUNK---

SOURCE: MSC.36(63).pdf
carrying a rescue boat, provided the craft meets all of the following requirements:
.5.1
.5.2
.5.3
the craft is arranged to allow a helpless person to be recovered from the water;
recovery of the helpless person can be observed from the navigating bridge; and
the craft is sufficiently manoeuvrable to close and recover persons ill the worst intended conditions.
W/1687n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY FOR HIGH SPEED CRAFT 8.10.2
MSC 62/23/Add.2
ANNEX 18
Page 91
.6 notwithstanding prov1s1ons of .4 and .5 above, craft should carry sufficient rescue boats to ensure that, in providing for abandonment by the total number of persons the craft is certified to carry:
.6.1
.6.2
.6.3
not more than nine of the liferafts provided in accordance with 8.10.1.1 are marshalled by each rescue boat; or
if the Administration is satisfied that the rescue boats are capable of towing a pair of such liferafts simultaneously, not more than 12 of the liferafts

provided in accordance with 8.10.1.1 are marshalled
by each rescue boat; and
the craft can be evacuated within the time specified
in 4.8.

---CHUNK---

SOURCE: MSC.36(63).pdf
boats are capable of towing a pair of such liferafts
simultaneously, not more than 12 of the liferafts
provided in accordance with 8.10.1.1 are marshalled
by each rescue boat; and
the craft can be evacuated within the time specified
in 4.8.
Where the Administration considers it appropriate, in view of the
sheltered nature of the voyages and the suitable climatic conditions
of the intended area of operations, the Administration may permit
the use of open reversible inflatable liferafts complying with
annex 10 on category A craft as an alternative to liferafts
complying with regulation 111/39 or 111/40 of the Convention.
W/1687n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT MSC 62/23/Add.2
ANNEX 18
Page 92
9.1
9.1.1
9.1.2
9.1.3
9.1.4
9.1.5
CHAPTER 9 - MACHINERY
PART A - GENERAL
General
The machinery, associated piping systems and fittings relating to
main machinery and auxiliary power units should be of a design and
construction adequate for the service for which they are intended
and should be so installed and protected as to reduce to a minimum

---CHUNK---

SOURCE: MSC.36(63).pdf
main machinery and auxiliary power units should be of a design and
construction adequate for the service for which they are intended
and should be so installed and protected as to reduce to a minimum
any danger to persons on board, due regard being paid to moving
parts, hot surfaces and other hazards. The design should have
regard to materials used in construction, the purpose for which the
equipment is intended, the working conditions to which it will be
s?bjected and the environmental conditions on board.
All surfaces with temperatures exceeding 220°C where impingement of
flammable liquids may occur as a result of a system failure should

be insulated. The insulation should be impervious to flammable liquids and vapours.

Special consideration should be given to the reliability of single essential propulsion components and may require a separate source of propulsion power sufficient to give the craft a navigable speed, especially in the case of unconventional arrangements.

,

Means should be provided whereby normal operation of propulsion machinery can be sustained or restored even though one of the

---CHUNK---

SOURCE: MSC.36(63).pdf

especially in the case of unconventional arrangements.

,

Means should be provided whereby normal operation of propulsion machinery can be sustained or restored even though one of the essential auxiliaries becomes inoperative. Special consideration should be given to the malfunctioning of:

.1 a generating set which serves as a main source of electrical power;

.2 the fuel oil supply systems for engines;

.3 the sources of lubricating oil pressure;

.4 the sources of water pressure;

.5 an air compressor and receiver for starting or control purposes;

.6 the hydraulic, pneumatic or electrical means for control in main propulsion machinery including controllable pitch propellers.

However, having regard to overall safety considerations, a partial reduction in propulsion capability from normal operation may be accepted.

Means should be provided to ensure that the machinery can be brought into operation from the dead craft condition without external aid.

W/1687n/pp/EWP

RESOLUTION MSC.36(63)

(adopted on 20 May 1994)

ADOPTION OF THE INTERNATIONAL CODE OF SAFETY FOR HIGH SPEED CRAFT 9.1.6

9.1.7

9.1.8

9.1.9

9.1.10

9.1.11

9.1.12

9.1.13

9.1.14

MSC 62/23/Add.2

---CHUNK---

SOURCE: MSC.36(63).pdf

W/1687n/pp/EWP

RESOLUTION MSC.36(63)

All parts of machinery, hydraulic, pneumatic and other systems and their associated fittings which are under internal pressure should be subjected to appropriate tests including a pressure test before being put into service for the first time.

Provision should be made to facilitate cleaning, inspection and maintenance of main propulsion and auxiliary machinery including boilers and pressure vessels.

The reliability of machinery installed in the craft should be adequate for its intended purpose.