The Administration may accept machinery which does not show detailed compliance with the Code where it has been used satisfactorily in a similar application, provided that it is satisfied:
.1 that the design, construction, testing, installation and prescribed maintenance are together adequate for its use in a marine environment; and
.2 that an equivalent level of safety will be achieved.

---CHUNK---

SOURCE: MSC.36(63).pdf
.1 that the design, construction, testing, installation and prescribed maintenance are together adequate for its use in a marine environment; and
.2 that an equivalent level of safety will be achieved.
A failure mode and effect analysis should include machinery systems and their associated controls.
Such information as is necessary to ensure that machinery can be installed correctly regarding such factors as operating conditions , and limitations should be made available by the manufacturers.
Main propulsion machinery and all auxiliary machinery essential to the propulsion and the safety of the craft should, as fitted in the craft, be designed to operate when the craft is upright and when inclined at any angle of list up to and including 15° either way under static conditions and 22.5
0
under dynamic conditions (rolling)
either way and simultaneously inclined by dynamically (pitching)
7.5 0 by bow or stern. The Administration may permit deviation from these angles, taking into consideration the type, size and service conditions of the craft.
All boilers, and pressure vessels and associated piping systems

---CHUNK---

SOURCE: MSC.36(63).pdf
7.5 0 by bow or stern. The Administration may permit deviation from these angles, taking into consideration the type, size and service conditions of the craft.
All boilers, and pressure vessels and associated piping systems should be of a design and construction adequate for the purpose intended and should be so installed and protected as to m1n1mize danger to persons on board. In particular, attention should be paid to the materials used in the construction and the working pressures and temperatures at which the item will operate and the need to provide an adequate margin of safety over the stresses normally produced in service. Every boiler, pressure vessel and associated piping systems should be fitted with adequate means to prevent over-pressures in service and be subjected to a hydraulic test before being put into service, and where appropriate at subsequent specified intervals, to a pressure suitably in excess of the working pressure.
Arrangements should be provided to ensure that, in the event of failure in any liquid cooling system, it is rapidly detected and

alarmed (visual and audible) and means instituted to minimize the

---CHUNK---

SOURCE: MSC.36(63).pdf
pressure.
Arrangements should be provided to ensure that, in the event of failure in any liquid cooling system, it is rapidly detected and alarmed (visual and audible) and means instituted to minimize the effects of such failures on machinery serviced by the system.
W/1687n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT MSC 62123/Add.2
ANNEX 18
Page 94
9.2
9.2.1
9.2.2
9.2.3
9.2.4
9.2.5
9.2.6
9.2.7
9.2.8
9.2.9
Engine (general)
The engines should be fitted with adequate safety monitoring and control devices in respect of speed, temperature, pressure and other operational functions. Control of the machinery should be from the craft's operating compartment. Category B craft and cargo craft should be provided with additional machinery controls in or close to the machinery space. The machinery installation should be suitable for operation as in an unmanned machinery space* including automatic fire detection system, bilge alarm system, remote machinery instrumentation and alarm system. Where the space is continuously manned, this requirement may be varied in accordance with the

---CHUNK---

SOURCE: MSC.36(63).pdf
fire detection system, bilge alarm system, remote machinery instrumentation and alarm system. Where the space is continuously manned, this requirement may be varied in accordance with the requirements of the Administration.
The engines should be protected against overspeed, loss of lubricating oil pressure, loss of cooling medium, high temperature, malfunction of moving parts and overload. Safety devices should not cause complete engine shutdown without prior warning, except in cases where there is a risk of complete breakdown or explosion. Such safety devices should be capable of being tested.
At least two independent means of stopping the engines quickly from the operating compartment under any operating conditions should be

available. Duplication of the actuator fitted to the engine should not be required.
The major components of the engine should have adequate,strength to withstand the thermal and dynamic conditions of normal operation.
The engine should not be damaged by a limited operation at a speed or at temperatures exceeding the normal values but within the range of the protective devices.

---CHUNK---

SOURCE: MSC.36(63).pdf
withstand the thermal and dynamic conditions of normal operation.
The engine should not be damaged by a limited operation at a speed or at temperatures exceeding the normal values but within the range of the protective devices.
The design of the engine should be such as to minimize the risk of fire or explosion and to enable compliance with the fire precaution requirements of chapter 7.
Provision should be made to drain all excess fuel and oil to a safe position so as to avoid a fire hazard.
Provision should be made to ensure that, whenever practical, the failure of systems driven by the engine should not unduly affect the integrity of the major components.
The ventilation arrangements in the machinery spaces should be adequate under all envisaged operating conditions. Where appropriate, arrangements should ensure that enclosed engine compartments are forcibly ventilated to the atmosphere before the engine can be started.
Any engines should be so installed as to avoid excessive vibration within the craft.
* Refer to part E of chapter 11-1 of the Convention.
WI1687n/pp/EWP
..
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)

---CHUNK---

SOURCE: MSC.36(63).pdf
engine can be started.
Any engines should be so installed as to avoid excessive vibration within the craft.
* Refer to part E of chapter 11-1 of the Convention.
WI1687n/pp/EWP
..
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT 9.3
9.3.1
9.3.2
9.3.3
9.3.4
9.3.5

9.3.6
9.3.7
9.3.8
9.3.9
9.4
9.4.1
Gas turbines

Gas turbines should be designed to operate in the marine environment and should be free from surge or dangerous instability throughout its operating range up to the maximum steady speed approved for use. The turbine installation should be arranged to ensure that the turbine cannot be continuously operated within any speed range where excessive vibration, stalling, or surging may be encountered.
The gas turbines should be designed and installed such that any reasonably probable shedding of compressor or turbine blades will not endanger the craft, other machinery, occupants of the craft or any other persons.
Requirements of 9.2.6 should apply to gas turbines in respect of fuel which might reach the interior of the jet pipe or exhaust