. 3 The lift divices, for the purposes of this section, are those items of machinery which directly raise the pressure of the air and move it for the primary purpose of providing lifting force for an air-cushion vehicle.

---CHUNK---

SOURCE: MSC.36(63).pdf
. 3 The lift divices, for the purposes of this section, are those items of machinery which directly raise the pressure of the air and move it for the primary purpose of providing lifting force for an air-cushion vehicle.
The propulsion and lift devices should be of adequate strength and stiffness. The design data, calculations and trials, where necessary, should establish the ability of the device to withstand the loads which can arise during the operations for which the craft is to be certificated, so that the possiblity of catastrophic failure is extremely remote.
The design of propulsion and lift devices should pay due regard to the effects of allowable corrosion, electrolytic action between different metals, erosion or cavitation which may result from operation in environments in which they are subjected to spray, debris, salt, sand, icing, etc.
The design data and testing of propulsion and lift devices should pay due regard, as appropriate, to any pressure which could be developed as a result of a duct blockage, to steady and cyclic loadings, to loadings due to external forces and to the use of the

---CHUNK---

SOURCE: MSC.36(63).pdf
pay due regard, as appropriate, to any pressure which could be developed as a result of a duct blockage, to steady and cyclic loadings, to loadings due to external forces and to the use of the devices in manoeuvring and reversing and to the axial location of rotating parts.
W/1687n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT MSC 62123/Add.2
ANNEX 18
Page 98
9.6.5 Appropriate arrangements should be made to ensure that:
.1 ingestion of debris or foreign matter is minimized;
. 2 the possibility of injury to personnel from shafting or rotating parts is minimized; and
. 3 where necessary, inspection and removal of debris can be carried out safely in service.
PART B - REQUIREMENTS FOR PASSENGER CRAFT
9.7 Independent means of propulsion for category B craft
Category B craft should be provided with at least two independent means of propulsion so that the failure of one engine or its support systems would not cause the failure of the other engine or engine systems and

with additonal machinery controls in or close to the machinery space.

---CHUNK---

SOURCE: MSC.36(63).pdf
of propulsion so that the failure of one engine or its support systems
would not cause the failure of the other engine or engine systems and
with additonal machinery controls in or close to the machinery space.
9.8 Means for return to a port of refuge for category B craft
Category B craft should be capable of maintaining the essential machinery
and control so that, in the event of a fire or other casualties in any
one compartment on board, the craft can return to a port of refuge under
its own power.
PART C - REQUIREMENTS FOR CARGO CRAFT
9.9 Essential machinery and .control
Cargo craft should be capable of maintaining the essential machinery
and control in the event of a fire or other casualties in one of any
compartment on board. The craft need not be able to return to a place
of refuge under its own power.
W/1687n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT 10.1
10.1.1
10.1. 2
10.1. 3
10.1. 4
10.1. 5
10.2
10.2.1
10.2.2
CHAPTER 10 - AUXILIARY SYSTEMS
PART A - GENERAL
General
MSC 62123/Add.2
ANNEX 18
Page 99
Fluid systems should be constructed and arranged so as to assure

---CHUNK---

SOURCE: MSC.36(63).pdf
10.1.1
10.1. 2
10.1. 3
10.1. 4
10.1. 5
10.2
10.2.1
10.2.2
CHAPTER 10 - AUXILIARY SYSTEMS
PART A - GENERAL
General

Fluid systems should be constructed and arranged so as to assure a safe and adequate flow of fluid at a prescribed flow rate and pressure under all conditions of craft operation. The probability of a failure or a leakage in anyone fluid system causing damage to the electrical system, a fire or an explosion hazard should be extremely remote. Attention should be directed to the avoidance of flammable liquid impingement on hot surfaces in the event of leakage or fracture of the pipe.
The maximum allowable working pressure in any part of the fluid system should not be greater than the design pressure, having regard to the allowable stresses in the materials. Where the maximum allowable working pressure of a system component, such as a valve or a fitting, is less than that computed for the pipe or tubing, the system pressure should be limited to the lowest of the component minimum allowable working pressures. Every system which may be exposed to pressures higher than the system's maximum allowable

---CHUNK---

SOURCE: MSC.36(63).pdf
system pressure should be limited to the lowest of the component minimum allowable working pressures. Every system which may be exposed to pressures higher than the system's maximum allowable working pressure should be safeguarded by appropriate relief devices.
Tanks and piping should be pressure tested to a pressure that will assure a safety margin in excess of the working pressur~ of the item. The test on any storage tank or reservoir should take into account any possible static head in the overflow condition ' and the dynamic forces arising from craft motions.
Materials used in piping systems should be compatible with the fluid conveyed and selected giving due regard to the risk of fire.
Non-metallic piping material may be permitted in certain systems provided the integrity of the hull and watertight decks and bulkheads is maintained.*
For the purposes of this chapter, the term "datum" means the datum described in 2.2.1.3.
Arrangement Qf oil fuel . lubric~ oil and other flammable oil
The provisions of 7.1.2.2 should apply to the use of oil as fuel.
Oil fuel, lubricating oil and other flammable oil lines should be

---CHUNK---

SOURCE: MSC.36(63).pdf
described in 2.2.1.3.
Arrangement Qf oil fuel . lubric~ oil and other flammable oil
The provisions of 7.1.2.2 should apply to the use of oil as fuel.
Oil fuel, lubricating oil and other flammable oil lines should be screened or otherwise suitably protected to avoid, as far as practicable, oil spray or oil leakages onto hot surfaces, into machinery air intakes or other sources of ignition. The number of joints in such piping systems should be kept to a minimum. Flexible

pipes carrying flammable liquids should be of an approved type.**
* Refer to the Guidelines for materials other than steel for pipes, adopted by the Organization by resolution A.753(18).
** Refer to MSC/Circ.647 on the Guidelines to minimize leakages from flammable liquid systems for improving reliability and reducing risk of fire.
W /1687 n/ppl EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT MSC 62/23/Add.2
ANNEX 18
Page 100
10.2.3 Fuel oil, lubricating oils and other flammable oils should not be carried forward of public spaces and crew accommodation.
Oil fuel arrangements
10.2.4
10.2.4.1
10.2.4.2
10.2.4.3
10.2.4.4

---CHUNK---