SOURCE: MSC.36(63).pdf
ANNEX 18
Page 100
10.2.3 Fuel oil, lubricating oils and other flammable oils should not be carried forward of public spaces and crew accommodation.
Oil fuel arrangements
10.2.4
10.2.4.1
10.2.4.2
10.2.4.3
10.2.4.4
10.2.4.5
10.2.4.6
10.2.4.7
10.2.4.7.1
10.2.4.7.2
W/1687n/pp/EWP
In a craft in which oil fuel is used, the arrangements for the storage, distribution and utilization of the oil fuel should be such as to ensure the safety of the craft and persons on board and should at least comply with the following provisions.
As far as practicable, all parts of the oil fuel system containing heated oil under pressure exceeding 0.18 N/mm2 should not be placed in a concealed position such that defects and leakage cannot readily be observed. The machinery spaces in way of such parts of the oil fuel system should be adequately illuminated.
The ventilation of machinery spaces should be sufficient under all normal conditions to prevent accumulation of oil vapour.
Location of fuel tanks should be in accordance with 7.5.2.
No oil fuel tank should be situated where spillage or leakage therefrom can constitute a hazard by falling on heated

---CHUNK---

SOURCE: MSC.36(63).pdf
all normal conditions to prevent accumulation of oil vapour.
Location of fuel tanks should be in accordance with 7.5.2.
No oil fuel tank should be situated where spillage or leakage therefrom can constitute a hazard by falling on heated
surfaces. Reference is made to the fire safety requirements in 7.5
,
Oil fuel pipes should be fitted with cocks or valves in accordance with 7.5.3.
Every fuel tank should, where necessary, be provided with savealls or gutters to catch any fuel which may leak from such tanks.
Safe and efficient means of ascertaining the amount of oil fuel contained in any oil fuel tank should be provided.
Where sounding pipes are used they should not terminate in any space where the risk of ignition of spillage from the sounding pipe might arise. In particular, they should not terminate in public spaces, crew accommodation or maChinery spaces.

Terminations should be provided with a suitable means of closure and provision to prevent spillage during refuelling operations.
Other oil-level gauges may be used in place of sounding pipes. Such means should be subject to the following conditions:
.1 In passenger craft, such means should not require

---CHUNK---

SOURCE: MSC.36(63).pdf
and provision to prevent spillage during refuelling operations.
Other oil-level gauges may be used in place of sounding pipes. Such means should be subject to the following conditions:
.1 In passenger craft, such means should not require penetration below the top of the tank and their failure or overfilling of the tanks will not permit release of fuel .
. 2 The use of cylindrical gauge glasses should be prohibited. In cargo craft, the Administration may permit the use of oil-level gauges with flat glasses and self-closing valves between the gauges and fuel tanks. Such other means should be acceptable to the Administration and should be maintained in the proper condition to ensure their continued accurate functioning in service.
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY FOR HIGH SPEED CRAFT 10.2.4.8
10.2.4.9
MSC 62/23/Add.2
ANNEX 18
Page 101
Provision should be made to prevent overpressure in any oil tank or in any part of the oil fuel system, including the filling pipes. Any relief valves and air or overflow pipes should discharge to a safe position and, for fuel of flashpoint less

---CHUNK---

SOURCE: MSC.36(63).pdf
Provision should be made to prevent overpressure in any oil tank or in any part of the oil fuel system, including the filling pipes. Any relief valves and air or overflow pipes should discharge to a safe position and, for fuel of flashpoint less
than 43°C, should terminate with flame arresters in accordance with the standards developed by the Organization.*
Oil fuel pipes and their valves and fittings should be of steel or other approved material, except that restricted use of flexible pipes should be permissible in positions where the Administration is satisfied that they are necessary. Such flexible pipes and end attachments should be of approved fire-resisting materials of adequate strength and should be constructed to the satisfaction of the Administration.
Lubricating oil arrangements
10.2.5 The arrangements for the storage, distribution and utilization of oil used in pressure lubrication systems should be such as to

ensure the safety of the craft and persons on board. The arrangements made in machinery spaces and, whenever practicable, in auxiliary machinery spaces should at least comply with the

---CHUNK---

SOURCE: MSC.36(63).pdf
ensure the safety of the craft and persons on board. The arrangements made in machinery spaces and, whenever practicable, in auxiliary machinery spaces should at least comply with the provisions of 10.2.4.1 and 10.2.4.4 to 10.2.4.8 except that:
.1 this does not preclude the use of sight-flow glasses in lubricating systems provided they are shown by test to have a suitable degree of fire resistance;
.2 sounding pipes may be permitted in machinery spaces if fitted with appropriate means of closure; and
.3 lubricating oil storage tanks with a capacity of less than 500 1 may be permitted without remote operated valves as required in 10.2.4.5.
Arrangements for other flammable oils
10.2.6 The arrangements for storage, distribution and utilization of other flammable oils employed under pressure in power transmission systems, control and activating systems and heating systems should be such as to ensure the safety of the craft and persons on board. In locations where means of ignition are present, such arrangements should at least comply with the provi~ions of 10.2.4.4 and 10.2.4.7 and with the prov1s1ons of

---CHUNK---

SOURCE: MSC.36(63).pdf
systems should be such as to ensure the safety of the craft and persons on board. In locations where means of ignition are present, such arrangements should at least comply with the provi~ions of 10.2.4.4 and 10.2.4.7 and with the prov1s1ons of 10.2.4.8 and 10.2.4.9 in respect of strength and construction.
* Refer to the Revised standards for the design, testing and locating of devices to prevent the passage of flame into cargo tanks (MSCICirc.373/Rev.1).
W/1687n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY FOR HIGH SPEED CRAFT MSC 62/23/Add.2
ANNEX 18
Page 102
Arrangements within machinery spaces
10.2.7 In addition to the requirements of 10.2.1 to 10.2.6, the oil fuel and lubricating oil systems should comply with the following:
10.2.7.1 Where daily service fuel tanks are filled automatically or by remote control, means should be provided to prevent overflow spillages.
10.2.7.2 Other equipment which treats flammable liquids automatically, such as oil fuel purifiers, which, whenever practicable, should be installed in a special space reserved for purifiers and their

---CHUNK---

SOURCE: MSC.36(63).pdf
10.2.7.2 Other equipment which treats flammable liquids automatically, such as oil fuel purifiers, which, whenever practicable, should be installed in a special space reserved for purifiers and their heaters, should have arrangements to prevent overflow spillages.
10.2.7.3 Where daily service oil fuel tanks or settling tanks are fitted with heating arrangements, a high temperature alarm should be provided if the flashpoint of the oil can be reached due to failure of the thermostatic control.
10.3 Bilge pumping and drainage systems
10.3.1 Arrangements should be made for draining any watertight compartment other than the compartments intended for permanent storage of liquid. Where in relation to particular compartments drainage is not considered necessary, drainage arrangements may be omitted but it should be demonstrated that the safety of the craft will not be impaired.
10.3.2
10.3.3
10.3.4
10.3.5