Bilge pumping arrangements should be provided to allow every watertight compartment other than those intended for permanent storage of liquid to be drained. The capacity or position of any such compartment should be such that flooding thereof could not

---CHUNK---

SOURCE: MSC.36(63).pdf
watertight compartment other than those intended for permanent storage of liquid to be drained. The capacity or position of any such compartment should be such that flooding thereof could not affect the safety of the craft.
The bilge pumping system should be capable of operation under all possible values of list and trim after the craft has sustained the postulated damage in 2.6.5 and 2.6.8. The bilge pumping system should be so designed as to prevent water flowing from one compartment to another. The necessary valves for controlling the bilge suctions should be capable of being operated from above the datum. All distribution boxes and manually operated valves in connection with the bilge pumping arrangements should be in positions which are accessible under ordinary circumstances.
The power operated self-priming bilge pumps may be used for other duties such as fire fighting or general service but not for pumping fuel or other flammable liquids.
Each power bilge pump should be capable of pumping water through the required bilge pipe at a speed of not less than 2 m/s.
W/1687n/pp/EWP
(
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)

---CHUNK---

SOURCE: MSC.36(63).pdf
fuel or other flammable liquids.
Each power bilge pump should be capable of pumping water through the required bilge pipe at a speed of not less than 2 m/s.
W/1687n/pp/EWP
(
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT 10.3.6
10.3.7
10.3.8
10.3.9
10.3.10
10.3.11
10.3.12
10.3.13
10.3.14
MSC 62/23/Add.2
ANNEX 18
Page 103

The diameter (d) of the bilge main should be calculated according to the following formula, except that the actual internal diameter of the bilge main may be rounded off to the nearest size of a recognized standard:
where:
d = 25 + 1.68(L(B + D»0.5
d is the internal diameter of the bilge main (mm);
L is the length of the craft (m) as defined in chapter 1;
B is for monohull craft, the breadth of the craft in m as defined in chapter 1 and for multihull craft, the breadth of a hull at or below the design waterline (m); and
D is the moulded depth of the craft to the datum (m).
Internal diameters of suction branches should meet the requirements of the Administration but should not be less than 25 ~n. Suction branches should be fitted with effective strainers.

---CHUNK---

SOURCE: MSC.36(63).pdf
D is the moulded depth of the craft to the datum (m).
Internal diameters of suction branches should meet the requirements of the Administration but should not be less than 25 ~n. Suction branches should be fitted with effective strainers.
An emergency bilge suction should be provided for each machinery space containing a propulsion prime mover. This suction should be led to the largest available power pump other than a bilge pump, propulsion pump or oil pump.
The spindles of the sea inlet valves should extend well above the machinery space floor plates.
All bilge suction piping up to the connection to the pumps should be independent of other piping.
Spaces situated above the water level in the worst anticipated damage conditions may be drained directly overboard through scuppers fitted with nonreturn valves.
Any unattended space for which bilge pumping arrangements are required should be provided with a bilge alarm.
For craft with individual bilge pumps, the total capacity Q of the bilge pumps for each hull should not be less than 2.4 times the capacity 'of the pump defined in 10.3.5 and 10.3.6.
In bilge pumping arrangements where a bilge main is not provided

---CHUNK---

SOURCE: MSC.36(63).pdf
bilge pumps for each hull should not be less than 2.4 times the capacity 'of the pump defined in 10.3.5 and 10.3.6.
In bilge pumping arrangements where a bilge main is not provided then, with the exception of the spaces forward of public spaces and crew accommodation, at least one fixed submersible pump should be provided for each space. In addition, at least one portable pump should be provided supplied from the emergency supply, if electric, for use on individual spaces. The capacity of each submersible pump Qn should not be less than:
Qn Q/{N-1) tonne/h with a minimum of 8 tonnes/h

where: N = number of submersible pumps
Q = total capacity as defined in 10.3.13.
W/1687n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT MSC 62/23/Add.2
ANNEX 18
Page 104
10.3.15
10.4
10.4.1
10.4.2
10.5
10.6
10.7
10.8
10.8.1
Nonreturn valves should be fitted in the following components:
.1 bilge valve distribution manifolds;
.2 bilge suction hose connections where fitted directly to the
pump or to the main bilge suction pipe; and
.3 direct bilge suction pipes and bilge pump connections to main

---CHUNK---

SOURCE: MSC.36(63).pdf
.1 bilge valve distribution manifolds;
.2 bilge suction hose connections where fitted directly to the
pump or to the main bilge suction pipe; and
.3 direct bilge suction pipes and bilge pump connections to main
bilge suction pipe.
Ballast systems
Water ballast should not in general be carried in tanks intended for
oil fuel. In craft in which it is not practicable to avoid putting
water in oil fuel tanks, oily-water separating equipment should be
fitted, or other alternative means such as discharge to shore
facilities should be provided for disposing of the oily-water
ballast. The provisions of this paragraph are without prejudice to
the provisions of the International Convention for the Prevention of
Pollution from Ships in force.
Where a fuel transfer system is used for ballast purposes, the
system should be isolated from any water ballast system and meet the
requirements for fuel systems and the International Convention for
the Prevention of Pollution from Ships in force.
Cooling systems
The cooling arrangements provided should be adequate to maintain all
lubricating and hydraulic fluid temperatures within manufacturers'

---CHUNK---

SOURCE: MSC.36(63).pdf
the Prevention of Pollution from Ships in force.
Cooling systems

The cooling arrangements provided should be adequate to maintain all lubricating and hydraulic fluid temperatures within manufacturers' recommended limits during all operations for which the craft is to be certificated.

Engine air intake systems

Arrangements should provide sufficient air to the engine and should give adequate protection against damage as distinct from deterioration, due to ingress of foreign matter.

Ventilation systems

Machinery spaces should be adequately ventilated so as to ensure that when machinery therein is operating at full power in all weather rionditions including heavy weather, an adequate supply of air is maintained to the spaces for the safety and comfort of personnel and the operation of the machinery. Auxiliary machinery spaces should be adequately ventilated appropriate for the purpose of those spaces. The ventilation arrangements should be adequate to ensure that the safe operation of the craft is not put at risk.

Exhaust systems

All engines exhaust systems should be adequate to assure the correct

---CHUNK---

SOURCE: MSC.36(63).pdf