of those spaces. The ventilation arrangements should be adequate to ensure that the safe operation of the craft is not put at risk.
Exhaust systems
All engines exhaust systems should be adequate to assure the correct functioning of the machinery and that safe operation of the craft is not put at risk.
W/1687n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT 10.8.2
10.8.3
10.8.4
10.9
10.9.1
10.9.2
10.9.3
10.9.4
10.9.5
MSC 62/23/Add.2
ANNEX 18
Page 105
Exhaust systems should be so arranged as to minimize the intake of exhaust gases into manned spaces, air-conditioning systems, and engine intakes. Exhaust systems should not discharge into air cushion intakes.
Pipes through which exhaust gases are discharged through the hull in the vicinity of the waterline should be fitted with erosion/corrosion resistant shut-off flaps or other devices on the shell or pipe end and acceptable arrangements made to prevent water flooding the space or entering the engine exhaust manifold.
Gas turbine engine exhausts should be arranged so that hot exhaust

---CHUNK---

SOURCE: MSC.36(63).pdf
shell or pipe end and acceptable arrangements made to prevent water flooding the space or entering the engine exhaust manifold.
Gas turbine engine exhausts should be arranged so that hot exhaust
gases are directed away from areas to which personnel have access, either on board the craft or in the vicinity of the craft when berthed.
PART B - REQUIREMENTS FOR PASSENGER CRAFT
Bilge pump ing a nd dra i nage syste ms
For category B craft at least three and for category A craft at least two power bilge pumps should be fitted connected to the bilge main, one of which may be driven by the propulsion machinery. Alternatively, the arrangement may be in accordance with the requirements of 10.3.14.
The arrangements should be such that at least one power pilge pump should be available for use in all flooding conditions which the craft is required to withstand as follows:
.1 one of the required bilge pumps should be an emergency pump of a reliable submersible type having an emergency source of

power; or
.2 the bilge pumps and their sources of power should be so distributed throughout the length of the craft that at least

---CHUNK---

SOURCE: MSC.36(63).pdf
a reliable submersible type having an emergency source of power; or
.2 the bilge pumps and their sources of power should be so distributed throughout the length of the craft that at least one pump in an undamaged compartment will be available.
On multihull craft, each hull should be provided with at least two bilge pumps.
Distribution boxes, cocks and valves in connection with the bilge pumping system should be so arranged that, in the event of flooding, one of the bilge pumps may be operative in any compartment. In addition, damage to a pump or its pipe connecting to the bilge main should not put the bilge system out of action. When, in addition to the main bilge pumping system, an emergency bilge pumping system is provided, it should be independent of the main system and so arranged that a pump is capable of operating in any compartment under flooding conditions as specified in 10.3.3. In that case only the valves necessary for the operation of the emergency system need be capable of being operated from above the datum.
All cocks and valves referred to in 10.9.4 which can be operated from above the datum should have their controls at their place of

---CHUNK---

SOURCE: MSC.36(63).pdf
be capable of being operated from above the datum.
All cocks and valves referred to in 10.9.4 which can be operated from above the datum should have their controls at their place of operation clearly marked and should be provided with means to indicate whether they are open or closed.
W/1687n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT MSC 62123/Add.2
ANNEX 18
Page 106
10.10
10.10.1
10.10.2
PART C - REQUIREMENTS FOR CARGO CRAFT
Bilge pumping systems
At least two power pumps connected to the main bilge system should be provided, one of which may be driven by the propulsion machinery. If the Administration is satisfied that the safety of the craft is not impaired, bilge pumping arrangements may be dispensed with in particular compartments. Alternatively, the arrangement may be in accordance with the requirements of 10.3.14.

On multihull craft each hull should be provided with at least two power pumps, unless a bilge pump in one hull is capable of pumping bilge in the other hull. At least one pump in each hull should be an independent power pump.
W/1687n/pp/EWP
(

---CHUNK---

SOURCE: MSC.36(63).pdf
On multihull craft each hull should be provided with at least two power pumps, unless a bilge pump in one hull is capable of pumping bilge in the other hull. At least one pump in each hull should be an independent power pump.
W/1687n/pp/EWP
(
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT 11.1
11.1.1
11.1. 2
11. 2
11. 2.1
11. 2.2
11. 2.3
11. 2.4
11.3
11. 3.1
MSC 62123/Add.2
ANNEX 18
Page 107
CHAPTER 11 - REMOTE CONTROL, ALARM AND SAFETY SYSTEMS
Definitions
"Remote control systems" comprise all equipment necessary to operate units from a control position where the operator cannot directly observe the effect of his actions.
"Back-up control systems" comprise all equipment necessary to maintain control of essential functions required for the craft's safe operation when the main control systems have failed or malfunctioned.
yeneral
Failure of any remote or automatic control systems should initiate an audible and visual alarm and should not prevent normal manual control.
Manoeuvring and emergency controls should permit the operating crew

---CHUNK---

SOURCE: MSC.36(63).pdf
malfunctioned.
yeneral
Failure of any remote or automatic control systems should initiate an audible and visual alarm and should not prevent normal manual

control.
Manoeuvring and emergency controls should permit the operating crew to perform the duties for which they are responsible in a correct manner without difficulty, fatigue or excessive concentration.
Where control of propulsion or manoeuvring is provided at stations adjacent to but outside the operating compartment, the transfer of control should only be effected from the station which ~akes charge of control. Two-way voice communication should be provided between all stations from which control functions may be exercised and between each such station and the look-out position. Failure of the operating control system or of transfer of control should bring the craft to low speed without hazarding passengers or the craft.
For category B craft and cargo craft, remote control systems for propulsion machinery and di~ectional control should be equipped with back-up systems controllable from the operating compartment. For cargo craft, instead of a back-up system described above, a

---CHUNK---

SOURCE: MSC.36(63).pdf
propulsion machinery and di~ectional control should be equipped with back-up systems controllable from the operating compartment. For cargo craft, instead of a back-up system described above, a