back-up system controllable from an engine control space such as an engine control room outside the operating compartment is acceptable.

Emergency controls

In all craft, the station or stations in the operating compartment from which control of craft manoeuvring and/or of its main machinery is exercised should be provided, within easy reach of the crew member at that station, with controls for use in an emergency to:

.1 activate fixed fire-extinguishing systems:

.2 close ventilation openings and stop ventilating machinery supplying spaces covered by fixed fire-extinguishing systems, if not incorporated in .1;

.3 shut off fuel supplies to machinery in main and auxiliary machinery spaces;

11. 3.2

11.4

11. 4.1

.4 disconnect all electrical power sources from the normal power

---CHUNK---

SOURCE: MSC.36(63).pdf

RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT MSC 62123/Add.2
ANNEX 18
Page 108

11. 3.2

11.4

11. 4.1

.4 disconnect all electrical power sources from the normal power distribution system (the operating control should be guarded to reduce the risk of inadvertent or careless operation); and

.5 stop main engine(s) and auxiliary machinery.

Where control of propulsion and manoeuvring is provided at stations outside the operating compartment, such stations should have direct communication with the operating compartment which should be a continuously manned control station.

Alarm system

Alarm systems should be provided which announce at the craft's control position, by visual and audible means, malfunctions or unsafe conditions. Alarms should be maintained until they are accepted and the visual indications of individual alarms should remain until the fault has been corrected, when the alarm should automatically reset to the normal operating condition. If an alarm has been accepted and a second fault occurs before the first is rectified, the audible and visual alarms should operate again.

---CHUNK---

SOURCE: MSC.36(63).pdf
automatically reset to the normal operating condition. If an alarm has been accepted and a second fault occurs before the first is rectified, the audible and visual alarms should operate again. Alarm systems should incorporate a test facility.

11.4.1.1 Alarms giving indication of conditions requiring immediate action should be distinctive and in full view of crew members in the operating compartment, and should be provided for the following:

.1 activation of a fire detection system;
.2 total loss of normal electrical supply;
.3 overspeed of main engines;
.4 thermal runaway of any permanently installed nickel-cadmium battery.

11.4.1.2 Alarms with a visual display distinct from that of alarms referred ~o in 11.4.1.1 should indicate conditions requiring action to prevent degradation to an unsafe condition. These should be provided for at least the following:

.1 exceeding the limiting value of any craft, machinery or system parameter other than engine overspeed;
.2 failure of normal power supply to powered directional or trim control devices;
.3 operation of any automatic bilge pump;
.4 failure of compass system;
.5 low level of a fuel tank contents;

---CHUNK---

SOURCE: MSC.36(63).pdf
parameter other than engine overspeed;
.2 failure of normal power supply to powered directional or trim control devices;
.3 operation of any automatic bilge pump;
.4 failure of compass system;
.5 low level of a fuel tank contents;
.6 fuel oil tank overflow;
.7 extinction of side, masthead or stern navigation lights;

.8 low level of contents of any fluid reservoir the contents of which are essential for normal craft operation;
.9 failure of any connected electrical power source;
.10 failure of any ventilation fan installed for ventilating spaces in which inflammable vapours may accumulate .
. 11 diesel engine fuel line failure as required by 9.4.2.

11.4.1.3 All warnings required by 11.4.1.1 and 11.4.1.2 should be provided at all stations at which control functions may be exercised.

11.4.2 The alarm system should meet appropriate constructional and operational requirements for required alarms.~
11.4.3 Equipment monitoring the passenger, cargo and machinery spaces for

---CHUNK---

SOURCE: MSC.36(63).pdf
all stations at which control functions may be exercised.
11.4.2 The alarm system should meet appropriate constructional and operational requirements for required alarms.~
11.4.3 Equipment monitoring the passenger, cargo and machinery spaces for fire and flooding should, so far as is practicable, form an integrated sub-centre incorporating monitoring and activation controls for all emergency situations. This sub-centre may require feed-back instrumentation to indicate that actions initiated have been fully implemented.
11.5 Safety system
Where arrangements are fitted for overriding any automatic shutdown system for the main propulsion machinery in accordance ~ith 9.2.2, they should be such as to preclude inadvertent operation. When a shutdown system is activated, an audible and visual alarm should be given at the control station and means should be provided to override the automatic shutdown except in cases where there is a risk of complete breakdown or explosion.
* Refer to the Code on alarms and indicators adopted by the Organization by resolution A.686(17).
W/1687n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)

---CHUNK---

SOURCE: MSC.36(63).pdf
risk of complete breakdown or explosion.
* Refer to the Code on alarms and indicators adopted by the Organization by resolution A.686(17).
W/1687n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY FOR HIGH SPEED CRAFT MSC 62/23/Add.2
ANNEX 18
Page 110
12.1
12.1.1
12.1. 2
12.1. 3
12.1. 4
12.1. 5
12.2.
12.2.1
CHAPTER 12 - ELECTRICAL INSTALLATIONS
PART A - GENERAL
General

Electrical insta11ations* should be such that:
.1 all electrical auxiliary services necessary for maintaining the craft in normal operation and habitable conditions will be ensured without recourse to the emergency source of electrical power;
.2 electrical services essential for safety will be ensured under various emergency conditions; and
. 3 the safety of passengers, crew and craft from electrical hazards will be ensured.
The FMEA should include the electrical system, taking into account the effects of electrical failure on the systems being supplied. In cases where faults can occur without being detected during routine checks on the installations, the analysis should take into account

---CHUNK---

SOURCE: MSC.36(63).pdf
the effects of electrical failure on the systems being supplied. In cases where faults can occur without being detected during routine checks on the installations, the analysis should take into account the possibility of faults occurring simultaneously or consecutively. The electrical system should be designed and installed so that the probability of the craft being at risk of failure of a service is