.3 the generator sets referred to in .1 and their self-contained systems are installed such that one of them remains operable after damage or flooding in anyone compartment.

For category A craft, the emergency source of power should be capable of supplying simultaneously the following services:

.1 for a period of 5 h emergency lighting:

.1.1 at the stowage positions of life-saving appliances;

.1.2 at all escape routes such as alleyways, stairways, exits from accommodation and service spaces, embarkation points, etc;

.1. 3 in the public spaces;

.1.4 in the machinery spaces and main emergency generating spaces including their control positions;

. 1. 5 in control stations;

W/1687n/pp/EWP

RESOLUTION MSC.36(63)

(adopted on 20 May 1994)

ADOPTION OF THE INTERNATIONAL CODE OF SAFETY

---CHUNK---

SOURCE: MSC.36(63).pdf

in the machinery spaces and main emergency generating spaces including their control positions;
in control stations;
W/1687n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT MSC 62/23/Add.2

ANNEX 18

Page 120

12.7.4

.1.6 at the stowage positions for firemen's outfits; and

.1.7 at the steering gear;

.2 for a period of 5 h:

.2.1 main navigation lights, except for "not under command" lights;

.2.2 electrical internal communication equipment for announcements for passengers and crew required during evacuation;

.2.3 fire detection and general alarm system and manual fire alarms; and

.2.4 remote control devices of fire-extinguishing systems, if electrical;

.3 for a period of 4 h of intermittent operation:

.3.1 the daylight signalling lamps, if they have no independent supply from their own accumulator battery; and

.3.2 the craft's whistle, if electrically driven;

.4 for a period of 5 h:
.4.1 craft radio facilities and other loads as set out
in 14.12.2; and
.4.2 essential electrically powered instruments and controls
for propulsion machinery, if alternate sources of power

---CHUNK---

SOURCE: MSC.36(63).pdf
.4 for a period of 5 h:
.4.1 craft radio facilities and other loads as set out
in 14.12.2; and
.4.2 essential electrically powered instruments and controls
for propulsion machinery, if alternate sources of power
are not available for such devices;
.5 for a period of 12 h, the "not under command" lights; and
.6 for a period of 10 min:
.6.1 power drives for directional control devices including
those required to direct thrust forward and astern,
unless there is a manual alternative acceptable to the
Administration as complying with 5.2.3.
For category B craft, the electrical power available should be
sufficient to supply all those services that are essential for
safety in an emergency, due regard being paid to such services as
may have to be operated simultaneously. The emergency source of
electrical power should be capable, having regard to starting
currents and the transitory nature of certain loads, of supplying
simultaneously at least the following services for the periods
specified hereinafter, if they depend upon an electrical source for
their operation
. 1 for a period of 12 h, emergency lighting:

---CHUNK---

SOURCE: MSC.36(63).pdf
simultaneously at least the following services for the periods
specified hereinafter, if they depend upon an electrical source for
their operation
. 1 for a period of 12 h, emergency lighting:
.1.1 at the stowage positions of life-saving appliances;
W/1687n/pp/EWP
(
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT .1.2
MSC 62123/Add.2
ANNEX 18
Page 121
at all escape routes, such as alley ways, stairways,
exits from accommodation and service spaces, embarkation
points, etc;
.1.3 in the passenger compartments;
.1.4 in the machinery spaces and main emergency generating

spaces including their control positions;
.1.5 in control stations;
.1.6 at the stowage positions for firemen's outfits; and
.1.7 at the steering gear .
2 for a period of 12 h:
.2.1 the navigation lights and other lights required by the International Regulations for Preventing Collisions at Sea in force;
.2.2
.2.3
.2.4
electrical internal communication equipment for announcements for passengers and crew required during evacuation;
fire detection and general alarm system and manual fire alarms; and

---CHUNK---

SOURCE: MSC.36(63).pdf
Sea in force;
.2.2
.2.3
.2.4
electrical internal communication equipment for announcements for passengers and crew required during evacuation;
fire detection and general alarm system and manual fire alarms; and
remote control devices of fire-extinguishing systems, if electrical;
.3 for a period of 4 h on intermittent operation:
.3.1 the daylight signalling lamps, if they have no independent supply from their own accumulator battery; and
.3.2 the craft's whistle, if electrically driven;
.4 for a period of 12 h:
.4.1 the navigational equipment as required by chapter 13. Where such provision is unreasonable or impracticable, the Administration may waive this requirement for craft of less than 5,000 tons gross tonnage;
.4.2 essential electrically powered instruments and controls for propulsion machinery, if alternate sources of power not available for such devices;
.4.3 one of the fire pumps required by 7.7.8.1;
.4.4 the sprinkler pump and drencher pump, if fitted;
.4.5 the emergency bilge pump and all the equipment essential for the operation of electrically powered remote controlled bilge valves as required by chapter 10; and
W/1687n/pp/EWP

---CHUNK---

SOURCE: MSC.36(63).pdf

.4.4 the sprinkler pump and drencher pump, if fitted;
.4.5 the emergency bilge pump and all the equipment essential for the operation of electrically powered remote controlled bilge valves as required by chapter 10; and
W/1687n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY FOR HIGH SPEED CRAFT MSC 62123/Add.2
ANNEX 18
Page 122
12.7.5
12.7.6
12.7.7
.4.6 craft radio facilities and other loads as set out in 14.12.2;
.5 for a period of 30 min, any watertight doors, required by chapter 2 to be power operated, together with their indicators and warning signals;
.6 for a period of 10 min, power drives for directional control devices including those required to direct thrust forward and astern, unless there is a manual alternative acceptable to the Administration as complying with 5.2.3.