systems are installed in accordance with 12.3.2.
12.8.2.2 The electrical power available should be sufficient to supply all those services that are essential for safety in an emergency, due regard being paid to such services as may have to be operated simultaneously. The emergency source of electrical power should be capable, having regard to starting currents and the transitory nature of certain loads, of supplying simultaneously at least the following services for the periods specified hereinafter, if they depend upon an electrical source for their operation:
.1 for a period of 12 h, emergency lighting:
.1.1 at the stowage positions of life-saving appliances;
.1.2 at all escape routes such as alleyways, stairways, exits

---CHUNK---

SOURCE: MSC.36(63).pdf
depend upon an electrical source for their operation:
.1 for a period of 12 h, emergency lighting:
.1.1 at the stowage positions of life-saving appliances;
.1.2 at all escape routes such as alleyways, stairways, exits from accommodation and service spaces, embarkation points, etc.;
.1.3 in the public spaces, if any;
.1.4 in the machinery spaces and main emergency generating spaces including their control positions;
.1.5 in control stations;
.1.6 at the stowage positions for fireman's outfits; and
.1.7 at the steering gear;
.2 for a period of 12 h:
.2.1 the navigation lights and other lights required by the International Regulations for Preventing Collisions at Sea in force;
W/1687n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY FOR HIGH SPEED CRAFT .2.2
.2.3
.2.4
MSC 62123/Add.2
ANNEX 18
Page 125
electrical internal communication equipment for announcements during evacuation;
fire detection and general alarm system and manual fire alarms; and
remote control devices of fire-extinguishing systems, if electrical;
.3 for a period of 4 h of intermittent operation:

---CHUNK---

SOURCE: MSC.36(63).pdf
announcements during evacuation;

fire detection and general alarm system and manual fire
alarms; and
remote control devices of fire-extinguishing systems, if
electrical;
.3 for a period of 4 h of intermittent operation:
.3.1 the daylight signalling lamps, if they have no
independent supply from their own accumulator battery;
and
.3.2 the craft's whistle, if electrically driven;
.4 for a period of 12 h:
.4.1 the navigational equipment as required by chapter 13.
Where such provision is unreasonable or impracticable,
the Administration may waive this requirement for craft
of less than 5,000 tons gross tonnage;
.4.2 essential electrically powered instruments and controls
for propulsion machinery, if alternate sources of power
are not available for such devices;
.4.3 one of the fire pumps required by 7.7.8.1;
.4.4 the sprinkler pump and drencher pump, if fitted;
.4.5 the emergency bilge pump and all the equipment essential
for the operation of electrically powered remote
controlled bilge valves as required by chapter 10; and
.4.6 craft radio facilities and other loads as set out
in 14.12.2;
.5 for a period of 10 min, power drives for directional control

---CHUNK---

SOURCE: MSC.36(63).pdf
for the operation of electrically powered remote
controlled bilge valves as required by chapter 10; and
.4.6 craft radio facilities and other loads as set out
in 14.12.2;
.5 for a period of 10 min, power drives for directional control
devices including those required to direct thrust forward and
astern, unless there is a manual alternative acceptable to the
Administration as complying with 5.2.3.
12.8.2.3 Provision should be made for the periodic testing of the complete
emergency system including the emergency consumers required by
12.8.2.2 and should include the testing of automatic starting
arrangements.
12.8.2.4 Where the emergency source of electrical power is a generator, a
transitional source of emergency electrical power should be provided
according to 12.8.3, unless the automatic starting system and the
characteristics of the prime mover are such as to permit the
emergency generator to carry its full rated load as quickly as is
safe and practicable, subject to a maximum of 45 s.
W/1687n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT MSC 62/23/Add.2
ANNEX 18

---CHUNK---

SOURCE: MSC.36(63).pdf
safe and practicable, subject to a maximum of 45 s.
W/1687n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT MSC 62/23/Add.2
ANNEX 18
Page 126
12.8.3 Transitional source of emergency electrical power
The transitional source of emergency electrical power required by paragraph 12.8.2.4 may consist of an accumulator battery suitably located for use in an emergency which should operate without recharging while maintaining the voltage of the battery throughout the discharge period within 12% above or below its nominal voltage and be of sufficient capacity and so arranged as to supply automatically, in the event of failure of either the main or emergency source of electrical power, at least the following services, if they depend upon an electrical source for their operation:
.1 for a period of 30 min, the load specified in 12.8.2.2.1, .2 and .3; and
.2 with respect to the watertight doors:
.2.1 power to operate the watertight doors, but not necessarily simultaneously, unless an independent temporary source of stored energy is provided. The

---CHUNK---

SOURCE: MSC.36(63).pdf
and .3; and
.2 with respect to the watertight doors:
.2.1 power to operate the watertight doors, but not necessarily simultaneously, unless an independent temporary source of stored energy is provided. The power source should have sufficient capacity to operate each door at least three times, i.e closed - open - closed against an adverse list of 15°; and
.2.2 power to the control, indication and alarm circuits for the watertight doors for half an hour.
WI1687n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT l3 .1
l3.1.l
13.1. 2
13.2
13.2.1
l3.2.2
13.2.3

13.2.4
13.2.5
13.2.6
l3.3
13.3.1
13.3.2
CHAPTER 13 - NAVIGATIONAL EQUIPMENT
Nav igatio n (gener a l)
MSC 62123/Add.2
ANNEX 18
Page 127
This chapter only covers items of navigational equipment which relate to the navigation of the craft as distinct from the safe functioning of the craft. The following paragraphs represent the minimum requirements for normal safe navigation unless it is demonstrated to the Administration that an equivalent level of safety is achieved by other means.

---CHUNK---

SOURCE: MSC.36(63).pdf
functioning of the craft. The following paragraphs represent
the minimum requirements for normal safe navigation unless it is