demonstrated to the Administration that an equivalent level of safety is achieved by other means.
The navigational equipment and its installation should be to the satisfaction of the Administration.
Compasses
Craft should be provided with a magnetic compass which is capable of operating without electrical supply, and which may be used for steering purposes. This compass should be mounted in a suitable binnacle containing the required correcting devices and should be suitable for the speed and motion characteristics of the craft.
The compass card or repeater should be capable of being easily read from the position at which the craft is normally controlled.
Each magnetic compass should be properly adjusted and its table or curve of residual deviations should be available at all times.
Care should be taken in siting a magnetic compass or magnetic sensing element so that magnetic interference is eliminated or minimized so far as is practicable.
Passenger craft certified to carry 100 passengers or less should, in

---CHUNK---

SOURCE: MSC.36(63).pdf
Care should be taken in siting a magnetic compass or magnetic sensing element so that magnetic interference is eliminated or minimized so far as is practicable.
Passenger craft certified to carry 100 passengers or less should, in addition to the compass required by 13.2.1, be provided with an instrument, suitable for the speed and motion characteristics and area of operation of the craft, providing a heading reference of accuracy superior to that provided by a magnetic compass.
Cargo craft and passenger craft certified to carry more than 100 passengers should, in addition to the compass required in 13.2.1, be provided with a gyro-compass which should be suitable for the speed and motion characteristics and area of operation of the craft.
~d and d istance measurement
Craft should be provided with a device to measure speed and distance, except when no device is available which will function reliably at all speeds at which the craft may operate.
Speed and distance measuring devices on craft fitted with automatic radar plotting aid should be capable of measuring speed and distance through the water.
WI1687n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)

---CHUNK---

SOURCE: MSC.36(63).pdf
Speed and distance measuring devices on craft fitted with automatic radar plotting aid should be capable of measuring speed and distance through the water.
WI1687n/pp/EWP
RESOLUTION MSC.36(63)

13.4
13.4.1
13.5
13.5.1
13.5.2
13.5.3
13.5.4
13.5.5
13.5.6
13.6
13.7
13.7.1
13.7.2
13.8
13.8.1
Echo - sounding dey~~
Non-amphibious craft should be fitted with an eCho-sounding device which will give an indication of depth of water to a sufficient degree of accuracy for use when the craft is in the displacement mode.
Radar installations
Craft should be provided with at least one azimuth-stabilized radar operating in the X-band (3 em).
Craft of 500 tons gross tonnage and upwards or craft certified to carry more than 450 passengers should be provided with at least two radar installations. A second radar may also be provided in craft of less than 500 tons gross tonnage or certified to carry 450 passengers or less where environmental conditions so require.
At least one radar should be equipped with facilities for plotting

---CHUNK---

SOURCE: MSC.36(63).pdf
craft of less than 500 tons gross tonnage or certified to carry 450 passengers or less where environmental conditions so require.
At least one radar should be equipped with facilities for plotting which are at least as effective as a reflector plotter.
Adequate communication facilities should be provided between the radar observer and the person in immediate charge of the craft.
Each radar installation provided should be suitable for the intended craft speed, motion characteristics and commonly encountered environmental conditions.
Each radar installation should be mounted so as to be as free as practicable from vibration.
Electronic positioning systems
Where the area of operation of a high speed craft is covered by a reliable electronic position-fixing system, the craft should be provided with the means to fix its position using such system.
Rate - of - turn indicator and rudder angle indicator

A rate-of-turn indicator should be provided unless the Administration determines otherwise. Means should be provided to warn the operator if an operationally dictated maximum rate of turn is being reached.
Craft should be provided with an indicator showing the rudder

---CHUNK---

SOURCE: MSC.36(63).pdf
Administration determines otherwise. Means should be provided to warn the operator if an operationally dictated maximum rate of turn is being reached.
Craft should be provided with an indicator showing the rudder angle. In craft without a rudder, the indicator should show the direction of steering thrust.
Other navigational aids
The information provided by navigational systems should be so displayed that the probability of misreading is reduced to a minimum and should be capable of giving readings to an optimum accuracy.
W/1687n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY FOR HIGH SPEED CRAFT 13.9
13.9.1
13.9.2
13.10
13.11
13.11.1
13.11.2
13.11. 3
13.12
13.12.1
13.12.2
13 .12.3
13.13
13.13.1
13.13.2
Searchlight
MSC 62123/Add.2
ANNEX 18
Page 129
Craft should be equipped with at least one adequate searchlight which should be controllable from the operating station.
One portable signalling lamp capable of operating independently of the craft's main electrical supply should be provided and maintained ready for use in the operating compartment at all times.
ltight vision eguipment

---CHUNK---

SOURCE: MSC.36(63).pdf
One portable signalling lamp capable of operating independently of the craft's main electrical supply should be provided and maintained

ready for use in the operating compartment at all times.

ltight vision eguipment

When operational conditions justify the provision of night vision enhancement equipment, such equipment should be fitted.

Steering arrangement and propulsion indicators

The steering arrangement should be so designed that the craft turns in the same direction as that of the wheel, tiller, joy stick or control lever.

Craft should be provided with indicators showing the mode of the propulsion system(s).

Craft with emergency steering positions should be provided with arrangements for supplying visual compass readings to the emergency steering position.

Automatic steering aid (automatic pilot eguipment)

Craft should, where possible, be equipped with automatic pilot equipment.

The alarm signalling facilities prescribed in paragraphs 3.1 and 3.2 of the Recommendation on performance standards for automatic pilots, adopted by the Organization by resolution A.342(IX), may be omitted.

Provision should be made to change from the automatic to manual mode

---CHUNK---