.6.4 capable of floating free if the craft sinks and of being
automatically activated when afloat; and
.6.5 capable of being activated manually.
* Refer to resolution A.70l(17) concerning carriage of INMARSAT enhanced
group call SafetyNET receivers under the GMDSS, adopted by the
Organization.
** Refer to the Recommendation on promulgation of maritime safety
information, adopted by the Organization by resolution A.705(17).
*** Refer to resolution A.616(15) concerning search and rescue homing
capability, adopted by the Organization.
**** Subject to the availability of appropriate receiving and processing

---CHUNK---

SOURCE: MSC.36(63).pdf
*** Refer to resolution A.616(15) concerning search and rescue homing
capability, adopted by the Organization.
**** Subject to the availability of appropriate receiving and processing
ground facilities for each ocean region covered by INMARSAT satellites.
W/1687n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT 14.6.2
14.6.3
14.6.4
14.7
14.7.1
MSC 62/23/Add.2
ANNEX 18
Page 135
Until 1 February 1999, or until such other date as may be determined
by the Maritime Safety Committee, every craft should, in addition ,
be fitted with a radio installation consisting of a radiotelephone
distress frequency watch receiver capable of operating on 2,182 kHz.
Until 1 February 1999, every craft should, unless the craft is
engaged on voyages in sea area Al only, be fitted with a device for
generating the radiotelephone alarm signal on the frequency
2,182 kHz*.
The Administration may exempt craft constructed on or after
1 February 1997 from the requirements prescribed by 14.6.2 and
14.6.3.
Radi o equ ipment : Sea area A1
In addition to meeting the requirements of 14.6, every craft engaged

---CHUNK---

SOURCE: MSC.36(63).pdf
2,182 kHz*.
The Administration may exempt craft constructed on or after
1 February 1997 from the requirements prescribed by 14.6.2 and
14.6.3.
Radi o equ ipment : Sea area A1
In addition to meeting the requirements of 14.6, every craft engaged

on voyages exclusively in sea area Al should be provided with a radio installation capable of initiating the transmission of ship-to-shore distress alerts from the position from which the craft is normally navigated, operating either:
.1 on VHF using DSC; this requirement may be fulfilled by the EPIRB prescribed by 14.7.3, either by installing the EPIRB close to, or by remote activation from, the position from which the craft is normally navigated; or
. 2 through the polar orbiting satellite service on 406 MHz; this requirement may be fulfilled by the satellite EPIRB, required by 14.6.1.6, either by installing the satellite EPIRB close to, or by remote activation from the position from which the craft is normally navigated; or
. 3 if the craft on voyages within coverage of MF coast stations equipped with DSC, on MF using DSC; or
.4 on HF using DSC; or
.5 through the INMARSAT geostationary satellite service; this

---CHUNK---

SOURCE: MSC.36(63).pdf
craft is normally navigated; or
. 3 if the craft on voyages within coverage of MF coast stations equipped with DSC, on MF using DSC; or
.4 on HF using DSC; or
.5 through the INMARSAT geostationary satellite service; this requirement may be fulfilled by:
.5.1 an INMARSAT ship earth station**; or
* Refer to resolution A.421(XI) concerning operational standards for radiotelephone alarm signal generators, adopted by the Organization.
** This requirement can be met by INMARSAT ship earth stations capable of two-way communications, such as Standard-A and B (resolution A.698(17» or Standard-C (resolution A.663(16» ship earth stations. Unless otherwise specified, this footnote applies to all requirements for an INMARSAT ship earth station prescribed by this chapter.
W/16B7n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT MSC 62/23/Add.2
ANNEX lB
Page 136
14.7.2
14.7.3
14. B
l4.B.l
.5.2 ,the satellite EPIRB, required by 14.6.1.6, either by installing the satellite EPIRB close to, or by remote activation from, the position from which the craft is normally navigated.

---CHUNK---

SOURCE: MSC.36(63).pdf

14.7.2
14.7.3
14. B
l4.B.l
.5.2 ,the satellite EPIRB, required by 14.6.1.6, either by installing the satellite EPIRB close to, or by remote activation from, the position from which the craft is normally navigated.
The VHF radio installation, required by 14.6.1.1, should also be capable of transmitting and receiving general radiocommunications using radiotelephony.
Craft engaged on voyages exclusively in sea area Al may carry, in lieu of the satellite EPIRB required by 14.6.1.6, an EPIRB which should be:
.1 capable of transmitting a distress alert using DSC on VHF channel 70 and providing for locating by means of a radar transponder operating in the 9 GHz band;
.2 installed in an easily accessible position;
.3 ready to be manually released and capable of being carried by one person into a survival craft;
.4 capable of floating free if the craft sinks and of being automatically activated when afloat; and
.5 capable of being activated manually.
Radio egui!?ment - Sea areas Al and A2
In addition to meeting the requirements of 14.6, every craft engaged on voyages beyond sea area AI, but remaining within sea area A2,

---CHUNK---

SOURCE: MSC.36(63).pdf
.5 capable of being activated manually.
Radio egui!?ment - Sea areas Al and A2
In addition to meeting the requirements of 14.6, every craft engaged on voyages beyond sea area AI, but remaining within sea area A2,
should be provided with:
.1 an MF radio installation capable of transmitting and receiving, for distress and safety purposes, on the frequencies:
.1.1 2,187.5 kHz using DSC; and
.1.2 2,182 kHz using radiotelephony;
.2 a radio installation capable of maintaining a continuous DSC watch on the frequency 2,187.5 kHz which may be separate from, or combined with, that required by 14.8.1.1.1; and
.3 means of initiating the transmission of ship-to-shore distress alerts by a radio service other than MF operating either:
.3.1 through the polar orbiting satellite service on 406 MHz; this requirement may be fulfilled by the satellite EPIRB, required by 14.6.1.6, either by installing the satellite EPIRB close to, or by remote activation from, the position from which the craft is normally navigated;
or

RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT 14.8.2
14.8.3
14.8.4
14.9

---CHUNK---

SOURCE: MSC.36(63).pdf
the position from which the craft is normally navigated;
or
W/1687n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT 14.8.2
14.8.3
14.8.4
14.9
14.9.1
.3.2