.3.3
.3.3.1
.3.3.2
on HF using DSC; or

through the INMARSAT geostationary satellite service;
this requirement may be fulfilled by:
the equipment specified in 14.8.3.2; or
the satellite EPIRB, required by 14.6.1.6, either
by installing the satellite EPIRB close to, or by remote
activation from, the position from which the craft is
normally navigated.
It should be possible to initiate transmission of distress alerts by
the radio installations specified in 14.8.1.1 and 14.8.1.3 from the
position from which the craft is normally navigated.
The craft should, in addition, be capable of transmitting and
receiving general radiocommunications using radiotelephony or
direct-printing telegraphy by either:
.1 a radio installation operating on working frequencies in the
bands between 1,605 kHz and 4,000 kHz or between 4,000 kHz and
27,500 kHz. This requirement may be fulfilled by the addition

---CHUNK---

SOURCE: MSC.36(63).pdf
direct-printing telegraphy by either:
.1 a radio installation operating on working frequencies in the
bands between 1,605 kHz and 4,000 kHz or between 4,000 kHz and
27,500 kHz. This requirement may be fulfilled by the addition
of this capability in the equipment required by 14.8.1.1; or
.2 an INMARSAT ship earth station.
The Administration may exempt crafts constructed before
1 February 1997, which are engaged exclusively on voyages within
sea area A2, from the requirements of 14.6.1.1.1 and 14.6.1.2
provided such crafts maintain, when practicable, a continuous
listening watch on VHF channel 16. This watch should be kept at the
position from which the craft is normally navigated. Such exemption
should be endorsed by the base port State in the Permit to Operate.
Radio equipment: Sea areas AI. A2 and A3
In addition to meeting the requirements of 14.6, every craft engaged
on voyages beyond sea areas Al and A2, but remaining within sea
area A3" should, if it does not comply with the requirements of
14.9.2, be provided with:
.1 an INMARSAT ship earth station capable of:
.1.1 transmitting and receiving distress and safety

---CHUNK---

SOURCE: MSC.36(63).pdf
area A3" should, if it does not comply with the requirements of
14.9.2, be provided with:
.1 an INMARSAT ship earth station capable of:

.1.1 transmitting and receiving distress and safety
communications using direct-printing telegraphy;
.1.2 initiating and receiving distress priority calls;
.1.3 maintaining watch fOl' shore-to-ship distress alerts,
including those directed to specifically defined
geographical areas;
.1.4 transmitting and receiving general radiocommunications,
using either radiotelephony or direct-printing
telegraphy; and
W/1687n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT MSC 62/23/Add.2
ANNEX 18
Page 138
14.9.2
.2 an MF radio installation capable of transmitting and
receiving, for distress and safety purposes, on the
frequencies:
.2.1 2,187.5 kHz using DSC; and
.2.2 2,182 kHz using radiotelephony; and
.3 a radio installation capable of maintaining a continuous DSC
watch on the frequency 2,187.5 kHz which may be separate from
or combined with that required by 14.9.1.2.1; and
.4 means of initiating the transmission of ship-to-shore distress

---CHUNK---

SOURCE: MSC.36(63).pdf
.3 a radio installation capable of maintaining a continuous DSC
watch on the frequency 2,187.5 kHz which may be separate from
or combined with that required by 14.9.1.2.1; and
.4 means of initiating the transmission of ship-to-shore distress
alerts by a radio service operating either:
.4.1 through the polar orbiting service on 406 MHz; this
requirement may be fulfilled by the satellite EPIRB,
required by 14.6.1.6, either by installing the satellite
EPIRB close to, or by remote activation from, the
position from which the craft is normally navigated; or
.4.2 on. HF using DSC; or
.4.3 through the INMARSAT geostationary satellite service,
by an additional ship earth station or by the satellite
EPIRB required by 14.6.1.6, either by installing the
satellite EPIRB close to, or by remote activation from,
the position from which the craft is normally navigated;
In addition to meeting the requirements of 14.6, every craft engaged
on voyages beyond sea areas Al and A2, but remaining within sea
area A3, should, if it does not comply with the requirements of
14.9.1, be provided with:
.1 an MF/HF radio installation capable of transmitting and

---CHUNK---

SOURCE: MSC.36(63).pdf
on voyages beyond sea areas Al and A2, but remaining within sea area A3, should, if it does not comply with the requirements of 14.9.1, be provided with:
.1 an MF/HF radio installation capable of transmitting and receiving, for distress and safety purposes, on all distress and safety frequencies in the bands between 1,605 kHz and 4,000 kHz and between 4,000 kHz and 27,500 kHz:
.1.1 using DSC;
.1.2 using radiotelephony; and
.1.3 using direct-printing telegraphy; and
.2 equipment capable of maintaining DSC watch on 2,187.5 kHz, 8,414.5 kHz and on at least one of the distress and safety DSC frequencies 4,207.5 kHz, 6,312 kHz, 12,577 kHz or 16,804.5 kHz; at any time, it should be possible to select any of these DSC distress and safety frequencies. This equipment may be separate from, or combined with, the equipment required by 14.9.2.1; and
.3 means of initiating the transmission of ship-to-shore distress alerts by a radiocommunication service other than HF operating either:
W/1687n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT 14.9.3
14.9.4
14.10
14.10.1
14.10.2
.3.1
.3.2

---CHUNK---

SOURCE: MSC.36(63).pdf
either:
W/1687n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT 14.9.3
14.9.4
14.10
14.10.1
14.10.2
.3.1
.3.2
MSC 62/23/Add.2
ANNEX 18
Page 139
through the polar orbiting satellite service on 406 MHz; this requirement may be fulfilled by the satellite EPIRB, required by 14.6.1.6, either by installing the

satellite EPIRB close to, or by remote activation from,
the position from which the craft is normally navigated;
or
through the INMARSAT geostationary satellite service;
this requirement may be fulfilled by:
.3.2.1 an INMARSAT ship earth station; or
.3.2.2 the satellite EPIRB, required by 14.6.1.6, either
by installing the satellite EPIRB close to, or by remote
activation from, the position from which the craft is
normally navigated; and
.4 in addition, the craft should be capable of transmitting and
receiving general radiocommunications using radiotelephony
or direct-printing telegraphy by an MF/HF radio installation
operating on working frequencies in the bands between
1,605 kHz and 4,000 kHz and between 4,000 kHz and 27,500 kHz.

---CHUNK---

SOURCE: MSC.36(63).pdf
receiving general radiocommunications using radiotelephony
or direct-printing telegraphy by an MF/HF radio installation
operating on working frequencies in the bands between
1,605 kHz and 4,000 kHz and between 4,000 kHz and 27,500 kHz.