This requirement may be fulfilled by the addition of this capability in the equipment required by 14.9.2.1.
It should be possible to initiate transmission of distress alerts by the radio installations specified in 14.9.1.1, 14.9.1.2, 14.9.1.4, 14.9.2.1 and 14.9.2.3 from the position from which the craft is normally navigated.
The Administration, in conjunction with the base port State, may exempt crafts constructed before 1 February 1997 and engaged exclusively on voyages within sea areas A2 and A3, from the requirements of 14.6.1.1.1 and 14.6.1.2 provided such crafts maintain, when practicable, a continuous listening watch on VHF channel 16. This watch should be kept at the position from which the craft is normally navigated.
Radio equipment: Sea areas AI, A2, A3 and A4
In addition to meeting the requirements of 14.6, craft engaged on voyages in all sea areas should be provided with the radio

---CHUNK---

SOURCE: MSC.36(63).pdf
the craft is normally navigated.
Radio equipment: Sea areas AI, A2, A3 and A4
In addition to meeting the requirements of 14.6, craft engaged on voyages in all sea areas should be provided with the radio installations and equipment required by 14.9.2, except that the equipment required by 14.9.2.3.2 should not be accepted as an alternative to that required by 14.9.2.3.1, which should always be provided. In addition, craft engaged on voyages in all sea areas should comply with the requirements of 14.9.3.
The Administration, in conjunction with the base port State, may exempt crafts constructed before 1 February 1997, and engaged exclusively on voyages within sea areas A2, A3 and A4, from the requirements of 14.6.1.1.1 and 14.6.1.2 provided such crafts maintain, when practicable, a continuous listening watch on VHF channel 16. This watch should be kept at the position from which the craft is normally navigated.
W/1687n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT MSC 62123/Add.2
ANNEX 18
Page 140
14.11
14.11.1
14.11.2
14.11.3
14.11.4
14.12
14.12.1
14.12.2
Watches

---CHUNK---

14.11
14.11.1
14.11.2
14.11.3
14.11.4
14.12
14.12.1
14.12.2
Watches
Every craft, while at sea, should maintain a continuous watch:
.1 on VHF DSC channel 70, if the craft, in accordance with the requirements of 14.6.1.2, is fitted with a VHF radio installation;
.2 on the distress and safety DSC frequency 2,187.5 kHz, if the craft, in accordance with the requirements of 14.8.1.2 or 14.9.1.3, is fitted with an MF radio installation:
.3 on the distress and safety DSC frequencies 2,187.5 kHz and 8,414.5 kHz and also on at least one of the distress and safety DSC frequencies 4,207.5 kHz, 6,312 kHz, 12,577 kHz or 16,804.5 kHz, appropriate to the time of day and the geographical position of the craft, if the craft, in accordance with the requirements of 14.9.2.2 or 14.10.1, is fitted with an MF/HF radio installation. This watch may be kept by means of a scanning receiver;
.4 for satellite shore-to-ship distress alerts, if the craft, in accordance with the requirements of 14.9.1.1, is fitted with

---CHUNK---

SOURCE: MSC.36(63).pdf
fitted with an MF/HF radio installation. This watch may be kept by means of a scanning receiver;
.4 for satellite shore-to-ship distress alerts, if the craft, in accordance with the requirements of 14.9.1.1, is fitted with an INMARSAT ship earth station.
Every craft, while at sea, should maintain a radio watch for broadcasts of maritime safety information on the appropriate frequency or frequencies on which such information is broadcast for the area in which the craft is navigating.
Until 1 February 1999 or until such other date as may be determined by the Maritime Safety Committee, every craft while at sea should maintain, when practicable, a continuous listening watch on VHF channel 16. This watch should be kept at the position from which the craft is normally navigated.
Until 1 February 1999 or until such other date as may be

determined by the Maritime Safety Committee, every craft required to carry a radiotelephone watch receiver should maintain, while at sea, a continuous watch on the radiotelephone distress frequency 2,182 kHz. This watch should be kept at the position from which the craft is normally navigated.
Sources of energy

---CHUNK---

SOURCE: MSC.36(63).pdf
sea, a continuous watch on the radiotelephone distress frequency 2,182 kHz. This watch should be kept at the position from which the craft is normally navigated.
Sources of energy
There should be available at all times, while the craft is at sea, a supply of electrical energy sufficient to operate the radio installations and to charge any batteries used as part of a reserve source of energy for the radio installations.
Reserve and emergency sources of energy should be provided on every craft to supply radio installations, for the purpose of conducting distress and safety radiocommunications, in the event of failure of the craft's main and emergency sources of electrical power. The reserve source of energy should be capable of simultaneously operating the VHF radio installation required by 14.6.1.1 and, as
W/1687n/pp/EWP
(
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT 14.12.3
14.12.4
14.12.5
14.12.6
14.12.7
MSC 62/23/Add.2
ANNEX 18
Page 141
appropriate for the sea area or sea areas for which the craft is equipped, either the MF radio installation required by 14.8.1.1, the

---CHUNK---

SOURCE: MSC.36(63).pdf
FOR HIGH SPEED CRAFT 14.12.3
14.12.4
14.12.5
14.12.6
14.12.7
MSC 62/23/Add.2
ANNEX 18
Page 141
appropriate for the sea area or sea areas for which the craft is equipped, either the MF radio installation required by 14.8.1.1, the
MF/HF radio installation required by 14.9.2.1 or 14.10.1 or the

INMARSAT ship earth station required by 14.9.1.1 and any of the additional loads mentioned in 14.12.5 and 14.12.8 for a period of at least 1 h.

The reserve source of energy should be independent of the propelling power of the craft and the craft's electrical system.

Where, in addition to the VHF radio installation, two or more of the other radio installations, referred to in 14.12.2, can be connected to the reserve source of energy, they should be capable of simultaneously supplying, for the period specified in 14.12.2, the VHF radio installation and:

.1 all other radio installations which can be connected to the reserve source of energy at the same time; or

.2 whichever of the radio installations will consume the most power, if only one of the other radio installations can be connected to the reserve source of energy at the same time as the VHF radio installation.

---CHUNK---

SOURCE: MSC.36(63).pdf

.2 whichever of the radio installations will consume the most power, if only one of the other radio installations can be connected to the reserve source of energy at the same time as