work. There should be facilities for lighting the chart. Chart table lighting should be screened.
Lighting

---CHUNK---

SOURCE: MSC.36(63).pdf
If considered necessary by the Administration, the operating compartment should be provided with a suitable table for chart work. There should be facilities for lighting the chart. Chart table lighting should be screened.
Lighting
A satisfactory level of lighting should be available to enable the operating personnel to adequately perform all their tasks both at sea and in port, by day and night. There should be only a limited reduction in the illumination of essential instruments and controls under likely system fault conditions.
Care should be taken to avoid glare and stray image reflection in the operating area environment. High contrast in brightness between work area and surroundings should be avoided. Non-reflective or matt surfaces should be used to reduce indirect glare to a minimum.
A satisfactory degree of flexibility within the lighting system should be available to enable the operating personnel to adjust the lighting intensity and direction as required in the different areas of the operating compartment and at individual instruments and controls.
Red light should be used to maintain dark adaptation whenever

---CHUNK---

SOURCE: MSC.36(63).pdf
lighting intensity and direction as required in the different areas of the operating compartment and at individual instruments and controls.
Red light should be used to maintain dark adaptation whenever possible in areas or on items of equipment requiring illumination in the operational mode, other than chart table.
During hours of darkness, it should be possible to discern displayed information and control devices.
Reference is made to additional requirements on lighting in 12.7 and 12.8.
Windows
Divisions between windows, located in the front, on the sides and in the doors, should be kept to a minimum. No division should be installed immediately forward of the operating stations.
Administrations should be satisfied that a clear view through the operating compartment windows is provided at all times regardless of weather conditions. The means provided for maintaining the windows in a clear condition should be so arranged that no reasonably probable single failure can result in a reduction of the cleared field of vision such as to interfere seriously with the ability of the operating crew to continue the operation and bring the craft to rest.
W/1687n/pp/EWP

---CHUNK---

SOURCE: MSC.36(63).pdf
probable single failure can result in a reduction of the cleared field of vision such as to interfere seriously with the ability of the operating crew to continue the operation and bring the craft to rest.
W/1687n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT MSC 62123/Add.2
ANNEX 18
Page 150
15.7.3
15.7.4
15.7.5
15.8
15.8.1
15.8.2
15.8.3
15.8.4
15.9
15.10
15.11
Arrangements should be provided so that the forward view from operating stations is not adversely affected by solar glare .
. Neither polarized nor tinted window glass should be fitted.
Operating compartment windows should be angled to reduce unwanted reflection.
The windows should be made of material which will not break into dangerous fragments if fractured.
Communication facilities
~uch means as are necessary should be provided to enable the crew to communicate between, and have access to, each other and with other occupants of the craft in both normal and emergency conditions.
Means to communicate between the operating compartment and spaces containing essential machinery, including any emergency steering

---CHUNK---

SOURCE: MSC.36(63).pdf
occupants of the craft in both normal and emergency conditions.
Means to communicate between the operating compartment and spaces containing essential machinery, including any emergency steering position, irrespective of whether the machinery is remotely or locally controlled, should be provided.
Means for making public address and safety announcements from control stations to all areas to which passengers and crew have access should be provided.
Provisions should be made for means to monitor, receive and transmit radio safety messages at the operating compartment.
Temperature and ventilation

The operating compartment should be equipped with adequate temperature and ventilation control systems.

Colours

The surface materials inside the operating compartment should have a suitable colour and finish to avoid reflections.

Safety measures

The operating area should be free of physical hazard to the operating personnel and have non-skid flooring in dry and wet conditions and adequate handrails. Doors should be fitted with devices to prevent them moving, whether they are open or closed.

WI1687n/pp/EWP
r

RESOLUTION MSC.36(63)
(adopted on 20 May 1994)

---CHUNK---

SOURCE: MSC.36(63).pdf

conditions and adequate handrails. Doors should be fitted with devices to prevent them moving, whether they are open or closed.
WI1687n/pp/EWP
r
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)

ADOPTION OF THE INTERNATIONAL CODE OF SAFETY FOR HIGH SPEED CRAFT 16.1

16.1.1

16.1. 2

16.1. 3

16.1. 4

16.1. 5

16.1. 6

16.2

16.2.1

CHAPTER 16 - STABILIZATION SYSTEMS

Definitions

MSC 621 2 3 I Add. 2
ANNEX 18
Page 151

"Stabilization control system" is a system intended to stabilize the main parameters of the craft's attitude: heel, trim, course and height and control the craft's motions; roll, pitch, yaw and heave. This term excludes devices not associated with the safe operation of the craft, e.g. motion reduction or ride control systems.

The main elements of a stabilization control system may include the following:

.1 devices such as rudders, foils, flaps, skirts, fans, water jets, tilting and steerable propellers, pumps for moving fluids;

.2 power drives actuating stabilization devices; and

.3 stabilization equipment for accumulating and processing data for making decisions and giving commands such as sensors, logic processors and automatic safety control.

---CHUNK---

SOURCE: MSC.36(63).pdf
fluids;
.2 power drives actuating stabilization devices; and
.3 stabilization equipment for accumulating and processing data for making decisions and giving commands such as sensors, logic processors and automatic safety control.
"Self-stabilization" of the craft is stabilization ensured solely by the craft's inherent characteristics.
"Forced stabilization" of the craft is stabilization achieved by:
.1 an automatic control system; or
.2 a manually control assisted system; or
.3 a combined system incorporating elements of both automatic and manually assisted control systems.
"Augmented stabilization" is a combination of self-stabilization and forced stabilization.
"Stabilization device" means a device as enumerated in 16.1.1.1 with the aid of which forces for controlling the craft's position are generated.
"Automatic safety control" is a logic unit for processing data and making decisions to put the craft into the displacement or other safe mode if a condition impairing safety arises.