General requiremen~
Stabilization systems should be so designed that in case of failure or malfunctioning of anyone of the stabilization devices, or

---CHUNK---

SOURCE: MSC.36(63).pdf
safe mode if a condition impairing safety arises.
General requiremen~
Stabilization systems should be so designed that in case of failure or malfunctioning of anyone of the stabilization devices, or equipment, it would be possible either to ensure maintaining the main parameters of craft's motion within safe limits with the aid of working stabilization devices or to put the craft into the displacement or other safe mode.
W/1687n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT MSC 62/23/Add.2
ANNEX 18
Page 152
16.2.2
16.2.3
16.2.4
16.2.5
16.2.6
16.3
16.3.1
16.3.2
16.4
16.4.1
16.4.2
In case of failure of any automatic equipment or stabilization device, or its power drive, the parameters of craft motion should
. remain within safe limits.
Craft fitted with an automatic stabilization system should be provided with an automatic safety control unless the redundancy in the system provides equivalent safety. Where an automatic safety control is fitted, provision should be made to override it and to cancel the override from the main operating station.

---CHUNK---

SOURCE: MSC.36(63).pdf
the system provides equivalent safety. Where an automatic safety control is fitted, provision should be made to override it and to cancel the override from the main operating station.
The parameters and the levels at which any automatic safety control gives the command to decrease speed and put the craft safely in the displacement or other safe mode should take account of the safe values of heel, trim, yaw and combination of trim and draught appropriate to the particular craft and service: also to the possible consequences of power failure for propulsion, lift or

stabilization devices.
The parameters and the degree of stabilization of the craft provided by the automatic stabilization system should be satisfactory having regard to the purpose and service conditions of the craft.
Failure mode and effect analysis should include the stabilization system.
Lateral and height control systems
Craft fitted with an automatic control system should be provided with an automatic safety control. Probable malfunctions should have only minor effects on automatic control system operation and should be capable of being readily counteracted by the operating crew.

---CHUNK---

SOURCE: MSC.36(63).pdf
with an automatic safety control. Probable malfunctions should have only minor effects on automatic control system operation and should be capable of being readily counteracted by the operating crew.
The parameters and levels at which any automatic control system gives the command to decrease speed and put the craft safely into the displacement or other safe mode should take account of the safety levels as given in section 2.4 of annex 3 and of the safe values of motions appropriate to the particular craft and service.
Demonstrations
The limits of safe use of any of the stabilization control system devices should be based on demonstrations and verification process in accordance with annex 8.
Demonstration in accordance with annex 8 should determine any adverse effects upon safe operation of the craft in the event of an uncontrollable total deflection of anyone control device. Any limitation on the operation of the craft as may be necessary to ensure that the redundancy or safeguards in the systems provide equivalent safety should be included in the craft operating manual.
W/1687n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)

---CHUNK---

SOURCE: MSC.36(63).pdf
ensure that the redundancy or safeguards in the systems provide equivalent safety should be included in the craft operating manual.
W/1687n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT 17.1
17.2
17 . 3
17.4
17.5
17.5.1
17.5.2
MSC 62/23/Add.2

CHAPTER 17 - HANDLING, CONTROLLABILITY AND PERFORMANCE
General
The operational safety of the craft in normal service conditions and in equipment failure situations of a craft to which this Code applies should be demonstrated by full-scale tests of the prototype craft. The objective of tests is to determine information to be included in the craft operating manual in relation to:
.1 handling and performance limitations;
. 2 actions to be taken in the event of prescribed failure; and
.3 limitations to be observed for safe operation subsequent to prescribed failures.
Proof of compliance
The information on controllability and manoeuvrability which should be contained in the operating manual should include the characteristics under 17.5, and the list of parameters of the

---CHUNK---

SOURCE: MSC.36(63).pdf
prescribed failures.
Proof of compliance
The information on controllability and manoeuvrability which should be contained in the operating manual should include the characteristics under 17.5, and the list of parameters of the worst intended conditions affecting the controllability and manoeuvrability according to 17.6 and the performance data verified in accordance with annex 8.
Weight and cen t r e of g ravity
Compliance with each of the handling, controllability and performance requirements should be established for all combinations of weight and centre of gravity position significant for the operational safety in the range of weights up to the maximum permissible weight.
Effect of failures
The effect of any likely failure in handling and control devices, services or components (e.g. power operation, power assistance, trimming and stability augmentation) should be assessed in order that a safe level of craft operation can be maintained. Effects of failure identified as being critical according to annex 4 should be verified in accordance with annex 8.
Con trollabilit y and man oe uv rability
Instructions to crew members should be provided in the craft

---CHUNK---

SOURCE: MSC.36(63).pdf
failure identified as being critical according to annex 4 should be verified in accordance with annex 8.
Con trollabilit y and man oe uv rability
Instructions to crew members should be provided in the craft operating manual regarding required actions and craft limitations subsequent to prescribed failures.

It is necessary to ensure that the effort required to operate
the controls in the worst intended conditions is not such that the
person at the control will be unduly fatigued or distracted by the
effort necessary to maintain the safe operation of the craft.
W/1687n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT MSC 62123/Add.2
ANNEX 18
Page 154
17.5.3 The craft should be controllable and be capable of performing those
manoeuvres essential to its safe operation up to the critical design
. conditions.
17.5.4.1 When determining the safety of a craft in respect of handling,
controllability and performance, the Administration should pay
particular attention to the following aspects during normal
operation and during and subsequent to failures:
.1 yawing;
.2 turning;

---CHUNK---